	WATER W	ELL RECORD F	orm WW	C-5 K	SA 82a-1212	2		
1 LOCATION OF WATER			SECT	ION NUMBER			RANGE NUI	
Sedgwick	SE 1/4	NE 1/4 SW	1/4	2	⊤ 27	S	R 2E	E/W
Distance and direction from nearest town or city street address of well if located within city?								
West side, Reserve G, Williamsgate & Ayesbury Wichita, Kansas								
2 WATER WELL OWNER: THE HAWTHORNE Board of Agriculture, Division of Water Resource								
RR#,ST. ADDRESS,B	5,BOX #: 350 N. Riverview Ste #610							alci resource
CITY, S	CITY, STATE: Wichita, Kansas ZIP CODE: Application Number:							
3 LOCATE WELL'S LOC		LETED WELL: 9	8 ft.		ELEVATION:			
WITH AN "X" IN SECTI	Depth of groundwater	Encountered:	ft.			ft.		ft.
	WELL'S STATIC WA	TER LEVEL 35	FT. BELO	W LAND SU	RFACE MEASUR	RED ON mo/d	ay/yr: 8/26/	05
Pump test data: Well water was ft. after hours of pumping @								gpm
1 1 1	Est. Yield:	gpm Well wa	ter was		ft. after	hours	of pumping @	gpm
w Mile	E Bore Hole Diameter	12 in.	to 9	8 ft.	and	in.	to	ft.
- A	WELL WATER TO B					9. Dewateri	ng 11. Injec	tion well
1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 12. Other (Specify below)								
2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well								
Was a chemical/bacteriological sample submitted to Department? YES NO ; If yes, what mo/day/yr was sample submitted was Was Water Well Disinfected? YES NO								
5 TVDE 05 0400	submitted						=	
5 TYPE OF CASIN	NG USED: 5. Wrought 3. RPM (SR)	Iron 7. Fiberglass	9. Ot	her (Specify	below) CASII	NG JOINTS: (Glued	Threaded
2. PVC	4. ABS 6. Asbestos	s-Cement 8. Concrete t	ile SDI	R-26			Welded	Clamped
	4. AB3			to	ft., D	ia.	in. to	ft.
Blank casing diameter	10	48 ft., Dia.	in.	to				и.
Casing height above land surface: 12 in., Weight: 2.35 lbs. / ft. Wall thickness or gauge No214								
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 5 Fiberglass 7, PVC 9, ABS 11. Other (specify)								
	Stainless Steel 5. Fiberglass	7. PVC	9. A				L - L - X	
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)								
SCREEN OR PERFORATION OPENINGS ARE:								
1. Continuous slot 3. Mill slot 5. Gauzed wrapped				7. Torch cut 9. Drilled holes 11. None (open hole			pen hole)	
2. Louvered shutter	4. Key punched 6. V	Vire wrapped	8. Sa	w cut	10. Other	r (specify)		
CODEEN DEDECORAT		48 ft. to	98		5			4
SCREEN - PERFORAT				ft.,	From	ft.	to	ft.
	From	ft. to		ft.,	From	ft.	to	ft.
GRAVEL PAC	KINTERVALS: From	24 ft. t	98	ft.,	From	ft.	to	ft.
	From	ft. t	0	ft.,	From	ft.	to	ft.
6 GROUT MATERIA	LS: 1. Neat cement	2. Cement Grout		Bentonite	(Other bent	onite hole plu	ıg
								ft.
What is the nearest sou	irce of possible contamination:						45 00	
1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well								
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below)								
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage								
Direction from well?	East				How mar	ny feet? 50 :		
From To	LITHOLOGI	CLOG	From	То		LITHOLO	GIC LOG	
0 4 1	topsoil							
	clay							
	shale		-					
65 98	shale and limestone		-					
			+					
			_					
							···· ··· · · · · · · · · · · · · · · ·	
7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and								
was completed on (mo/day/year) 8/26/2005 and this record is true to the best of my knowledge and belief.								
under the business name of Harp Well & Pump Service Inc. by (signature) Jo d d S. Harp								
					20	uu J.	July P	