WATER WELL RECORD F	orm WWC-5 K	SA 82a-1212	
1 LOCATION OF WATER WELL: FRACTION	SECTION NUMBER	· L	RANGE NUMBER
Sedgwick NE 1/4 NW 1/4 NW	1/4 11	T 27 S	R 2E E/W
Distance and direction from nearest town or city street address of well if located within city?			
2129 N. Glenwood Ct. Wichita, Kansas			
2 WATER WELL OWNER: RUDISILL, Ed		Roard of Acr	iculture, Division of Water Resource
RR#,ST. ADDRESS,BOX #: 2129 N. Glenwood Ct.		board or Agr	iculture, Division of Water Nesource
CITY, STATE: Wichita, Kansas	ZIP CODE:	Application Nur	mber:
3 LOCATE WELL'S LOCATION 4 DEPTH OF COMPLETED WELL: 80	ft.	ELEVATION:	
WITH AN "X" IN SECTION BOX: N Depth of groundwater Encountered:	ft.	ft.	ft.
WELL'S STATIC WATER LEVEL 30	FT. BELOW LAND SU	JRFACE MEASURED ON mo/o	day/yr: 9/12/05
Pump test data: Well wat	er was	ft. after hours	s of pumping @ gpm
	er was	ft. after hours	s of pumping @ gpm
Est. Yield: gpm Well wat Bore Hole Diameter 12 in.	to 80 ft.	and in.	to ft.
₩ELL WATER TO BE USED AS:		9. Dewateri	ng 11 Injection well
1. Domestic 3. Feedlot 5. Public wat	ter supply 7. Lawn a		12. Other (Specify below)
2. Irrigation 4. Industrial 6. Oil field w			ng well what mo/day/yr was sample
S Was a chemical/bacteriological sample submitted to D submitted		NO ; If yes, Vater Well Disinfected?	YES NO
TYPE OF CASING USED: 5. Wrought Iron 7. Fiberglass 1. Steel 3. RPM (SR)	Other (Specify	below) CASING JOINTS:	
2. PVC 4. ABS 6. Asbestos-Cement 8. Concrete til	le SDR-26		Welded Clamped
Blank casing diameter 5 in. to 40 ft., Dia.	in. to	ft., Dia.	in. to ft.
Tolgin.	2.35 lbs. / ft.	Wall thickness or gau	ge No214
TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC	9. ABS	11. Other (specify)	
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR)	10. Asbestos-Cer		hole)
	IV. ASDESIOS-CEI	nem 12. None used (open	Tible)
SCREEN OR PERFORATION OPENINGS ARE:			44 None (over bota)
1. Continuous slot 3. Mill slot 5. Gauzed wrapped	7. Torch cut	9. Drilled holes	11. None (open hole)
2. Louvered shutter 4. Key punched 6. Wire wrapped	8. Saw cut	10. Other (specify)	
SCREEN - PERFORATION INTERVAL From 40 ft. to	80 ft.,	From ft.	to ft.
From ft. to	•	From ft.	to ft.
GRAVEL PACK INTERVALS: From 24 ft. to		From ft.	to ft.
Tron	,	_	
	ft.,	From ft.	to ft.
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout	3. Bentonite	Other bent	tonite hole plug
Grout Intervals: From 4 ft. to 24 ft., From What is the nearest source of possible contamination:	ft. to	ft., From	ft. to ft.
1. Septic tank 4. Lateral lines 7. Pit privy	0. Livestock pens	13. Insecticide storage	15. Oil well/Gas well
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below)			
3. Watertight sewer line 6. Seepage pit 9. Feed yard 1 Direction from well? South	2. I el tilizer storage	How many feet? 15	
From To LITHOLOGIC LOG	From To	···	OGIC LOG
0 4 topsoil	110111 10	LITTIOL	7010 L00
4 15 clay			
15 70 shale			
70 80 limestone			
	 		
			-
7 Contractor's or Landowner's Certification: This water well was 1. constructed	2. reconstructe	d or 3, plugged	under my jurisdiction and
was completed on (mo/day/year) 9/12/2005 and this record is true to the best of my knowledge and belief.			
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 9/14/2005			
under the business name of Harp Well & Pump Service Inc. by (signature)			