*		WATE	R WELL	REC	CORD	Form	ww	/C-5 K	SA 82a-	1212				
1 LOCATION OF WAT	TER WELL:	FRACTION					SECT	ION NUMBER	R TOWN	ISHIP NU	MBER	R/	NGE NUN	IBER
Sedgwick		SE	1/4 S	SE 1	1/4 SW	1/4		2	T	27	S	R	2E	E/W
Distance and direction f		-			•									
Reserve A.,	21st St. North				ms Gate			Wichit	a, Kansa	<u>s</u>				
2 WATER WELL	OWNER: TH	E HAWT	HORNE	,							D1 -			
RR#,ST. ADDRES	SS,BOX #: 350	0 N. Rivery	view Ste	#610						,	Board of A	griculture, Divi	sion of wa	ter Resource
CIT	, STATE: Wi	ichita, Kan	sas				ZIF	CODE:		Ap	plication N	umber:		
3 LOCATE WELL'S	LOCATION 4	DEPTH OF	COMPLET	ED WE	LL: {	35	ft.		ELEVATIO	N:				
WITH AN "X" IN S	lr.	 Depth of groun	dwater End	countere	ed:		ft.				ft.			ft.
		WELL'S STAT				FT I		W I AND SI	JRFACE ME	ASI IDEI		n/day/vr	9/19/	
		WELLO O'IA	Pump te			ater was		II LAND SC	ft. after			rs of pumpir		
WW	NE	Est. Yield		gpm		ater was			ft. after			irs of pumpir	-	gp gpr
w Mile		Bore Hole Dia	-	12	in.		to 8	5 ft.			in.	ns or pumpa	to	gpi ft.
-		WELL WATER						. 11.	anu					
sw	s E	1. Domestic				ater su	vlaa	7. Lawn a	and garden		. Dewate		1. Inject	
	: I I	2. Irrigation		ustrial	6. Oil field				ditioning		. Monito	اک. Ui ring well	ner (Spe	cify belov
1		Was a chemica					• • •	YES	NO	```		, what mo/d	ay/yr wa	is sample
		submitted	an accomonog	rour ourrip		у Борини			Vater Well D	isinfecte	d?	YES	N	o .
5 TYPE OF CA	ASING USED:				2 =:		9 01	her (Specify	(below)	CASING	JOINTS	Glued		Threaded
1. Steel	3. RPM ((SR) 5. W	rought Iron		7. Fiberglas	S			below)	0.701110	301110	Welded		Clamped
2. PVC	4. ABS	6. As	sbestos-Cer	ment	8. Concrete	tile	SDF	₹-26						Janpeu
Blank casing diame	_	in.	to 40	ft.,	Dia.		in.	to	ft.,	Dia.		in.	to	ft.
		12	in	•	Maiabh	2.35								
Casing height abo					Weight:	4.33	Ю	s. / ft.	vva	ali tnickni	ess or ga	iuge No.	.214	
TYPE OF SCREEN 1. Steel	3. Stainless Steel				7. PVC		9. A	26	11	. Other (snecify)			
			crete Tile		8. RMP (SR)			sbestos-Cer				n haia)		
2. Brass	4. Galvanized	o. Con	crete the		o. KIVIF (SK)		10. A	spesios-Cei	nent 12	. None t	ısed (ope	ii noie)		
SCREEN OR PERI	FORATION OPEN	INGS ARE:												
1. Continuous si	ot 3. Mili	slot	5. Gauz	ed wra	pped		7. To r	ch cut	9.	Drilled h	oles	11. N	one (op	en hole)
2. Louvered shut	tter 4. Key	punched	6. Wire	wrappe	ed		8. Sa v	w cut	10.	Other (s	pecify)			
SCREEN - PERFO	DATION INITEDIA	L From	,	40 ft		:o	85	4	From					
SCREEN - PERFO	CATION INTERVA						03	ft.,			ft.		to	ft.
		From		fl		o		ft.,	From		ft.		to	ft.
GRAVEL F	ACK INTERVALS	: From	7	24 ft	t.	to :	85	ft.,	. From		ft.		to	ft.
		From		ft	t.	to		ft.,	From		ft.		to	ft.
G GROUT MATE	RIALS: 1 No.	at cement	2	Camai	nt Grout			Bentonite		Oth	er her	ntonite h	de nlu	
Grout Intervals:		4 ft.	to 24				ft.					ft.	- '	_
What is the nearest		•		• 11.	, 110111		H.	to	ft.	, ,	rom	ıı.	to	ft.
1. Septic tank		ral lines	7. Pit	privy		10. Liv	estoc	k pens	13. ins	ecticide	storage	15. O i	well/Ga	s well
2. Sewer lines	5. Ces :	s Pool	8. Sev	wage la	goon	11. Fu	el stor	age	14. Ab	andon v	vater we	ll 16. Ot	her (spe	cify below
		page pit	9 Fee	ed yard		12. Fer	rtilizer	storage						
3. Watertight sev		hage bit	0.100	ou yunu				otorugo	Hov	w many f	eet? 50) ft. plus		
From To	1101111	LITHOL	OGIC I	റദ		T En	om	То	1,00			OGIC LO	<u> </u>	
0 3	tonsoil	LITTIOL	OGIC L	<u> </u>		+ ' ' '	OIII	10			ITTIOL	OGIC LO	<u></u>	
3 7	topsoil clay					+								
7 40	tan shale					_								
40 60	gray shale					_								
60 85	gypsum-gr	av shala_hl	ackehala	_lima	etono	_						•		
102	- gypanii-gr	ay snarc-m	ACKSHAR		SLUILE									
7 Contractor's c	r Landowner's Cer	rtification: This	water well	was 1 (constructe	a) 2	rec	constructed	d or 3.	plug	ged	under my	urisdictio	n and
was completed of		9-19-										,		
,				а	nd this recor				_					
Kansas Water W	ell Contractor's Lic	ense No.	236		This water	well reco	ord wa	s completed	d on (mo/day	/year)	9-2	21-2005		
under the busine	ss name of Har	p Well & I	Pump Se	rvice	Inc.		by (sig	gnature)		7 1	110	. Har		
1		-	-							10 d	a.)	Mr. r.	2	