		WATER W	ELL REC	ORD F	Form W\	VC-5 K	(SA 82a-12	212			
1 LOCATION OF WAT	FRACTION				SECTION NUMBER		TOWNSHIP NUMBER		RANGE NUMBER		
Sedgwick  Distance and direction from	om nearest town or city	NE 1/4	- 11	/4 NE	1/4	8	<u> </u>	<b>27</b> s	R	<u> 2E</u>	E/W
2134 Keenlar			, Kansas	ony							
2 WATER WELL OWNER: RITCHIE BUILDER											
RR#,ST. ADDRES		E. 22nd St. N	N. Bldg.10	00				Board of Ag	griculture, Division	of Wate	r Resource
CITY		hita, Kansas				IP CODE:		Application No	umber:		
3 LOCATE WELL'S L	OCATION 4	DEPTH OF COMP	PLETED WEL	.L: 8	O ft.		ELEVATION	:			
N N	Dep	pth of groundwate			f			ft.			ft.
		ELL'S STATIC WA		30		OW LAND S		SURED ON mo	,,	9/29/0 -	
NW	NE	Pu Est. Yield:	mp test data:	Well wa Well wa			ft. after ft. after		rs of pumping (	_	gpm
w Miles	E B	ore Hole Diameter	gpm r 12	in.	to	<b>80</b> ft		in.	rs of pumping ( to	_	gpm ft.
=	,	ELL WATER TO E	BE USED AS:					9 Dewate	44		on well
sw	1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 12. Other (Specify below)										
		•		6. Oil field w		-		10. Monitor	•	hr was	cample
Was a chemical/bacteriological sample submitted to Department? YES NO ; If yes, what mo/day/yr was sample submitted Was Water Well Disinfected? YES NO											
5 TYPE OF CA	SING USED:	5 Wrough	lron	7 Eiberglass	9. 0	ther (Specif	v below) C/	ASING JOINTS:	Glued	T	hreaded
1. Steel 3. RPM (SR) Weided Clamped											
2. PVC	4. ABS	6. Asbesto		8. Concrete t	ile 515	10-20					
Blank casing diame	ter 5	in. to	40 ft.,	Dia.	in.	to	ft.,	Dia.	in. to		ft.
Casing height abov		12 in.,		Weight:	2.35	bs. / ft.	Wall	thickness or ga	uge No2	214	
TYPE OF SCREEN OR PERFORATION MATERIAL:  1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)											
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)  2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)											
SCREEN OR PERFORATION OPENINGS ARE:  1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole)											
2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify)											
								mer (specify)			
SCREEN - PERFOR	ATION INTERVAL	From	<b>40</b> ft.			ft.,	From	ft.	to		ft.
25.1/5/ 5		From	ft.	-		ft.,	From	ft.	to		ft.
GRAVEL PA	ACK INTERVALS:	From	<b>24</b> ft.			ft.,	From	ft.	to		ft.
		From	ft.	to	· · · · · · · · · · · · · · · · · · ·	ft.,	From	ft.	to		ft.
GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hole plug Grout Intervals: From 4 ft. to 24 ft. From ft to ft From ft to											
What is the nearest s		ontamination:		From	ft.	to	ft.,	From	ft.	to	ft.
1. Septic tank	4. Lateral	l lines 7	7. Pit privy	•	10. Livesto	ck pens	13. <b>Inse</b>	cticide storage			
2. Sewer lines	5. Cess P	ool 8	s. Sewage lag	joon	11. Fuel sto	rage	14. Abar	ndon water wel	l 16. Other	(spec	ify below)
③ Watertight sew		ge pit 9	. Feed yard		12. Fertilize	r storage					
Direction from well? South					1 =	T =	How	many feet? 50			
From To		LITHOLOGIC	CLOG		From	To_		LITHOL	OGIC LOG	<u></u>	
$\begin{array}{c c} 0 & 3 \\ \hline 3 & 7 \end{array}$	topsoil clay					<del>                                     </del>					
7 35	tan shale										
35 60	gray shale										
60 80	gypsum-gray	shale			-	<del> </del>					
	<del>                                     </del>				1	1					
	1					-					
<del>                                     </del>	+					-					
											700
	1				L	1	L				
7 Contractor's or	Landowner's Certific			constructed	2. re	constructe	<b>d</b> or 3.	plugged	under my juris	diction	and
was completed on	(mo/day/year)	9/29/2005	an	d this record	is true to th	e best of my	knowledge and	d belief.			
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 9/30/2005											
under the business	s name of Harp	Well & Pumj	Service I	nc.	by (s	ignature)	c	7011 5	Д		