

WATER WELL RECORD

orm WWC-

Division of Water Resources; App. No.

1 LOCATION OF WATER WELL:

County: SEDGWICK

Fraction

NE SE SE SW

Section Number

Township Number

Range Number

Distance and direction from nearest town or city street address of well if located within city? 1440 FREEDOM RD. WICHITA, KS

Global Positioning Systems (decimal degrees, min. of 4 digits)

Latitude:

Longitude:

Elevation:


Datum:

Data Collection Method:

2 WATER WELL OWNER:

RR#, St. Address, Box # : 1202 N. ANDOVER RD.
City, State, ZIP Code : ANDOVER KS, 67002

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:



4 DEPTH OF COMPLETED WELL 107 ft.

Depth(s) Groundwater Encountered (1) ft. (2) ft. (3) ft.
WELL'S STATIC WATER LEVEL 25 ft. below land surface measured on mo/day/yr.....Pump test data: Well water was ft. after hours pumping gpm
Est. Yield 20 gpm: Well water was ft. after hours pumping gpmWELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring wellWas a chemical/bacteriological sample submitted to Department? Yes No ☒; If yes, mo/day/yr
Sample was submitted Water well disinfected? Yes ☒ No

5 TYPE OF CASING USED:

1 Steel 3 RMP (SR)
2 PVC 4 ABS5 Wrought Iron 6 Asbestos-Cement
7 Fiberglass

8 Concrete tile 9 Other (specify below)

CASING JOINTS: Glued ☒ Clamped
Welded
ThreadedBlank casing diameter 5 in. to 20 ft., Diameter in. to ft., Diameter in. to ft.
Casing height above land surface 12 in., Weight 2-40 lbs./ft. Wall thickness or guage No. 160 NF

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel 3 Stainless Steel 5 Fiberglass 7 PVC 9 ABS 11 Other (Specify)
2 Brass 4 Galvanized Steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot 2 Mill slot 3 Guazed wrapped 4 Torch cut 5 Drilled holes 6 None (open hole)
7 Louvered shutter 8 Key punched 9 Wire wrapped 10 Saw Cut 11 Other (specify)

SCREEN-PERFORATED INTERVALS: From 20 ft. to 107 ft., From ft. to ft.

From ft. to ft., From ft. to ft.

GRAVEL PACK INTERVALS: From 20 ft. to 107 ft., From ft. to ft.

From ft. to ft., From ft. to ft.

6 GROUT MATERIAL:

1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 20 ft. to 107 ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 13 Insecticide Storage 16 Other (specify below)
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 14 Abandoned water well
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer Storage 15 Oil well/gas well

Direction from well? W How many feet? 10

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1	TOP SOIL			
1	3	CLAY			
3	45	LIME STONE			
45	107	SHALE			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-29-05 and this record is true to the best of my knowledge and belief.
Kansas Water Well Contractor's License No. 740 This Water Well Record was completed on (mo/day/year) 11-5-05
under the business name of WENWICK DRILLING, INC. by (signature)

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well. Visit us at <http://www.kdhe.state.ks.us/geo/waterwells>.