	WATER WELL RE	ECORD F	orm WW	/C-5 KS	SA 82a-121	2		
1 LOCATION OF WATER WELL:	FRACTION		SECT	ION NUMBER			RANGE NUM	BER
Sedgwick	NE 1/4 NE	1/4 SW	1/4	2	т 27	S	R 2E	E/W
Distance and direction from nearest town or city:		•						
2546 N. Rosemont Circle WATER WELL OWNER: MAS	Wichita, K STERPIECE HOME							
	9 SW Butler Rd.	<i>.</i> S				Board of Agric	culture, Division of Wat	er Resource
	hill, Kansas		71	P CODE:		Application Num	her:	
	DEPTH OF COMPLETED W	VELL: 80		OODL.	ELEVATION:	трриосион ти		
→ WITH AN "X" IN SECTION BOX:	pth of groundwater Encounter		ft.			ft.		ft.
	ELL'S STATIC WATER LEV			WI WID SIN	RFACE MEASU		av/vr: 11/19/	
NW	Pump test da			W LAND 30	ft. after		of pumping @	gpm
	Est. Yield: gpm	Well water			ft. after		of pumping @	gpm
₩ E Bo	ore Hole Diameter 12	2 in.	to 8	0 ft.	and	in.	to	ft.
1 000 1 0 1	ELL WATER TO BE USED					9. Dewaterir	ng 11. Injecti	on well
	. Domestic 3. Feedlot				nd garden only	10. Monitorin	12. Other (Spe	cify below)
	l. Irrigation 4. Industria Vas a chemical/bacteriological sa			YES	NO		what mo/day/yr wa	s sample
•	bmitted	imple submitted to be	opartment:		ater Well Disinfe		YES NO	
TYPE OF CASING USED:	5. Wrought Iron	7. Fiberglass	9. Ot	her (Specify	below) CASI	NG JOINTS: (Glued T	hreaded
1. Steel 3. RPM (SR	₹)		SDF	R-26	,		Welded	Clamped
2. PVC 4. ABS	6. Asbestos-Cement		5	20				
•	in. to 40 ft.		in.	to	ft., C)ia. i	n, to	ft.
Casing height above land surface:	12 _{in.,}	Weight:	2.35 lb	s. / ft.	Wall thic	kness or gaug	e No214	
TYPE OF SCREEN OR PERFORATION 1. Steel 3. Stainless Steel		7. PVC	9. Al		11 Oth	er (specify)		
Steel Stainless Steel Brass 4. Galvanized	 Fiberglass Concrete Tile 	8. RMP (SR)		sbestos-Cem		er (specify) ne used (open l	hole)	
		o. 1 (01)	10.7	3003103-0011	12.1101	o dood (opon i	110.07	
SCREEN OR PERFORATION OPENING 1. Continuous slot 3. Mill slo		ranned	7 To r	rch cut	9. Drille	d holes	11. None (ope	en hole)
		• •					· · · · · · · · · · · · · · · · · · ·	,
, p.		ppea	8. Sav	w cut	10. Otne	r (specify)		
SCREEN - PERFORATION INTERVAL	From 40	ft. to	80	ft.,	From	ft.	to	ft.
	From	ft. to		ft.,	From	ft.	to	ft.
GRAVEL PACK INTERVALS:	From 24	ft. to	80	ft.,	From	ft.	to	ft.
	From	ft. to		ft.,	From	ft.	to	ft.
GROUT MATERIALS: 1. Neat of	cement 2. Cen	nent Grout	3	. Bentonite	(Other bent	onite hole plug	
Grout Intervals: From 4	ft. to 24	ft., From	ft.	to	ft.,	From	ft. to	ft.
What is the nearest source of possible co 1. Septic tank 4. Lateral	7 Did mais a	, 10	. Livestoci	k pens	13. Insectio	ide storage	15. Oil well/Gas	s well
1. Septic tank 4. Lateral lines 7. Fit privy 10. Livestock pens 13. Insecticide storage 15. Oil wein das weil 2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below							ify below)	
3. Watertight sewer line 6. Seepag		•	2. Fertilizer	-	,			
Direction from well? North	ge pit				How mar	ny feet? 12		
From To I	LITHOLOGIC LOG		From	To		LITHOLO	GIC LOG	
0 3 topsoil								
3 10 clay	27 L							
10 35 tan shale 35 65 gray shale								
35 65 gray shale 65 80 gypsum-gray	shale							
9/1								
	- Tank							
		-						
7								
7 Contractor's or Landowner's Certific				constructed			under my jurisdiction	1 and
was completed on (mo/day/year)	11/19/2005	and this record is	s true to the	best of my k	nowledge and be	elief.		
Kansas Water Well Contractor's Licens	se No. 236	This water wel	Il record was	s completed	on (mo/day/year	11/2	23/05	
under the business name of Harp	Well & Pump Servic	e Inc.	by (sig	gnature)	7	11 9	11	

Jodd S. Harp