

1	LOCATION OF WATER WELL: Sedgwick	FRACTION SE 1/4 SW 1/4 NW 1/4	SECTION NUMBER 11	TOWNSHIP NUMBER T 27 S	RANGE NUMBER R 2E E/W
---	--	---	-----------------------------	----------------------------------	---------------------------------

1822 N. Peckham Wichita, Kansas

2	WATER WELL OWNER:	INK CONSTRUCTION		Board of Agriculture, Division of Water Resource
	RR#,ST. ADDRESS,BOX #:	240 N. Rock Road Ste.#104		
	CITY, STATE:	Wichita, Kansas	ZIP CODE:	Application Number:

3	LOCATE WELL'S LOCATION	4	DEPTH OF COMPLETED WELL: 95 ft.	ELEVATION:
---	------------------------	---	---------------------------------	------------

WITH AN "X" IN SECTION BOX:

1 Mile		N		ft.	
		W	E	ft.	ft.
		NW	NE		
		SW	SE		
		S			

Depth of groundwater Encountered: 30 ft. BELOW LAND SURFACE MEASURED ON 11/18/05

WELL'S STATIC WATER LEVEL

Pump test data: Well water was _____ ft. after _____ hours of pumping @ _____ gpm

Est. Yield: _____ gpm Well water was _____ ft. after _____ hours of pumping @ _____ gpm

Bore Hole Diameter 12 in. to 95 ft. and _____ in. to _____ ft.

WELL WATER TO BE USED AS:

1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 9. Dewatering 11. Injection well

2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well 12. Other (Specify below)

Was a chemical/bacteriological sample submitted to Department? YES NO ; If yes, what mo/day/yr was sample submitted

Was Water Well Disinfected? YES NO

5		TYPE OF CASING USED:				CASING JOINTS:		<input checked="" type="radio"/> Glued <input type="radio"/> Welded		<input type="radio"/> Threaded <input type="radio"/> Clamped	
1. Steel		3. RPM (SR)		5. Wrought iron		7. Fiberglass		9. Other (Specify below)			
2. PVC		4. ABS		6. Asbestos-Cement		8. Concrete tile					
Blank casing diameter		5 in.		to 40 ft.,		Dia. in.		to ft.,		Dia. in. to ft.	
Casing height above land surface:		12 in.,		Weight:		2.35 lbs. / ft.		Wall thickness or gauge No.		.214	
TYPE OF SCREEN OR PERFORATION MATERIAL:											
1. Steel		3. Stainless Steel		5. Fiberglass		7. PVC		9. ABS		11. Other (specify)	
2. Brass		4. Galvanized		6. Concrete Tile		8. RMP (SR)		10. Asbestos-Cement		12. None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:											
1. Continuous slot		3. Mill slot		5. Gauzed wrapped		7. Torch cut		9. Drilled holes		11. None (open hole)	
2. Louvered shutter		4. Key punched		6. Wire wrapped		8. Saw cut		10. Other (specify)			
SCREEN - PERFORATION INTERVAL		From		40 ft.		to 95 ft.,		From ft.		to ft.	
		From		ft.		to ft.,		From ft.		to ft.	
GRAVEL PACK INTERVALS:		From		24 ft.		to 95 ft.,		From ft.		to ft.	
		From		ft.		to ft.,		From ft.		to ft.	

6	GROUT MATERIALS:		1. Neat cement		2. Cement Grout		3. Bentonite		Other		bentonite hole plug		
	Grout Intervals:	From	4	ft.	to	24	ft.	From	ft.	to	ft.	ft.	
What is the nearest source of possible contamination:													
1. Septic tank			4. Lateral lines			7. Pit privy			10. Livestock pens			13. Insecticide storage	
2. Sewer lines			5. Cess Pool			8. Sewage lagoon			11. Fuel storage			14. Abandon water well	
3. Watertight sewer line			6. Seepage pit			9. Feed yard			12. Fertilizer storage			15. Oil well/Gas well	
Direction from well?			East						How many feet?			25	
												16. Other (specify below)	

[illegible]

7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. **reconstructed** or 3. **plugged** under my jurisdiction and was completed on (mo/day/year) **11/18/2005** and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. **236** This water well record was completed on (mo/day/year) **11-23-2005**

under the business name of **Harp Well & Pump Service Inc.** by (signature) *Jo dd S. Harp*