	orm WWC-5 K	SA 82a-1212	
1 LOCATION OF WATER WELL: FRACTION	SECTION NUMBER		RANGE NUMBER
Sedgwick NE 1/4 NE 1/4 NW	1/4 11	T 27 S	R 2E E/W
Distance and direction from nearest town or city street address of well if located within city?  Contar, of Crooked Pine and contar of Clearance!			
Center of Crooked Pine andcenter of Clearcreek  NATER WELL OWNER: RITCHIE DEVELOPMENT			
	Board of Agriculture Division of Water Resource		
CITY, STATE: Wichita, Kansas	ZIP CODE:	Application Number:	
3 LOCATE WELL'S LOCATION 4 DEPTH OF COMPLETED WELL: 98		ELEVATION:	
WITH AN "X" IN SECTION BOX:	ft.	ft.	ft.
WELL'S STATIC WATER LEVEL 25		IRFACE MEASURED ON mo/o	
Pump test data: Well water			s of pumping @ gpm
Ny NE			s of pumping @ gpm
Est. Yield: gpm Well wate Bore Hole Diameter 12 in.	to <b>98</b> ft.		to ft.
▼ WELL WATER TO BE USED AS:		9. Dewateri	ng 11. Injection well
1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 12. Other (Specify below)			
2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well  Was a chemical/bacteriological sample submitted to Denathment? VES NO ; If yes, what mo/day/yr was sample			
Was a chemical/bacteriological sample submitted to Department? YES NO ; if yes, what mo/day/yr was sample submitted was Water Well Disinfected? YES NO			
TYPE OF CASING LISED:			Glued Threaded
5. Wrought Iron 7. Fiberglass 7. Steel 3. RPM (SR)	9. Other (Specify	DEION) CHOING JOINTS:	Welded Clamped
2. PVC 4. ABS 6. Asbestos-Cement 8. Concrete til	<sub>e</sub> SDR-26		sides Sidiffed
Blank casing diameter 5 in. to 28 ft., Dia.	in. to	ft., Dia.	in. to ft.
Casing height above land surface: 24 in., Weight:	2.35 lbs. / ft.	Wall thickness or gau	ge No214
TYPE OF SCREEN OR PERFORATION MATERIAL:			
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC	9. ABS	11. Other (specify)	
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:			
1. Continuous slot 3. Mill slot 5. Gauzed wrapped	7. Torch cut	9. Drilled holes	11. None ( open hole)
2. Louvered shutter 4. Key punched 6. Wire wrapped	8. Saw cut	10. Other (specify)	
20	98 ft.	_	_
SCREEN - PERFORATION INTERVAL From 28 ft. to	,	From ft.	to ft.
From ft. to	ft.,	From ft.	to ft.
GRAVEL PACK INTERVALS: From 24 ft. to	<b>98</b> ft.,	From ft.	to ft.
From ft. to	ft.,	From ft.	to ft.
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout	3. Bentonite	Other bent	tonite hole plug
Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft.			
What is the nearest source of possible contamination:  1. Seption tank 4. Lateral lines 7. Pit privy 1	0. Livestock pens	13. Insecticide storage	15. Oil well/Gas well
1. Septic tank 4. Lateral lines 4. Source larger 11 First storage 14 Abandon water well 16. Other (specify below)			
2. Sewer lines 5. Cess root			
S. Watertight sewer line S. Scape of the	2. Fertilizer storage	How many feet? 12	
From To LITHOLOGIC LOG	From To		OGIC LOG
0 3 topsoil	7,011	LITTOE	
3 10 clay			
10 55 gray shale			
55 98 gypsum/limestone/gray shale			
	<del>                                     </del>		
7		d or 2 plumped	under my juriediction and
Contractor's or Landowner's Certification: This water well was 1. constructed 2, reconstructed or 3, plugged under my jurisdiction and			
was completed on (mo/day/year) 1/23/2006 and this record is true to the best of my knowledge and belief.			
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 1/25/2006			
under the business name of Harp Well & Pump Service Inc. by (signature)			
		10 d d	C-EV # 10