	WATER	R WELL RECOR	RD For	rm WW	/C-5 K	SA 82a-12 ⁻	12			
1 LOCATION OF WATER WE	į.				ION NUMBER		PNUMBER	RANGE N		
Sedgwick	NE NE	1/4 NW 1/4		1/4	2	Т 2	7 s	R 21	E/W	
	rest town or city street address of		ſ?							
12927 Mainsgate 2 WATER WELL OWN		hita, Kansas								
RR#,ST. ADDRESS,BOX							Board of Agric	culture, Division of V	Vater Resource	
	CITY, STATE: Wichita, Kansas						Application Num	ber:		
3 LOCATE WELL'S LOCATI	ON 4 DEPTH OF C	OMPLETED WELL:	80	ft.	P CODE:	ELEVATION:				
WITH AN "X" IN SECTION	IBOX:	water Encountered:		ft.			ft.		ft.	
	—	WATER LEVEL	30 F	T. BELO	W LAND SU	IRFACE MEASU	JRED ON mo/d	ay/yr: 3/2	/06	
NWNE	<u></u>	Pump test data:	Well water	was		ft. after	hours	of pumping @	gpm	
w Z w	Est. Yield:	gpm	Well water	was		ft. after	hours	of pumping @	gpm	
	E Bore Hole Dian			to 8	0 ft.	and	in.	to	ft.	
swsE		TO BE USED AS: 3. Feedlot 5. F	Public water	sunniv (7. Lawn a	and garden only	9. Dewaterii	יש	ction well	
	2. Irrigation		Dil field wate				10. Monitorin	12. Other (S _i ig well	pecity below	
S S		bacteriological sample sul			YES	NO		vhat mo/day/yr v		
	submitted				Was V	Vater Well Disin	fected? (YES)	NO	
5 TYPE OF CASING 1. Steel	USED: 3. RPM (SR) 5. Wro	ught Iron 7. F	iberglass	9. Ot	her (Specify	below) CAS	SING JOINTS: (Glued	Threaded	
2. PVC	. ,	estos-Cement 8. C	concrete tile	SDF	R-26			Welded	Clamped	
Blank casing diameter	5 in. to	40 ft.,	Dia.	in.	to	ft.,	Dia. i	n. to	ft.	
Casing height above land	12				s. / ft.	-	ickness or gaug		14.	
	ERFORATION MATERIAL:	,	agnt. 2 •	.55 10	S. / IL.	vvaii ui	ickness or gaug	e No214		
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC					3S	11. Ot	her (specify)			
2. Brass 4. Gal	lvanized 6. Concre	ete Tile 8. R	MP (SR)	10. As	sbestos-Cer	nent 12. No	one used (open	hole)		
SCREEN OR PERFORAT	ION OPENINGS ARE:									
1. Continuous slot 3. Mill slot 5. Gauzed wrapped				7. Torch cut 9. Drilled holes 11. None (open hole)					pen hole)	
2. Louvered shutter	4. Key punched	6. Wire wrapped		(8. Sav	v cut	10. Oth	er (specify)			
SCREEN - PERFORATION	NINTERVAL From	40 ft.	to	80	ft.,	From	ft,	to	ft.	
	From	ft.	to		ft.,	From	ft.	to	ft.	
GRAVEL PACK IN	NTERVALS: From	24 ft.	to	80	ft.,	From	ft.	to	ft.	
	From	ft.	to		ft.,	From	ft.	to	ft.	
6 GROUT MATERIALS:	1. Neat cement	2. Cement Gr	·out	2	. Bentonite			onite hole pla		
-	rom 4 ft.	to 24 ft.,	From	ft.	to	ft.,	From	ft. to	45 ft.	
What is the nearest source	of possible contamination:		10							
1. Septic tank 4. Lateral lines					Livestock pens 13. Insecticide			40 Other (ifbelow)		
2. Sewer lines	5. Cess Pool	8. Sewage lagoon		Fuel stor	-	14. Aband	on water well	io. Other (sp	ecity below,	
O Watertight sewer line Direction from well?	6. Seepage pit North	9. Feed yard	12.	Fertilizer	storage	How m	any feet? 50 f	oot plus		
From To	LITHOLO	GICLOG		From	То	HOW ITIE	LITHOLO			
	soil	010 200		110111	-10		LITTIOLO	OIO LOG		
3 10 cla										
	shale									
	y shale									
50 80 gyr	osum/gray shale/lime	estone								
			-							
·										
ļl	···									
Contractor's or Lando	owner's Certification: This w	vater well was 1. cor	nstructed	2. red	onstructed	or 3.	plugged (under my jurisdict	ion and	
was completed on (mo/o	day/year) 3/2/20	06 and th	is record is t	rue to the	best of my	knowledge and l	belief.			
Kansas Water Well Cont	tractor's License No.	236 This	water well r	ecord was	s completed	on (mo/day/yea	ar) 3/6/2	2006		
under the business name	e of Harp Well & Pu	ımp Service Inc.		by (sic	nature)	a	110	11		
	The state of the s	THE		, , , ,	,	1,	dd S.	Harn		