			WAIERV	VELL REC	ORD F	orm WV	VC-5 K	SA 82a-12	12		
111	N OF WATE	R WELL:	FRACTION				TION NUMBER			RANGE N	
Sedgy			NE 1/4		/4 SE	1/4	2	Т 2	7 S	R 21	C E/W
Distance and direction from nearest town or city street address of well if located within city? Reserve B Just East of 14320 E. 24th Wichita, Kansas											
						sas					
2 WATER WELL OWNER: RITCHIE DEVELOPMENT RR#,ST. ADDRESS,BOX #: 8100 E. 22nd St. N. Suite 1000 Board of Agriculture, Division of Water Resource											
',			ita, Kansas	THI DUILE IN	,,,,	71	P CODE:		Application Num	ber:	
3 LOCAT	E WELL'S LO		DEPTH OF COM	IPLETED WEL	95		T OODL.	ELEVATION:			
WITH A	N "X" IN SEC	TION BOX:	oth of groundwa			ft.			ft.		ft.
lı 🗁	N		ELL'S STATIC W					JRFACE MEASU		3/29	3/06
				ranck Level rump test data:			W LAND SU	ft. after		.,,	
0	- /	: NE	Est. Yield:	gpm	Well wat			ft. after		of pumping @ of pumping @	gpm gpm
W Wije		E B	ore Hole Diamet	٠	in.	to 9	95 ft.		in.	to	ft.
-		X WE	ELL WATER TO	BE USED AS:					9 Dewateri	44 1-1-	ction well
	- sw	SE 1.	Domestic	3. Feedlot	5. Public wat	ter supply	7. Lawn	and garden only		•	pecify below
2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well											
	S		/as a chemical/bac bmitted	teriological samp	le submitted to D	epartment?	YES	NO Water Well Disin		vhat mo/day/yr v	was sample NO
E TV	DE OE CAS	ING USED:	billitted							$\overline{}$	
\simeq	l. Steel	3. RPM (SF	5. Wroug	ht Iron	7. Fiberglass		ther (Specify	below) CAS	SING JOINTS: (Glued	Threaded
	2. PVC	> 4. ABS	•	os-Cement	8. Concrete til	e SD	R-26			Welded	Clamped
Blank cas	sing diamete	_	in. to	45 ft.,	Dia.	in.	to	ft.,	Dia. i	in. to	ft.
Casing h	eight ahove	land surface:	12 in		Weight:	2.35	he /ft	Wall th	ickness or gaug	se No. 214	
Casing height above land surface: 12 in., Weight: 2.35 lbs. / ft. Wall thickness or gauge No214 TYPE OF SCREEN OR PERFORATION MATERIAL:											
1. Stee		. Stainless Steel	5. Fiberglas	is C	7. PVC	9. A	BS	11. Ot	her (specify)		
2. Bras		. Galvanized	6. Concrete	Tile	B. RMP (SR)	10. A	sbestos-Ce	ment 12. No	one used (open	hole)	
SCREEN	OR PERFO	RATION OPENING	SS ADE:								
	nuous slot			. Gauzed wra	oped	7. To	rch cut	9. Dril	ed holes	11. None (open hole)
							w cut				
			uncned 0	. Wire wrappe	eu		WCut	10. 0111	er (specify)		
SCREEN -	- PERFORA	TION INTERVAL	From	45 ft	. to	95	ft.,	From	ft.	to	ft.
			From	ft	. to		ft.,	From	ft.	to	ft.
G	RAVEL PA	CK INTERVALS:	From	24 ft	. to	95	ft.,	From	ft.	to	ft.
			From	ft	to		ft.,	From	ft.	to	ft.
6 GROU	JT MATERI	ALS: 1. Neat	cement	2. Cemer	nt Grout		3. Bentonite		Other bent	onite hole pl	ug
Grout	Intervals:	From 4	ft. to			ft.	to	ft.,	From	ft. to	ft.
What is the nearest source of possible contamination:								Con wall			
1. Seption	c tank	4. Lateral	l lines						cticide storage 15. Oil well/Gas well		
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify bell pond pond											
	rtight sewe	r line 6. Seepa	ge pit	9. Feed yard	1	2. Fertilize	r storage			•	iiu
	from well?	South	LITUOL OO	10.1.00				How m	any feet? 50 f		
From	To		LITHOLOG	IC LOG		From	То		LITHOLO	GIC LOG	
3	8	topsoil clav		.			1				
8	65	tan shale/gra	v shale				<u> </u>		**************************************		
65	95	gray shale/ li									
			·			-	 			*** ·	
				-		 	 			·	
			"				Ì				
		<u></u>					<u> </u>				
7 Conf	tractor's or l	_andowner's Certific	cation: This wat	er well was 1.0	constructed) 2. re	constructe	d or 3.	plugged	under my jurisdic	tion and
was completed on (mo/day/year) 3/28/2006 and this record is true to the best of my knowledge and belief.											
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 3/31/2006											
under the business name of Harp Well & Pump Service Inc. by (signature) Jo d d S. Harp											