Form WWC-5 WATER WELL RECORD KSA 82a-1212 LOCATION OF WATER WELL: SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER T27 26 Sedgwick \mathbf{SW} NW11 **2E** E/W ΝW SE R 1/4 1/4 1/4 Distance and direction from nearest town or city street address of well if located within city? 13233 Bridlewood Wichita, Kansas ROBL CONSTRUCTION WATER WELL OWNER: Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: 5842 W. 21st St. N. CITY, STATE: Wichita, Kansas Application Number: ZIP CODE: 83 **ELEVATION:** 4 DEPTH OF COMPLETED WELL: ft. LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: ft ft. Depth of groundwater Encountered: ft. WELL'S STATIC WATER LEVEL 42 4/15/06 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: Pump test data: Well water was hours of pumping @ ft. after gpm NW ΝE Est. Yield: Well water was ft. after hours of pumping @ gpm gpm Φ ≌ 12 83 ft. Bore Hole Diameter in. and WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering 5. Public water supply 7. Lawn and garden only SW SE 3. Feedlot 1. Domestic 12. Other (Specify below) 6. Oil field water supply 8. Air conditioning 10. Monitoring well 2. Irrigation 4. Industrial ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO) Was Water Well Disinfected? (YES) submitted TYPE OF CASING USED: CASING JOINTS: Glued Threaded 9. Other (Specify below) 5. Wrought Iron 7. Fiberglass 3. RPM (SR) 1. Steel Welded Clamped SDR-26 8. Concrete tile 6. Asbestos-Cement 2. PVC 4. ABS Blank casing diameter 5 43 Dia. Dia. ft. in. 24 2.35 Casing height above land surface: in Weight: lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 11. Other (specify) 9 ARS 1. Steel 3. Stainless Steel 5. Fiberglass 8. RMP (SR) 12. None used (open hole) 2. Brass 4. Galvanized 6. Concrete Tile 10. Asbestos-Cement SCREEN OR PERFORATION OPENINGS ARE: 9. Drilled holes 11. None (open hole) 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify) SCREEN - PERFORATION INTERVAL 43 83 ft ft., From From to ft. to ft. From to ft., From ft. ft. 24 **GRAVEL PACK INTERVALS:** ft. to 83 From ft., From ft. ft. ft. From to From ft. ft. to **GROUT MATERIALS:** Other bentonite hole plug 1. Neat cement 2. Cement Grout 3. Bentonite Grout Intervals: From 4 ft. 24 ft., From ft. ft From to ft.. What is the nearest source of possible contamination: 10. Livestock pens 15. Oil well/Gas well 7. Pit privy 13. Insecticide storage 1. Septic tank 4. Lateral lines 16. Other (specify below) 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 2. Sewer lines 5. Cess Pool None Apparent 9. Feed yard 12. Fertilizer storage 6. Seepage pit 3. Watertight sewer line How many feet? 14 Direction from well? From LITHOLOGIC LOG LITHOLOGIC LOG Τо From To topsoil 10 clav 10 45 tan shale 45 83 limestone//gray shale

Contractor's or Landowner's Certification: This water well was 1. Constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 4/15/2006 and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 4/17/2006

under the business name of Harp Well & Pump Service Inc.

by (signature)

Jodd S. Harp