	WATER WELL RECORD FO	orm WWC-5 K	SA 82a-1212	
LOCATION OF WATER WELL:  Sedgwick	FRACTION NW 1/4 NE 1/4 SW	SECTION NUMBER	TOWNSHIP NUMBER T 27 S	RANGE NUMBER R 2E E/W
Distance and direction from nearest town or city	y street address of well if located within city?			74541
13104 E. Mainsgate Ct. Wichita, Kansas  2 WATER WELL OWNER: DAILEY				
2 WATER WELL OWNER: DAILEY RR#,ST. ADDRESS,BOX #: 13104 E. Mainsgate Ct.  Board of Agriculture, Division of Water Resource				
	hita, Kansas	ZIP CODE:	Application Nur	nber:
3 LOCATE WELL'S LOCATION 4 WITH AN "X" IN SECTION BOX:	DEPTH OF COMPLETED WELL: 70	ft.	ELEVATION:	
N De	epth of groundwater Encountered:	ft.	ft.	ft.
	ELL'S STATIC WATER LEVEL 30		RFACE MEASURED ON mo/o	
0NWNE	Pump test data: Well wate  Est. Yield: gpm Well wate			s of pumping @ gpm s of pumping @ gpm
E B	Bore Hole Diameter 12 in.	to <b>70</b> ft.		to ft.
-   <u> </u>	ELL WATER TO BE USED AS:  1. Domestic 3. Feedlot 5. Public wate	ar armely 7 Jawn a	9. Dewateri	•
1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 12. Other (Specify below 2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well				
S Was a chemical/bacteriological sample submitted to Department? YES NO ; If yes, what mo/day/yr was sample				
	ubmitted		Vater Well Disinfected?	YES NO
TYPE OF CASING USED:  1. Steel 3. RPM (SI	R) 5. Wrought Iron 7. Fiberglass	9. Other (Specify	below) CASING JOINTS:	Glued Threaded Welded Clamped
2. PVC 4. ABS	6. Asbestos-Cement 8. Concrete tile	SDR-26		Troises Claimpos
Blank casing diameter 5	in. to 30 ft., Dia.	in. to	ft., Dia.	in. to ft.
Casing height above land surface: 12 in., Weight: 2.35 lbs. / ft. Wall thickness or gauge No214				
TYPE OF SCREEN OR PERFORATION MATERIAL:  1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)				
2. Brass    4. Galvanized    6. Concrete Tile    8. RMP (SR)    10. Asbestos-Cement    12. None used (open hole)				
SCREEN OR PERFORATION OPENINGS ARE:				
1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11			11. None ( open hole)	
2. Louvered shutter 4. Key p	ounched 6. Wire wrapped	8. Saw cut	10. Other (specify)	
SCREEN - PERFORATION INTERVAL	From 30 ft. to	<b>70</b> ft.,	From ft.	to ft.
	From ft. to	ft.,	From ft.	to ft.
GRAVEL PACK INTERVALS:	From 24 ft. to	<b>70</b> ft.,	From ft.	to ft.
	From ft. to	ft.,	From ft.	to ft.
GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hole plug  Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to				
Grout Intervals: From 4 ft. to 24 ft., From What is the nearest source of possible contamination:			ft., From	ft. to ft.
1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock p			13. Insecticide storage	15. Oil well/Gas well 16. Other (specify below)
2. Sewer lines 5. Cess Pool 5. Sewer lines 5. Cess Pool 6. Sewer lines 5. Cess Pool 6. Sewer lines 6. Sewer lin				
Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage  Direction from well? South How many feet? 20 feet plus				
Birootion from work	LITHOLOGIC LOG	From To		OGIC LOG
0 3 topsoil				
3 7 clay 7 32 brown shale				
32 70 gray shale				
7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and				
was completed on (mo/day/year) 3/31/2006 and this record is true to the best of my knowledge and belief.				
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 4/3/2006				
under the business name of Harp Well & Pump Service Inc. by (signature)				