	WATER WELL RECORD Fo	orm WWC-5 K	SA 82a-1212	
1 LOCATION OF WATER WELL:	FRACTION	SECTION NUMBER	1	RANGE NUMBER
Sedgwick		1/4 1	T 27 S	R 2E E/W
Distance and direction from nearest town or city street address of well if located within city? 2525 N. 159th St. E. Wichita, Kansas				
2 WATER WELL OWNER: LEE, Doug				
	25 N. 159th St. E.		Board of Agr	riculture, Division of Water Resource
	chita, Kansas	ZIP CODE:	Application Nur	mber:
3 LOCATE WELL'S LOCATION 4	DEPTH OF COMPLETED WELL: 103	ft.	ELEVATION:	
WITH AN "X" IN SECTION BOX:	Depth of groundwater Encountered:	ft.	ft.	ft.
	WELL'S STATIC WATER LEVEL 52	FT. BELOW LAND SU	RFACE MEASURED ON mo/	day/yr: 4/21/06
N V	Pump test data: Well water	r was	ft. after hours	s of pumping @ gpm
W XE	Est. Yield: gpm Well wate	4.0.0		s of pumping @ gpm
	Bore Hole Diameter 12 in.	to 103 ft.		to ft.
swse	WELL WATER TO BE USED AS: 1. Domestic 3. Feedlot 5. Public wate	er supply 7. Lawn a	nd garden only 9. Dewater	•
		ter supply 8. Air con		12. Other (Specify below) ng well
S	Was a chemical/bacteriological sample submitted to De	epartment? YES	NO ; If yes,	what mo/day/yr was sample
	submitted	Was V	Vater Well Disinfected?	YES NO
TYPE OF CASING USED: 5. Wrought Iron 7. Fiberglass 9. Other (Specify below) CASING JOINTS: Glued Threaded 1. Steel 3. RPM (SR) Wolded Clarged				
2. PVC 4. ABS 6. Asbestos-Cement 8. Concrete tile SDR-26 Welded Clamped				
Blank casing diameter 5	in. to 43 ft., Dia .	in. to	ft., Dia.	in. to ft.
Casing height above land surface:	4.	2.35 lbs. / ft.		
Casing height above land surface: 12 in., Weight: 2.35 lbs. / ft. Wall thickness or gauge No214 TYPE OF SCREEN OR PERFORATION MATERIAL:				
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)				
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)				
SCREEN OR PERFORATION OPENINGS ARE:				
1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole)				
2. Louvered shutter 4. Key	punched 6. Wire wrapped	8. Saw cut	10. Other (specify)	
SCREEN - PERFORATION INTERVAL	L From 43 ft. to	103 ft.,	From ft	4. 4
	From ft. to	ft.,	From ft. From ft.	to ft.
GRAVEL PACK INTERVALS:		103 ft.,	From ft.	to ft.
0.0002217.0000001200	From ft. to	,	_	
6 GROUT MATERIALS: 1 No.		ft.,	16	to ft.
Count Integrals 5. Definite God 5. Bentoine Bottonic India				
Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination:				
			15. Oil well/Gas well	
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon v			14. Abandon water well	
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage None Apparent				
Direction from well?			How many feet?	
From To	LITHOLOGIC LOG	From To	LITHOLO	OGIC LOG
0 3 top soil 3 8 clay			***	
8 70 tan shale				
70 103 gray shale/	limestone			
7 Contractor's or Landowner's Cer	rtification: This water well was 1. constructed	2 reconstructed	i or 3. plugged	under my jurisdiction and
1/20/2006				
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 4/24/2006				
under the business name of Harp Well & Pump Service Inc. by (signature)				