		WATERW	ELL RECC	אט די	orm WW		SA 82a-121			
1 LOCATION OF WATER	R WELL:	FRACTION	NIE	. ~-		ION NUMBER	1		RANGE NU	
Sedgwick		SE 1/4	NE 1/4		1/4	10	T 2	7 S	R 2E	E/W
Distance and direction from	-			city?						
827 N. 127th E		Wichita, Ka	nsas							1
2 WATER WELL O		SNON, Ken						Board of Acri	cultura Division of 14	Jater Pesouses
RR#,ST. ADDRESS,		I. 127th E.						board of Agric	culture, Division of V	valer Resource
CITY, S	STATE: Wich	ita, Kansas			ZIF	CODE:		Application Num	nber:	
3 LOCATE WELL'S LOC	CATION 4 D	DEPTH OF COMP	LETED WELL	.: 87	ft.		ELEVATION:			
WITH AN "X" IN SEC	TION BOX:	th of groundwate			ft.			ft.		ft.
l I		LL'S STATIC WA				W I AND SH	RFACE MEASU		lav/vr: 4/20	
			mp test data:	Well wate		TAND 30	ft, after		-,,,	
	-NE	Est. Yield:					π. aπer ft. after		of pumping @ of pumping @	gpm
W Mile		est. Yield: ore Hole Diamete	дрт r 12	Well water	erwas to 8	7 ft.		in.	to	gpm ft.
£ "	' ! !	ELL WATER TO E		111.	ω σ	, it.	and		44 1-1-	τι. ction well
sw	_		Feedlot 5	5. Public wat	er supply '	7. Lawn a	nd garden only	> Dewateri	''9	pecify below)
	1			6. Oil field wa				10. Monitorir		pecity below)
	1	as a chemical/bacte				YES	NO		what mo/day/yr v	vas sample
		omitted					Vater Well Disinf	fected?	YES	NO
5 TYPE OF CASI	ING USED:	5 W/ss	lean 7	Liboralesa	9 Ot	her (Specify	below) CAS	ING JOINTS: (Glued	Threaded
1. Steel	3. RPM (SR	5. Wrought	i iiOii /	'. Fiberglass					Welded	Clamped
2. PVC	4 . ABS	Asbesto	s-Cement 8	3. Concrete tile	e SDF	R-26				
Blank casing diamete	r 5 i	in. to	32 ft.,	Dia.	in.	to	ft.,	Dia.	in. to	ft.
Casing height above	land surface.	24 in.,		Weight:	2.35 lb	os. / ft.	Wall th	ickness or gaug	ge No214	
TYPE OF SCREEN O		,		rroigitt.		75. 7 IL.	YVali (I)	onnos or yaut	,214	
	. Stainless Steel	5. Fiberglass	7	PVC	9. AI	BS	11. Ot	her (specify)		
	. Galvanized	6. Concrete		RMP (SR)		sbestos-Cer		ne used (open	hole)	
			0.	(511)	10. A				,	
SCREEN OR PERFO								lad bale -	44 Name (anan hala)
1. Continuous slot 3. Mill slot 5. Gauzed wrapped						7. Torch cut 9. Drilled holes 11. None (open hole)				
2. Louvered shutter	r 4. Key pu	unched 6.	Wire wrapped	l	8. Sa	w cut	10. Oth	er (specify)		
SCREEN - PERFORA	TION INTERVAL	From	32 ft.	to	87	ft.,	From	ft.	to	ft.
		From	ft.	to	-,	ft.,	From	ft.		
ODAYEL BA	OK INTERVALO:		24 ft.	to	87				to	ft.
GRAVEL PAC	CK INTERVALS:	From			0/	ft.,	From	ft.	to	ft.
		From	ft.	to		ft.,	From	ft.	to	ft.
6 GROUT MATERIA	ALS: 1. Neat of	cement	2. Cement	Grout	3	B. Bentonite		Other bent	onite hole pl	ug
Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft.										
What is the nearest source of possible contamination: 1 Sontic tank 4 Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/G.							Gae well			
1. Septic tank 4. Lateral lines						•		_		
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below										
3. Watertight sewe	r line 6. Seepag	ge pit	9. Feed yard	1	2. Fertilize	r storage				
Direction from well?	West						How m	any feet? 50		
From To		LITHOLOGI	C LOG		From	То		LITHOLO	OGIC LOG	
0 3	top soil									
3 10	clay									
10 50	tan shale							HIII		
50 65	gray shale					-				
65 87	gypsum/limes	stone/gray sh	ale		-					
					-	 				
		~								****
					-	 				
						-				
7 Contractor of	andowned Codific	ootion. This was	ruelluse 4				d or 2	nlugged	under my juriedic	tion and
	Landowner's Certific		,				d or 3.	plugged	under my jurisdid	ction and
7 Contractor's or I was completed on		cation: This wate 4/20/2006	,				d or 3.		under my jurisdic	etion and
	(mo/day/year)	4/20/2006	ó an	d this record	is true to the	e best of my		belief.	under my jurisdic	ction and
was completed on	(mo/day/year) Contractor's Licens	4/20/2006 se No. 2	6 an	d this record	is true to the	e best of my	knowledge and	belief.	4/2006	ction and