WATER WELL RECORD Form WWC-5 KSA 82a-1212 LOCATION OF WATER WELL: SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER Sedgwick 11 27 2EТ s R E/W 1/4 Distance and direction from nearest town or city street address of well if located within city? 1817 N. Glenwood Circle Wichita, Kansas ROBL CONSTRUCTION WATER WELL OWNER: Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: 5842 W. 21st St. N. Wichita, Kansas CITY, STATE: Application Number: ZIP CODE: 86 **ELEVATION:** 4 DEPTH OF COMPLETED WELL: LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: Depth of groundwater Encountered: ft. ft. 35 WELL'S STATIC WATER LEVEL FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: Pump test data: Well water was ft. after hours of pumping @ gpm NW. NE Est. Yield: Well water was ft. after hours of pumping @ gpm gpm 12 86 Ξ Bore Hole Diameter ft. in. and in. WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering 5. Public water supply 7. Lawn and garden only 9W SE-1. Domestic 3. Feedlot 12. Other (Specify below) 6. Oil field water supply 8. Air conditioning 10. Monitoring well 2. Irrigation 4. Industrial ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO submitted Was Water Well Disinfected? (YES) NO TYPE OF CASING USED: 5 CASING JOINTS: Glued Threaded 9. Other (Specify below) 7. Fiberglass 5. Wrought Iron 3. RPM (SR) 1. Steel Welded Clamped SDR-26 6. Asbestos-Cement 8. Concrete tile 2. PVC 4. ABS 5 Blank casing diameter 36 in to ft.. Dia. in. to ft.. Dia in. to ft. 24 Casing height above land surface: Weight: 2.35 lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 9. ABS 11. Other (specify) 3. Stainless Steel 5. Fiberglass 1. Steel 2. Brass 6. Concrete Tile 8. RMP (SR) 12. None used (open hole) 4. Galvanized 10. Asbestos-Cement SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 8. Saw cut 10. Other (specify) Wire wrapped 4. Key punched SCREEN - PERFORATION INTERVAL 36 ft. 86 From From to ft., ft. ft. From to From ft., ft. ft. 24 GRAVEL PACK INTERVALS: 86 to From ft., From to ft. From ft. to From ft. ft. to **GROUT MATERIALS:** Other bentonite hole plug 1. Neat cement 2. Cement Grout 3. Bentonite Grout Intervals: From 24 ft. From ft ft. From ft. to What is the nearest source of possible contamination: 10. Livestock pens 15. Oil well/Gas well 7. Pit privy 13. Insecticide storage 1. Septic tank 4. Lateral lines 16. Other (specify below) 11. Fuel storage 8. Sewage lagoon 14. Abandon water well 5. Cess Pool 2. Sewer lines 3. Watertight sewer line 9. Feed yard 12. Fertilizer storage 6. Seepage pit North Direction from well? How many feet? 22 LITHOLOGIC LOG LITHOLOGIC LOG From Tο From Tο topsoil 10 clav 10 tan shale 45 80 gray shale 80 gypsum/limestone under my jurisdiction and Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged

Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 5/08/2006 and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 5/10/2006

under the business name of Harp Well & Pump Service Inc.

by (signature)

Jodd S. Harp