			ELL RECOR	D For	m WW		SA 82a-12			
1 LOCATION OF WATER	R WELL:	FRACTION				ON NUMBER		P NUMBER	RANGE N	
Sedgwick		NE 1/4	SW 1/4		/4	2	Т 2	7 s	R 2E	E/W
Distance and direction from	-	street address of well	I if located within city?	•						
2320 N. Burni		Wichita, Ka	ansas							
2 WATER WELL C		NN, Andy						D	- 4	(-t F
RR#,ST. ADDRESS,BOX #: 2320 N. Burning Tree Board of Agriculture, Division of Water Resource										
CITY,	STATE: Wich	ita, Kansas			ZIF	CODE:		Application Num	nber:	
3 LOCATE WELL'S LO		EPTH OF COMP	LETED WELL:	102	ft.		ELEVATION:			
WITH AN "X" IN SEC		th of groundwater	r Encountered:		ft.			ft.		ft.
lı 		LL'S STATIC WA		50 F1		W I WND SII	DEACE MEASI	JRED ON mo/d	lav/vr: 6/9/	
				Well water v		V LAND 30	ft. after		,,	
	- NE	Est. Yield:	•				ft. after		of pumping @	gpm
w Mie		re Hole Diameter	٠,	Well water	was to 10	no <u>a</u>			of pumping @	gpm
2 "	,				ιο 1	02 ft.	and	in.	to	ft.
		LL WATER TO B Domestic 3.		ıblic water	sunnly S	7. Lawn a	nd garden onl	9. Dewateri	· · · · ·	ction well
	\sim 1 \sim					8. Air con		10. Monitorir		pecify below)
		_	riological sample subr			YES	NO		what mo/day/yr v	vas sample
•		mitted	norogical sample subi	mileo to Depe	artinent:		ater Well Disin			NO
5 TYPE OF CAS	ING USED:				9 04	ner (Specify		SING JOINTS: (Glued	Threaded
1. Steel	3. RPM (SR	5. Wrought	Iron 7. Fit	perglass			Delow) CA	JIING JUNING: N	Welded	Clamped
2. PVC	> 4. ABS	6. Asbestos	s-Cement 8. Co	ncrete tile	SDR	R-26			**GIUBU	Ciarriped
Blank casing diameter	_	in. to	55 ft.,	Dia.	in.	to	ft.,	Dia.	in. to	ft.
1		10		_						
Casing height above land surface: 12 in., Weight: 2.35 lbs. / ft. Wall thickness or gauge No214										
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)										
	. Stainless Steel	5. Fiberglass				-		ther (specify)		
2. Brass 4	. Galvanized	6. Concrete T	Γile 8. RM	P (SR)	10. As	sbestos-Cen	nent 12. No	one used (open	hole)	
SCREEN OR PERFO	RATION OPENING	SS ARE:								
1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open								open hole)		
2. Louvered shutte	er 4. Key pu	inched 6 \	Wire wrapped		(8. Sav	v cut	10. Oth	er (specify)		
							511	(Speeding)		
SCREEN - PERFORA	TION INTERVAL	From	55 ft.	to	102	ft.,	From	ft.	to	ft.
		From	ft.	to		ft.,	From	ft.	to	ft.
GRAVEL PA	CK INTERVALS:	From	24 ft.	to	102	ft.,	From	ft.	to	ft.
		From	ft.	to		ft.,	From	ft.	to	ft.
O COUTAGES	AI C									
GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hole plug										
Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft.										
What is the nearest source of possible contamination: 1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well								Sas well		
S Square larger 11 Fuel storage 14 Abandan water 16. Other (specify below)										
2. Sewer lines	5. Cess P	001	• •			_	14. ADANG	JOH WALET WELL	,	
3. Watertight sewe		ge pit 9	. Feed yard	12.	Fertilizer	storage				
Direction from well?	East	LITUOLOGY	0100			- -	How m	any feet? 15	010100	
From To		LITHOLOGIC	C LOG		From	То		LITHOLO	GIC LOG	
0 4	topsoil									
4 12	clay									
12 70	shale									
70 102	limestone									
	 									
	<u> </u>									
			-100							
7 0	Landauranda O. 700	antina This		$\overline{}$				nlugged	under mit historia	tion and
Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and										
was completed on (mo/day/year) 6/9/2006 and this record is true to the best of my knowledge and belief.										
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 6/12/2006										
Transact trater from	Contractor's Licens	se No. 236		water well	record wa	s completed	-		2/2006	
	Contractor's Licens		This	water well		s completed	on (mo/day/ye			