		WATER WE	ELL REC	ORD F	orm WV		SA 82a-12					
1 LOCATION OF WA	ATER WELL:	FRACTION SE 1/4	NE 1	/4 SE	1/4 SEC	TION NUMBER	T 2	P NUMBER 7 S	RANGE N			
	from nearest town or city				1/4		1 2		1 1 2			
2332 N. Burning Tree Wichita, Kansas												
2 WATER WELL OWNER: AYESH, Clint  RR#,ST. ADDRESS,BOX #: 2332 N. Burning Tree  Board of Agriculture, Division of Water Resource												
	CITY, STATE: Wichita, Kansas						ZIP CODE: Application Number:					
3 LOCATE WELL'S	SLOCATION 4	DEPTH OF COMPL	LETED WEL	.L: 10		, 0002.	ELEVATION:			·		
WITH AN "X" IN	SECTION BOX: Dep	pth of groundwater	Encountered	d:	ft			ft.		ft.		
	, WE	ELL'S STATIC WA	TER LEVEL	50	FT. BELC	W LAND SU	JRFACE MEAS	JRED ON mo/o	day/yr: 6/2	0/06		
NM	NE		np test data:				ft. after		of pumping @	gpm		
W Wile	F B	Est. Yield: ore Hole Diameter	gpm 12	Well wa	ter was to 1	1 <b>03</b> ft.	ft. after and	hours in.	s of pumping @ to	gpm ft.		
[= "]	1 1 1	ELL WATER TO BE	E USED AS:					0 Dewateri	44 1-1-	ection well		
sw	1 1 1						and garden only	$\triangleright$	12. Other (S	pecify below)		
	2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning  Was a chemical/bacteriological sample submitted to Department?  YES  NO  10. Monitoring well  15. If yes, what mo/day/yr was sam									was sample		
		bmitted	ological sampl	e submitted to t	Department:	YES Was V	Vater Well Disin		YES	NO		
~	CASING USED:	5. Wrought I	Iron	7. Fiberglass	9. O	ther (Specify	below) CAS	SING JOINTS:	Glued	Threaded		
1. Steel	3. RPM (SF 4. ABS	≺) 6. Asbestos	-Cement	8. Concrete t	ile SD	R-26			Welded	Clamped		
Blank casing dian			53 ft.,	Dia.	in.	to	ft.,	Dia.	in. to	ft.		
Ĭ		12 in		Weight:	2.35	bs. / ft.		nickness or gau		<b>!</b>		
Casing height above land surface: 12 in., Weight: 2.35 lbs. / ft. Wall thickness or gauge No214  TYPE OF SCREEN OR PERFORATION MATERIAL:												
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC						BS		ther (specify)				
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)												
SCREEN OR PERFORATION OPENINGS ARE:												
1. Continuous slot 3. Mill slot 5. Gauzed wrapped						7. Torch cut 9. Drilled holes 11. None ( open hole)						
2. Louvered shi		unched b. W	Vire wrappe			w cut	10. Oth	er (specify)				
SCREEN - PERFO	PRATION INTERVAL	From	53 ft.			ft.,	From	ft.	to	ft,		
CDAVE!	PACK INTERVALS:	From	ft. <b>24</b> ft.			ft.,	From	ft.	to	ft.		
GRAVEL	PACK INTERVALS:	From	2-4 it.			ft.,	From	ft.	to	ft.		
6 GROUT MAT	EDIALS:	From	2. Cemen			ft.,	From	ft. Other hent	tonite hole pl	ft.		
GROUT MATI	1.11001	ft.	3. Bentonite to	ft.,	From	ft. to	•					
What is the nearest source of possible contamination:					10. Livestoo							
1. Septic tank 4. Lateral lines 8. Sewage lagger 11						40 04 (						
2. Sewer lines 5. Cess Pool 6. Sewage lagoon 7. Abandon water wen 7. Abandon water w										,,,		
Q. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage  Direction from well? East How many feet? 12 feet plus												
From To		LITHOLOGIC	LOG		From	То			OGIĆ LOG			
0 4	topsoil				ļ	ļ						
4 15 15 103					<del>                                     </del>	<del>                                     </del>						
10.												
						-						
										<del></del>		
					<del> </del>							
7 Contractor's	or Landowner's Certific	cation: This water	well was 1 (	constructed	2 re	constructed	d or 3.	plugged	under my jurisdio	ction and		
$\vdash$	on (mo/day/year)	6-20-2006					knowledge and		,,,,			
	, , ,								2-2006			
under the business name of Harp Well and Pump Service by (signature)												