			WATER WE	LL RECORD	For	m WW	C-5 K	SA 82a-1212	2				
1 LOCATION OF WATER WELL: FRACTION						SECTIO	ON NUMBER	TOWNSHIP	TOWNSHIP NUMBER RANGE NUMBER				
Sedgwick SW 1/4 NE 1/4 SW				<b>SW</b> 1	/4	2	т 27	T 27 S R 2E E/W					
Distance and direction from nearest town or city street address of well if located within city?													
2315 Rosemont Circle Wichita, Kansas													
2 WATER	WELL OV	VNER: DB C	CONSTRUCTION	ON									
RR#,ST. AD	RR#,ST. ADDRESS,BOX #: 15307 E. 71st South									iculture, Division of W	ater Resource		
	CITY, STATE: Rosehill, Kansas							ZIP CODE: Application Number:					
3 LOCATE W	ELL'S LOC	ATION 4	DEPTH OF COMPLE	ETED WELL:	70	ft.		ELEVATION:					
WITH AN	X" IN SECT	ION BOX:	pth of groundwater E			ft.			ft.		ft.		
	- N		ELL'S STATIC WATI		25 F		I I AND SI	IRFACE MEASUR		day/yr: 7/25			
		-			Vell water		V LAND 30	ft. after		s of pumping @	gpm		
NY	<b>*</b>	- NE	Est. Yield:		Vell water			ft. after		s of pumping @	gpm		
Wile w		F   R	Sore Hole Diameter	gpm V 12 in.	veli water	to 70	) ft.		in.	to	ft.		
1_ (		' I I	ELL WATER TO BE			10 70		Gild		44 1.1.	ction well		
of the state of th								'''9	pecify below)				
1		2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well									, , , , , , , , , , , , , , , , , , , ,		
	S Was a chemical/bacteriological sample submitted to Department? YES NO ; If yes, what mo/day/yr was sample												
		su	bmitted				Was V	Vater Well Disinfe	cted?	YES I	NO ·		
		NG USED:	5. Wrought In	on 7. Fibe	erglass	9. Oth	er (Specify	below) CASI	NG JOINTS:	Glued	Threaded		
1. S	Steel	3. RPM (SI	R)		•	SDR	-26			Welded	Clamped		
	PVC >	4. ABS	6. Asbestos-0		ncrete tile								
Blank casing	g diameter	5	in. to 3	30 ft., D	Dia.	in.	to	ft., C	ia.	in. to	ft.		
Casing heig	jht above l	and surface:	12 in.,	Weig	jht: 2.	.35 lbs	s. / ft.	Wall thic	kness or gau	ge No214			
TYPE OF SO	CREEN O	R PERFORATION	N MATERIAL:										
1. Steel	3.	Stainless Steel	5. Fiberglass	7. PVC	$\geq$	9. AB	S	11. Oth	er (specify)				
2. Brass	4.	Galvanized	6. Concrete Tile	e 8. RMF	P (SR)	10. As	bestos-Cer	ment 12. Nor	ne used (open	hole)			
SCREEN OR PERFORATION OPENINGS ARE:													
1. Continu		3. Mill si		auzed wrapped		7. Tor	ch cut	9. <b>Drille</b>	d holes	11. None (	open hole)		
										•	,		
2. Louvere	ed shutter	4. Key p	ounched 6. W	ire wrapped		8. Sav	v cut	10. Otne	r (specify)				
SCREEN - P	ERFORAT	TION INTERVAL	From	<b>30</b> ft.	to	70	ft.,	From	ft.	to	ft.		
			From	ft.	to		ft.,	From	ft.	to	ft.		
GRAVEL PACK INTERVALS: From 24 ft.					to	70	ft.,	From	ft.	to	ft.		
			From	ft.	to			From					
			From	11.	10		ft.,		ft.	to	ft.		
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hole plug									•				
Grout Int		From 4	ft. to	24 ft.,	From	ft.	to	ft.,	From	ft. to	ft.		
I .		urce of possible o	7	Pit privy	10.	Livestock	pens	13. Insection	ide storage	15. Oil well/	Gas well		
1. Septic tank 4. Lateral lines 4. Source legger 11. Filel storage 14. Abandon water well 16. Other (specify													
2. Sewer I		5. Cess						17. Abando	water well		,		
3. Waterti			age pit 9.	Feed yard	12.	. Fertilizer	storage	U	nu forto EA	ft plus			
Direction fro		East	LITUOLOGIO	1.00		Cross 1	Te	How ma	ny feet? 50				
From	To		LITHOLOGIC	LUG		From	То		LIHOL	OGIC LOG			
0		topsoil											
17		clay											
<del></del>	/U	gray shale											
		L						<u> </u>					
Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and													
was completed on (mo/day/year) 7/25/2006 and this record is true to the best of my knowledge and belief.													
under the	business	name of Harp	Well and Pun	np Service		by (si	gnature)	7,	115	<i>H</i>			
under the business name of Harp Well and Pump Service by (signature)  Jo d d S. Harp													