		WATER V	VELL RECO	DRD Fo	rm WW	C-5 K	SA 82a-12	12		
1 LOCATION OF WATER	WELL:	FRACTION			SECTI	ON NUMBER		P NUMBER	RANGE N	
Sedgwick		SW 1/4	SE 1/4	NW	1/4	11	Т 2	7 s	R 21	E/W
Distance and direction from nearest town or city street address of well if located within city?										
1809 N. Glenwood Wichita, Kansas										
2 WATER WELL OWNER: QUAM Board of Agriculture, Division of Water Resource										
	R#,S1. ADDRESS,BOX #: 1809 14. Gleffwood									
CITY, S	STATE: Wich	ita, Kansas			ZIF	CODE:		Application Num	ber:	
3 LOCATE WELL'S LOC	CATION 4 D	DEPTH OF COM	IPLETED WELL	.: 73	ft.		ELEVATION:			1
WITH AN "X" IN SEC		th of groundwat	er Encountered:		ft.			ft.		ft.
	WE	ELL'S STATIC W	ATER LEVEL	26	FT. BELOV	V LAND SU	RFACE MEAS	URED ON mo/d	ay/yr: 8/7	/06
NW+	-NE	P	ump test data:	Well wate	r was		ft. after	hours	of pumping @	gpm
		Est. Yield:	gpm	Well water			ft. after		of pumping @	gpm
w X	E Bo	ore Hole Diamet	1.0	in.	to 73	3 ft.	and	in.	to	ft.
- =	WE	LL WATER TO						9. Dewaterii	na 11. lnje	ction well
sw	1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 12. Other (Specify below)									pecify below)
2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well										
Was a chemical/bacteriological sample submitted to Department? YES NO ; If yes, what mo/day/yr was sample										· · · · · ·
		omitted				Was W	/ater Well Disir	nfected?	YES	NO
5 TYPE OF CASI		5. Wroug	ht Iron 7	. Fiberglass	9. Ot	her (Specify	below) CA	SING JOINTS: (Glued	Threaded
1. Steel	3. RPM (SR	•	os-Cement 8	. Concrete tile	SDF	R-26			Welded	Clamped
2. PVC	4. ABS				,		_			
Blank casing diamete	r 5 i	in. to	25 ft.,	Dia.	in.	to	ft.,	Dia.	in. to	ft.
Casing height above	land surface:	12 in.,		Weight:	2.35 lb	s. / ft.	Wall t	hickness or gaug	ge No214	
TYPE OF SCREEN OR PERFORATION MATERIAL:										
1. Steel 3.	Stainless Steel	Fiberglas	is $\overline{7}$.	PVC	9. A	BS	11. C	ther (specify)		1
2. Brass 4.	Galvanized	Concrete	Tile 8.	RMP (SR)	10. As	sbestos-Cen	nent 12. N	lone used (open	hole)	
SCREEN OR PERFORATION OPENINGS ARE:										
1. Continuous slot	3. Mill slo		. Gauzed wrap	ped	7. To r	ch cut	9. Dri	lled holes	11. None (open hole)
						8. Saw cut 10. Other (specify)				
2. Louvered shutte	4. Key pu	unched c	. Wire wrapped			W CUI	10. 00	iei (specity)		
SCREEN - PERFORA	TION INTERVAL	From	25 ft.	to	73	ft.,	From	ft.	to	ft.
		From	ft.	to		ft.,	From	ft.	to	ft.
GRAVEL PAG	CK INTERVALS:	From	24 ft.	to	73	ft.,	From	ft.	to	ft.
		From	ft.	to		ft.,	From	ft.	to	ft.
C GPOLIT MATERI	A1 S:									
GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hole plug Grout Intervals: From 4 ft. to 24 ft From ft to ft										
Grout Intervals: What is the nearest so			o 24 ft.,	From	ft.	to	ft.,	From	ft. to	ft.
What is the nearest source of possible contamination: 1. Septic tank 4. Lateral lines 7. Pit privy 10.						k pens	13. Inse d	ticide storage	15. Oil well/	Gas well
2. Sewer lines	5. Cess P		8. Sewage lag	oon 1	1. Fuel sto	rage	14. Aban	don water well	16. Other (s	pecify below)
			9. Feed yard		2. Fertilize ı	storage	- 3			
6. Seepage pit 9. Feed yard 12. Fertilizer storage West How many feet? 21										
From To LITHOLOGIC LOG					From	То			OGIC LOG	
0 3	topsoil				170111	'		Littlocc	<u> </u>	
3 16	clav									
16 53	brown shale									
53 73	gray shale	-								
						 				4
					 	-				
-					-		-			
7 0								mlumma a d	ander en deside de	otion and
_	_andowner's Certific		,	constructed		constructed		plugged	under my jurisdi	CHOIL SUG
was completed on	(mo/day/year)	8/7/200	6 an	d this record i	s true to the	e best of my	knowledge and	d belief.		
Kansas Water Well	Contractor's Licen	se No. 236		This water we	II record wa	s completed	d on (mo/day/y	ear) 8-9	-2006	
under the business name of Harp Well and Pump Service by (signature) Jo d d S. Jarp										
Jo a a J. Jarp										