WATER WELL RECORD Form WWC-5 KSA 82a-1212								
1 LOCATION OF WATER WELL: Sedgwick FRACTION SW 1/4 SE 1/4 NW			.	TION NUMBER			RANGE NUMBER	
Sedgwick Distance and direction from nearest town or city	.,,,	0.7 2111	1/4	11	T 27	S	R	2E E/W
13229 E. Bridlewood Ct.	Wichita, K	•						
2 WATER WELL OWNER: ROBL CONSTRUCTION								
	W. 21st St. N.					Board of Agri	culture, Division of	of Water Resource
CITY, STATE: Wich	nita, Kansas		_	P CODE:		Application Nun	nber:	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	DEPTH OF COMPLETE	ED WELL:	80 ft.		ELEVATION:			
N De	pth of groundwater Enco		ft.			ft.		ft.
	ELL'S STATIC WATER			W LAND SU	JRFACE MEASU			25/06
NWNE	Pump te		ater was		ft. after		of pumping @	0.
₩ X B	Est. Yield: o	$_{ m 12}$ $_{ m in.}$	ater was to 8	30 ft.	ft. after and	nours in.	of pumping @ to) gpm ft.
	ELL WATER TO BE US	SED AS:				9. Dewateri	44.	njection well
sw sE 1	. Domestic 3. Feed	flot 5. Public w	ater supply	7. Lawn a	and garden only	> Dewater	9	(Specify below)
2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well								
S Was a chemical/bacteriological sample submitted to Department? YES NO ; If yes, what mo/day/yr was sample submitted Was Water Well Disinfected? YES NO								
5 TYPE OF CASING USED:	5 Manual Mana	. 7 Fib	- 9.0	ther (Specify		NG JOINTS: (Glued	Threaded
1. Steel 3. RPM (SF		7. Fiberglas	SD	R-26	50.011)		Welded	Clamped
2. PVC 4. ABS	6. Asbestos-Cen		tile SD	K-20				
Blank casing diameter 5	in. to 50	ft., Dia.	in.	to	ft., C	Dia.	in. to	ft.
Casing height above land surface:	12 _{in.,}	Weight:	2.35 II	bs. / ft.	Wall thic	kness or gaug	ge No21	14
TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)								
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify) 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)								
SCREEN OR PERFORATION OPENINGS ARE:								
1. Continuous slot 3. Mill sl		ed wrapped	7. T o	rch cut	9. Drille	d holes	11. None	(open hole)
2. Louvered shutter 4. Key p		wrapped		w cut		r (specify)		(
	_					(Specify)		
SCREEN - PERFORATION INTERVAL			o 80	ft.,	From	ft.	to	ft.
ODANEL BACK INTERNALO	From		0	ft.,	From	ft.	to	ft.
GRAVEL PACK INTERVALS:	110111		to 80	ft.,	From	ft.	to	ft.
- Longuiz Marrows	From	ft.	to	ft.,	From	ft.	to	ft.
6 GROUT MATERIALS: 1. Neat		Cement Grout		3. Bentonite			onite hole p	
Grout Intervals: From 4 What is the nearest source of possible co		ft., From	ft.	to	ft.,	From	ft.	to ft.
1. Septic tank 4. Lateral lines 7. Pit privy 10. Liv				k pens	13. Insecticide storage 15. Oil well/Gas well			
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below)								
3 Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage								
Direction from well? East	LITUOLOGIC LA	20	T =		How mar	ny feet? 22	010100	
From To 0 4 topsoil	LITHOLOGIC LO	<u></u>	From	То		LITHOLO	GIC LOG	
4 20 clay								
20 70 shale								
70 80 limestone				 				
			 	 				
			+					··
						,		
			-					
Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and								
was completed on (mo/day/year) 8-25-2006 and this record is true to the best of my knowledge and belief.								
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 8-28-2006								
under the business name of Harp Well and Pump Service by (signature) Todd S. Harb								