	WATER WELL RE	CORD F	orm WW	C-5 K	SA 82a-1212	2			
1 LOCATION OF WATER WELL:				ON NUMBER	TOWNSHIP I	TOWNSHIP NUMBER RANGE			
☐ Sedgwick	SW 1/4 SW	1/4 NW	1/4	11	T 27	S	R 2E	E/W	
Distance and direction from nearest town or city	•	•							
1818 N. Glenwood Ct.	Wichita, Kansas								
- 1	CHIE CONSTRUCTI					Board of Agric	culture, Division of Wate	r Resource	
	****					•			
	hita, Kansas	0.0		CODE:		Application Num	iber:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	DEPTH OF COURSES WE	ELL: 82	ft.		ELEVATION:				
N De	epth of groundwater Encounter	red:	ft.			ft.		ft.	
w	/ELL'S STATIC WATER LEVE	L 35	FT. BELO	V LAND SU	JRFACE MEASUR	RED ON mo/d	lay/yr: 8/2/0 6	,	
NW NE	Pump test data	a: Well wate	er was		ft. after	hours	of pumping @	gpm	
W X	Est. Yield: gpm	Well water	er was		ft. after	hours	of pumping @	gpm	
	Bore Hole Diameter	in.	to	ft.	and	in.	to	ft.	
	VELL WATER WASE USED AS 1. Domestic 3. Feedlot		or eupply (7 Lawn a	and garden only	9. Dewaterin	•		
	2. Irrigation 4. Industrial				nditioning	10. Monitorin	12. Other (Spec	ify below)	
	Was a chemical/bacteriological sam			YES	NO		vhat mo/day/yr was	sample	
,	ubmitted	.,,	-		Vater Well Disinfe	cted?	YES NO		
5 TYPE OF CASING USED:	5. Wrought Iron	7. Fiberglass	9. Ot	ner (Specify	(below) CASII	NG JOINTS:	Glued Th	readed	
1. Steel 3. RPM (S	SR)	-			•		Welded C	lamped	
2. PVC 4. ABS	6. Asbestos-Cement	8. Concrete tile	Э						
Blank casing diameter 5	in. to ft.,	Dia.	in.	to	ft., D	ia. i	in. to	ft.	
Casing height land surface:	36 in.,	Weight: 2	2.35 lb	s. / ft.	Wall thic	kness or gaug	ge No214		
TYPE OF SCREEN OR PERFORATION MATERIAL:									
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify) N/A									
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:									
1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole)								n hole)	
2. Louvered shutter 4. Key p	punched 6. Wire wrapp	ped	8. Sa v	v cut	10. Other	(specify) N	/A		
SCREEN - PERFORATION INTERVAL	From	ft. to		ft.,	From	ft.	to	ft.	
		ft. to		ft.,	From	ft.	to	ft.	
GRAVEL PACK INTERVALS:		ft. to		ft.,	From	ft.	to	ft.	
GIVALET MORE INTERVALES.	7.000	ft. to							
T	From	п. 10		ft.,	From	ft.	to	ft.	
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hole plug									
Grout Intervals: From 3		ft., From	44 ft.	to	48 ft.,	From	ft. to	ft.	
What is the nearest source of possible contamination: 1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well						well			
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below							fy below)		
2. Sewer lines 5. Cess root 12 Fortilizer eterate									
3. Watertight sewer line 6. Seepage pit 9. reed yard 12.				•	How man	y feet?			
From To	LITHOLOGIC LOG		From	То		LITHOLO	GIC LOG	-	
			0	3	compacted to	psoils			
			3	35	bentonite ho				
			35	82	chlorinated s	vell gravel			
									
					-				
7 Contracted and and an area of Contract	fination: This water well was 4	00004041	^ ==	onetri-t-	d or 3 (hannul	under my juriediation	and	
Contractor's or Landowner's Certification: This water well was 1, constructed 2, reconstructed or 3, plugged under my jurisdiction and									
was completed on (mo/day/year) 8-02-2006 and this record is true to the best of my knowledge and belief.									
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 8-07-2006									
under the business name of Harp Well and Pump Service by (signature)									