	WATER WELL RECOR	RD Form V	VWC-5 K	SA 82a-121	2			
1 LOCATION OF WATER WELL:	FRACTION NINK ALL SE				NUMBER	l	RANGE NUMBER	
Sedgwick  Distance and direction from nearest town or city	NW 1/4 NW 1/4	SE 1/4	2	T 27	S	R 2E	E/W	
2525 N. Rosemont Ct.	Wichita, Kansas	/ <b>:</b>						
	- DRUMRIGHT BUILDEI	RS						
RR#,ST. ADDRESS,BOX #: P.O.	Box780427				Board of Agric	culture, Division of Wa	ter Resource	
	nita, Kansas		ZIP CODE:		Application Num	nber:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	DEPTH OF COMPLETED WELL:	80	ft.	ELEVATION:				
	pth of groundwater Encountered:		ft.		ft.		ft.	
	ELL'S STATIC WATER LEVEL		LOW LAND SU	JRFACE MEASU			<b>J6</b>	
NW NE		Well water was		ft. after		of pumping @	gpm	
e B	Est. Yield: gpm ore Hole Diameter 12 in.	Well water was	<b>80</b> ft	ft. after and	in.	of pumping @ to	gpm ft.	
	ELL WATER TO BE USED AS:				0 Dowatorii	44 1 1 1		
1 SW SE 1	. Domestic 3. Feedlot 5. P	ublic water supp			>	12. Other (Spe	cify below)	
	<ol> <li>Irrigation 4. Industrial 6. O</li> <li>Vas a chemical/bacteriological sample sub</li> </ol>	il field water sup		nditioning	10. Monitorin	<b>ıg weli</b> vhat mo/day/yr wa	ıs sample	
•	vas a chemical/bacteriological sample sub bmitted	omitted to Departmen		NO Vater Well Disinfe		YES NO	•	
TYPE OF CASING USED:	5. Wrought Iron 7. Fi	iberglass <sup>9</sup>	. Other (Specify	/ below) CASI	NG JOINTS: (	Glued	Threaded	
1. Steel 3. RPM (SF	₹)		DR-26	•		Welded	Clamped	
2. PVC 4. ABS		oncrete tile						
1	10	Dia. in	-	•		in. to	ft.	
Casing height above land surface:		eight: <b>2.35</b>	lbs. / ft.	Wall thi	ckness or gaug	ge No214		
TYPE OF SCREEN OR PERFORATION  1. Steel 3. Stainless Steel	N MATERIAL: 5. Fiberglass 7. PV	(C)	9. ABS	11. Oth	er (specify)			
2. Brass 4. Galvanized			0. Asbestos-Ce		ne used (open	hole)		
SCREEN OR PERFORATION OPENING	GS ARE:							
1. Continuous slot 3. Mill sl		7.	Torch cut	9. <b>Drille</b>	ed holes	11. None ( op	en hole)	
2. Louvered shutter 4. Key p	unched 6. Wire wrapped	(8)	Saw cut	10. Othe	r (specify)			
SCREEN - PERFORATION INTERVAL	From <b>50</b> ft.	to <b>8</b> (	) ft.,	From	ft.	40	4	
SOILER - LEN GRATION INTERVAL	From ft.	to	ft.,	From	n. ft.	to to	ft. ft.	
GRAVEL PACK INTERVALS:	From 24 ft.	to 80	•	From	ft.	to	ft.	
	From ft.	to	ft.,	From	ft.	to	ft.	
6 GROUT MATERIALS: 1. Neat			3. Bentonite			onite hole plus		
Grout Intervals: From 4	ft. to <b>24</b> ft.,	From	ft. to	ft.,	From	ft. to	≨ ft.	
What is the nearest source of possible co	ontamination:							
1. Seput tank 4. Euteral lines			tock pens		13. Insecticide storage 15. Oil well/Gas well  14. Abandon water well 16. Other (specify below)			
2. Sewer lines 5. Cess F			•	14. Abando	on water well	To: Other (spe	ony below,	
3. Watertight sewer line 6. Seepa Direction from well?	ge pit 9. Feed yard	12. <b>Ferti</b>	izer storage	How ma	ny feet? 50 f	ft plus		
Direction from wor.	LITHOLOGIC LOG	Fro	m To	TIOW THE		GIC LOG		
0 4 topsoil		1.10			LITTIOLO			
4 18 clay								
18 80 shale								
					<del> </del>			
7 Contractor's or Landowner's Certifi	cation: This water well was 1	nstructed 2.	reconstructe	d or 3, p	olugged	under my jurisdictio	n and	
_	10/5/000/					and my jurisdiction		
was completed on (mo/day/year)		is record is true to	·	_		0/2007		
Kansas Water Well Contractor's Licen		water well record	•			9/2006		
under the business name of Harp	Well and Pump Service	by	(signature)	To	rad S	. Harp		