

1 LOCATION OF WATER WELL: Sedgwick	FRACTION NE 1/4 NE 1/4 SE 1/4	SECTION NUMBER 10	TOWNSHIP NUMBER T 27 S	RANGE NUMBER R 2E E/W	
Distance and direction from nearest town or city street address of well if located within city? 12620 E. Tallowood Wichita, Kansas					
2 WATER WELL OWNER: WINKLE, Mike RR#, ST. ADDRESS, BOX #: 12620 E. Tallowood CITY, STATE: Wichita, Kansas					
			Board of Agriculture, Division of Water Resource		
			ZIP CODE:		
			Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: 80 ft.			
		ELEVATION:			
		Depth of groundwater Encountered: _____ ft.			
		WELL'S STATIC WATER LEVEL 40 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 10/13/06			
Pump test data:		Well water was _____ ft. after _____ hours of pumping @ _____ gpm			
Est. Yield: _____ gpm		Well water was _____ ft. after _____ hours of pumping @ _____ gpm			
Bore Hole Diameter	12 in.	to 80 ft.	and _____ in.	to _____ ft.	
WELL WATER TO BE USED AS:					
1. Domestic	3. Feedlot	5. Public water supply	7. Lawn and garden only	9. Dewatering	
2. Irrigation	4. Industrial	6. Oil field water supply	8. Air conditioning	10. Monitoring well	
Was a chemical/bacteriological sample submitted to Department? YES NO ; If yes, what mo/day/yr was sample submitted			YES NO		
5 TYPE OF CASING USED:					
1. Steel	3. RPM (SR)	5. Wrought Iron	7. Fiberglass	9. Other (Specify below) CASING JOINTS: Glued Threaded Welded Clamped	
2. PVC	4. ABS	6. Asbestos-Cement	8. Concrete tile	SDR-26	
Blank casing diameter	5 in.	to 40 ft., Dia.	in.	to _____ ft., Dia.	
Casing height above land surface:	12 in.,	Weight:	2.35 lbs. / ft.	Wall thickness or gauge No. .214	
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1. Steel	3. Stainless Steel	5. Fiberglass	7. PVC	9. ABS	
2. Brass	4. Galvanized	6. Concrete Tile	8. RMP (SR)	10. Asbestos-Cement	
SCREEN OR PERFORATION OPENINGS ARE:					
1. Continuous slot	3. Mill slot	5. Gauzed wrapped	7. Torch cut	9. Drilled holes	
2. Louvered shutter	4. Key punched	6. Wire wrapped	8. Saw cut	10. Other (specify)	
SCREEN - PERFORATION INTERVAL	From 40 ft.	to 80 ft.,	From _____ ft.	to _____ ft.	
	From _____ ft.	to _____ ft.,	From _____ ft.	to _____ ft.	
GRAVEL PACK INTERVALS:	From 24 ft.	to 80 ft.,	From _____ ft.	to _____ ft.	
	From _____ ft.	to _____ ft.,	From _____ ft.	to _____ ft.	
6 GROUT MATERIALS:					
Grout Intervals:	From 4 ft.	to 24 ft., From _____ ft.	to _____ ft., From _____ ft.	Other bentonite hole plug	
What is the nearest source of possible contamination:					
1. Septic tank	4. Lateral lines	7. Pit privy	10. Livestock pens	13. Insecticide storage	
2. Sewer lines	5. Cess Pool	8. Sewage lagoon	11. Fuel storage	14. Abandon water well	
3. Watertight sewer line	6. Seepage pit	9. Feed yard	12. Fertilizer storage	15. Oil well/Gas well	
Direction from well? Northwest			How many feet? 50 ft. plus		
From	To	LITHOLOGIC LOG	From	To	LITHOLOGIC LOG
0	4	topsoil			
4	30	clay			
30	65	shale			
65	80	limestone			
7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 10-13-2006 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 10-16-2006 under the business name of Harp Well and Pump Service by (signature) <i>Todd S. Harp</i>					