	WATER WELL RECORD FO	orm WWC-	5 KSA 82a-1212			
1 LOCATION OF WATE		SECTION N	i i	MBER F	RANGE NUMBER	
☐ Sedgwick	NW 1/4 NE 1/4 SE	1/4 2	т 27	S	R 2E E/W	
1	m nearest town or city street address of well if located within city?					
13808 Mainsg						
2 WATER WELL O	•			Board of Agriculture D	ivision of Water Resource	
RR#,ST. ADDRESS	BOX #: 13808 Mainsgate Circle					
CITY,	STATE: Wichita, Kansas	ZIP CO	DE: Ap	oplication Number:		
3 LOCATE WELL'S LO		O ft.	ELEVATION:			
WITH AN "X" IN SEC	Depth of groundwater Encountered:	ft.		ft.	ft.	
	WELL'S STATIC WATER LEVEL 60	FT. BELOW LA	ND SURFACE MEASURE	D ON mo/day/yr:	11/1/06	
	Pump test data: Well water	er was	ft. after	hours of pump	ping @ gpm	
	Est. Yield: gpm Well water	er was	ft. after	hours of pump	ping @ gpm	
w Mile	E Bore Hole Diameter 12 in.	to 110	ft. and	in.	to ft.	
 	WELL WATER TO BE USED AS:			9. Dewatering	11. Injection well	
1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 12. Other (Specify below						
	2. Irrigation 4. Industrial 6. Oil field wa	ater supply 8. A		O. Monitoring well	the terms are le	
S	Was a chemical/bacteriological sample submitted to De submitted	epartment? Y	Was Water Well Disinfector		n/day/yr was sample NO	
5 P/PE 05 040						
5 TYPE OF CAS	5. Wrought Iron 7. Fiberglass 3. RPM (SR)	9. Other (Specify below) CASING	JOINTS: Glued		
	4. ABS 6. Asbestos-Cement 8. Concrete tile	e SDR-26	,	Welded	d Clamped	
2. PVC	4. ADS		to # Dia	-	4- 64	
Blank casing diamete			to ft., Dia	. in.	to ft.	
Casing height above	e land surface: 12 in., Weight:	2.35 lbs. / fi	t. Wall thickr	ness or gauge No.	.214	
TYPE OF SCREEN OR PERFORATION MATERIAL:						
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)						
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)						
SCREEN OR PERFO	PRATION OPENINGS ARE:					
1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole)						
2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify)						
		110 ft				
SCREEN - PERFORA		,	From	ft.	to ft.	
	From ft. to	ft.,	From	ft.	to ft.	
GRAVEL PA	CK INTERVALS: From 24 ft. to	110 ft.,	From	ft.	to ft.	
	From ft. to	ft.,	From	ft.	to ft.	
6 GROUT MATER	ALS: 1. Neat cement 2. Cement Grout	3. Be i	ntonite Otl	ner bentonite l	hole plug	
Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to						
What is the nearest source of possible contamination:						
1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas						
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below)						
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage						
Direction from well?	North		How many	feet? 17 ft.		
From To	LITHOLOGIC LOG	From	Го L	ITHOLOGIC L	OG	
0 4	topsoil					
4 18	clav					
18 85	shale					
85 95	limestone					
95 110	shale and limestone					
						
		 				
7 Contractor's or Landowner's Certification: This water well was 1. constructed 2, reconstructed or 3, plugged under my jurisdiction and						
11.01.000						
was completed on (mo/day/year) 11-01-2006 and this record is true to the best of my knowledge and belief.						
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 11/03/2006						
under the business	under the business name of Harp Well and Pump Service by (signature) Todd S. Harp					
1000 S. TOP						