			WATER W	ELL RE	CORD	Forn	n WW	C-5 K	SA 82a-121	2		
1'1	OF WATER	WELL:	FRACTION	N7887			10000	ON NUMBER			RANGE N	
Sedgw			SW 1/4	NW		SE 1/4	1	2	T 2'	7 S	R 21	E/W
l		nearest town or city :		ita, Kan	•		4-					
2 WATER WELL OWNER: GOENTZEL CONSTRUCTION												
RR#,ST. ADDRESS,BOX #: 902 E. Indianapolis Board of Agriculture, Division of Water Resource												/ater Resource
	CITY, S		ita, Kansas				ZIF	CODE:		Application Nun	nber:	
3 LOCATE	WELL'S LO	CATION 4	DEPTH OF COME	PLETED W	VELL:	86	ft.		ELEVATION:			
WITH AN	N "X" IN SEC	TION BOX: Dep	oth of groundwate	r Encounte	ered:		ft.			ft.		ft.
		WE	ELL'S STATIC W	ATER LEV	EL 50	FT.	BELOV	V LAND SU	JRFACE MEASU	JRED ON mo/o	day/yr: 11/1	6/06
	NW	-NE	Pu	ımp test da	ata: We	ell water w	as		ft. after	hours	s of pumping @	gpm
Wile w		1	Est. Yield:	gpm	•	ell water w			ft. after	hours	s of pumping @	gpm
			ore Hole Diamete				to 8 0	b ft.	. and	in.	to	ft.
	sw X		ELL WATER TO E . Domestic 3	. Feedlot	AS: 5. Publ i	ic water s	vlaque	7. Lawn a	and garden only	⊳ ^{9. Dewateri}	9	ction well pecify below)
	1			Industria				8. Air cor		10. Monitori		pecity below;
'	s		as a chemical/bacte	eriological sa				YES	NO		what mo/day/yr v	•
			bmitted					Was V	Water Well Disin		=	NO
~	PE OF CASI . Steel	NG USED: 3. RPM (SF	5. Wrough	t Iron	7. Fiber	glass	9. Otl	ner (Specify	y below) CAS	SING JOINTS:	Glued	Threaded
	PVC	4. ABS	6. Asbesto	s-Cement	8. Conc	rete tile	SDF	R-26			Welded	Clamped
_	ing diamete	_	in. to	36 ft.	., Dia	ı.	in.	to	ft.,	Dia.	in. to	ft.
	•	-	12 in.,			. 2.3	5 lb	e /ft	Wall th	ickness or gau	ge No255	
1 *	Casing height above land surface: 12 in., Weight: 2.35 lbs. / ft. Wall thickness or gauge No255 TYPE OF SCREEN OR PERFORATION MATERIAL:											
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)												
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)												
SCREEN (OR PERFO	RATION OPENING	GS ARE:									
1. Contin	nuous slot	3. Mill sl	ot 5.	Gauzed w	vrapped		7. Tor	ch cut	9. Dril	led holes	11. None (open hole)
2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify)												
SCREEN -	PERFORA	TION INTERVAL	From	36	ft.	to	86	ft.,	From	ft.	to	ft.
			From		ft.	to		ft.,	From	ft.	to	ft.
GI	RAVEL PAG	CK INTERVALS:	From	20	ft.	to	86	ft.,	From	ft.	to	ft.
			From		ft.	to		ft.,	From	ft.	to	ft.
6 GROU	JT MATERI	ALS: 1 Nost		2 Cor	mont Grout			Bentonite			tonite hole pl	
									ft. to			
What is the	nearest so	urce of possible co	ontamination:	7 D'4					•			
1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestoc								-		icide storage	15. Oil well/	pecify below)
2. Sewe	r lines	5. Cess I	001	8. Sewage	_		uel sto	-	14. Aband	lon water well	io. Other (s	pecity below)
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage Direction from well? West How many feet? 10 ft. plus												
From	from well?	West	LITHOLOGI	CIOG			rom	То	How m		OGIC LOG	
0	3	topsoil	LITTIOLOGI	C LOG		- '	10111	10		LITTIOL	<u> </u>	
3	5	clav										
5	65	gray shale										
65	75	limestone				_						
75	86	gray shale				_				w		
	-									· · · · · · ·		
	L	<u> </u>										
Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and												ction and
was completed on (mo/day/year) 11-16-2006 and this record is true to the best of my knowledge and belief.												
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 11-20-2006												
under th	ne business	name of Harp	Well and Pu	ımp Ser	vice		by (si	gnature)	Τ	odd!	S. Hari	b