		WATER WE	LL RECO	RD Fo	rm WW	C-5 K	SA 82a-121	2		
1 LOCATION OF WATER WEI	FRACTION NINE ALL SEE			1	ON NUMBER		TOWNSHIP NUMBER		RANGE NUMBER	
Sedgwick	rest town or city st	NW 1/4	NW 1/4		1/4	2	T 27	S	R 2E	E/W
Distance and direction from nearest town or city street address of well if located within city? 2533 Loch Lomond Ct. Wichita, Kansas										
2 WATER WELL OWNE	~~~	TZEL CON		ON						
RR#,ST. ADDRESS,BOX #: 902 E. Indianapolis								Board of Agric	culture, Division of W	ater Resource
CITY, STAT		ta, Kansas		97		CODE:	E. E. (4. E. O.)	Application Num	ber:	
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION	BOX:	EPTH OF COMPL		91	ft. ft.		ELEVATION:	ft.		ft.
l I		h of groundwater		50 F		/ I AND SH	RFACE MEASU		ay/yr: 11/9	
NWNE			p test data:	Well water		V LAND 30	ft. after		of pumping @	gpm
		Est. Yield:	gpm	Well water			ft. after		of pumping @	gpm
W N N N N N N N N N N N N N N N N N N N	1 1	re Hole Diameter		n.	to 98	3 ft.	and	in.	to	ft.
swse		LL WATER TO BE Domestic 3. F	USED AS: Feedlot 5.	Public wate	r supply	7. Lawn a	nd garden only	9. Dewaterir	'9	ction well
	1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 12. Other (Specify below 2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well									
S		as a chemical/bacteri				YES	NO		vhat mo/day/yr v	vas sample NO
5 TYPE OF CASING		mitted .			0.04		/ater Well Disinf		Glued	Threaded
5 TYPE OF CASING 1. Steel	3. RPM (SR)	5. Wrought I	ron 7. l	Fiberglass		er (Specify	below) CAS	ING JOINTS: (Welded	Clamped
2. PVC	4. ABS	6. Asbestos	-Cement 8.	Concrete tile	SDR	-26				
Blank casing diameter	5 i		50 ft.,	Dia.	in.	to	ft.,	Dia. i	in. to	ft.
Casing height above land		12 in.,	W	Veight: 2	2.35 lb	s. / ft.	Wall thi	ckness or gaug	ge No214	
TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)										
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify) 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)										
SCREEN OR PERFORATION OPENINGS ARE:										
1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole)										open hole)
2. Louvered shutter	4. Key pu	nched 6. V	Vire wrapped		8. Sav	v cut	10. Oth	er (specify)		
SCREEN - PERFORATION	N INTERVAL	From	50 ft.	to	97	ft.,	From	ft.	to	ft.
		From	ft.	to		ft.,	From	ft.	to	ft.
GRAVEL PACK II	NTERVALS:	From	24 ft.	to	97	ft.,	From	ft.	to	ft.
		From	ft.	to		ft.,	From	ft.	to	ft.
6 GROUT MATERIALS	1. Neat c	ement	2. Cement C	Grout	3	Bentonite		Other bent	onite hole pl	ug
	rom 4	ft. to	24 ft.,	From	ft.	to	ft.,	From	ft. to	ft.
What is the nearest source of possible contamination: 1. Septic tank 4. Lateral lines 7. Pit privy					Livestock pens		13. Insecti	cide storage	15. Oil well/0	Gas well
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify b									pecify below)	
3. Watertight sewer lin	6. Seepag	je pit 9.	Feed yard	12	2. Fertilizer	storage				
Direction from well?	North						How ma	any feet? 12		
From To		ITHOLOGIC	LOG		From	То		LITHOLO	GIC LOG	
0 4 tor 4 15 cla	psoil							***		***************************************
	ale									
90 97 lin	nestone							-3.75		
									**	

7 Contractor's or Land	downer's Certific	cation: This water	well was 1.Co	onstructed) 2. re	constructe	d or 3.	plugged	under my jurisdic	tion and
was completed on (mo		11-9-2006					knowledge and	belief.		
Kansas Water Well Cor		se No. 236	T	his water we	II record wa	s completed	d on (mo/day/yea	ar) 11/1	3/2006	
under the business name of Harp Well and Pump Service by (signature) Todd S. Harb										