	WATER WELL	RECORD F	orm WW	C-5 K	SA 82a-1212	!			
1 LOCATION OF WATER WELL:	FRACTION			ON NUMBER	}	TOWNSHIP NUMBER		RANGE NUMBER	
Sedgwick Distance and direction from nearest town or cit			1/4	2	Т 27	S	R 2E	E/W	
14115 E. 24th Ct. No.	Wichita.								
	ASK, Barry								
	15 E. 24th Ct. No.					Board of Agri	iculture, Division of Wa	iter Resource	
	chita, Kansas		^	CODE:		Application Nun	nber:		
WITH AN "X" IN SECTION BOX:	DEPTH OF COMPLETE				ELEVATION:				
	epth of groundwater End		ft.	AZ L AND CIT	DEACE MEACUE	ft.	day/yr: 12/19	ft.	
	VELL'S STATIC WATER	est data: Well wa		W LAND SU	RFACE MEASUR ft. after		aay/yr: 12/19 s of pumping @	gpm	
ΦNWNE			ter was		ft. after		s of pumping @	gpm	
₩ ₩ E	Bore Hole Diameter	12 in.	to 8	2 ft.	and	in.	to	ft.	
~	VELL WATER TO BE US	SED AS:	tar aummbr 6	7 Lawn a	nd garden only	9. Dewateri	•		
l l	1. Domestic 3. Feed 2. Irrigation 4. Indu					10. Monitori i	12. Other (Spang well	ecify below)	
S	Was a chemical/bacteriologi			YES	NO	; If yes,	what mo/day/yr wa		
	submitted			Was V	Vater Well Disinfe	cted? (YES N	0	
TYPE OF CASING USED: 1. Steel 3. RPM (5	5. Wrought Iron	7. Fiberglass		her (Specify	below) CASII	NG JOINTS: (Threaded	
2. PVC 4. ABS	6. Asbestos-Cer	ment 8. Concrete	tile SDF	R-26			Welded	Clamped	
Blank casing diameter 5	in. to 55	ft., Dia.	in.	to	ft., D	ia.	in. to	ft.	
Casing height above land surface:	12 in.,	Weight:	2.35 Ib	s. / ft.	Wall thic	kness or gau	ge No214		
TYPE OF SCREEN OR PERFORATION MATERIAL:									
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify) 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)									
2. Brass 4. Galvanized	6. Concrete Tile	8. RMP (SR)	10. A	sbestos-Cer	nent 12. Non	e usea (open	i noie)		
SCREEN OR PERFORATION OPENII 1. Continuous slot 3. Mill		zed wrapped	7 T o	ch cut	9. Drille	d holes	11. None (o	oen hole)	
		••	8. Sa			(specify)	, ,, ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		
		wrapped							
SCREEN - PERFORATION INTERVAL	- ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	55 ft. to		ft.,	From	ft.	to	ft.	
CDAVEL BACK INTERVALS:	From	ft. to 24 ft. t	。 。 80	ft.,	From	ft.	to	ft.	
GRAVEL PACK INTERVALS:	110111		0	ft.,	From From	ft.	to	ft.	
6 GROUT MATERIALS: 1 No.	From			ft.,		ft. Other hent	tonite hole plu	ft.	
<u> </u>		2. Cement Grout	ft.	. Bentonite to	ft.,	From	ft. to	g ft.	
What is the nearest source of possible	contamination:	,					15. Oil well/G		
1. Septic tank 4. Lateral lines					13. Insectio	_	46 Other (en		
2. Sewer lines 5. Cess Pool 5. Sewage lagoon 17. Tuto storage lagoon 14. Abandon water well									
2. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage Direction from well? West					How many feet? 20				
From To	LITHOLOGIC L	.OG	From	То			OGIC LOG		
0 4 topsoil									
4 18 clay		 							
18 80 shale	- 61-								
			+						
									
Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and									
was completed on (mo/day/year) 12-19-2006 and this record is true to the best of my knowledge and belief.									
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 12-27-2006									
under the business name of Harp Well and Pump Service by (signature) Todd S. Horb									