LOCATION OF WAT	ER WELL:	FRACTION SW NW SW NE				orm W	CTION NUMBER		82a-1212 TOWNSHIP NUMBER		RANGE NUMBER	
Sedgwick		366 1/2	O 8 8 7	1/4	ME	1/4	8	Т	27 s	R	2E	E/W
	om nearest town or city s			•								
1968 N. Red		Wich:	ita, Kans									
RR#,ST. ADDRES		W. 21st N.							Board of A	griculture, Divisio	n of Wat	ter Resourc
	•	ita, Kansas				Z	ZIP CODE:		Application N	lumber:		
LOCATE WELL'S I		EPTH OF COM	IPLETED V	VELL:	70	ft.		ELEVATION	V:			
WITH AN "X" IN SE N	D 4	h of groundwa	ter Encount	ered:		f	t.		ft.			ft.
:	WEI	LL'S STATIC V	VATER LEV	EL 1	15	FT. BELO	OW LAND SU	RFACE MEA	SURED ON mo	o/day/yr: 1	2/26/	06
NW	X - NE		ump test da		Vell wate			ft. after		ırs of pumping	_	gp
W	E Bo	Est. Yield: re Hole Diamet	gpm ter 1 :		Vell wate	er was to	70 ft.	ft. after and	hou in,	urs of pumping	@ to	gpi ft
	' I I	LL WATER TO	_			10	, o ii.	and	9. Dewate	44		ion well
sw · -	SE 1. I	Domestic	3. Feedlot	5. Pul	olic wate	er supply	7. Lawn a	nd garden o	nly s. Dewate	n mg	•	cify below
	1	•	4. Industria			ter suppl	•		10. Monito	ring well s, what mo/day	der wor	a aamala
s		as a chemical/bac mitted	teriological sa	imple subm	itted to De	epartment?	YES Was W	ater Well Dis	,	YES	nyi was	•
TYPÉ OF CA	SING USED:	5 141		7 5%		9 (Other (Specify		ASING JOINTS	Glued	т	hreaded
1. Steel	3. RPM (SR)				erglass	S.L.	R-26	00.017)		Welded		Clamped
2. PVC	> 4. ABS	6. Asbest	tos-Cement	8. Cor	crete tile	, SL	/K-20					
Blank casing diame		n. to	25 ft.	., D	ia.	in.	to	ft.,	Dia.	in. to)	ft.
Casing height abov		12 in.,		Weig	ht: 2	2.35	lbs. / ft.	Wai	l thickness or ga	uge No.	214	
1. Steel	OR PERFORATION 3. Stainless Steel	MATERIAL: 5. Fiberglas	is C	7. PVC		9. /	ABS	11.	Other (specify)			
2. Brass	Galvanized	6. Concrete		8. RMP			Asbestos-Cem		None used (ope	en hole)		
CREEN OR PERF	ORATION OPENINGS	S ARF										
1. Continuous slo			. Gauzed w	rapped		7. Te	orch cut	9. D	rilled holes	11. No	ne (ope	en hole)
2. Louvered shutt	ter 4. Key pui	nched 6	. Wire wrap	ped		(8. S	aw cut	10. C	ther (specify)			
CREEN - PERFOR	ATION INTERVAL	From	25	ft.	to	70	ft.,	From	ft.	to		ft.
5/122.1 · 2/1 · 5/1		From	20	ft.	to	, 0	ft.,	From	ft.	to		ft.
GRAVEL P	ACK INTERVALS:	From	24	ft,	to	70	ft.,	From	ft.	to		ft.
		From		ft.	to		ft.,	From	ft.	to		ft.
GROUT MATER	RIALS: 1. Neat ce	ement	2 Can	nent Grou			3. Bentonite			ntonite hole		
Grout Intervals:			2. 3		From	ft		ft.,	From	•	to	, ft
hat is the nearest s	source of possible con	tamination:	7. Pit privy			. Livesto						
1. Septic tank	4. Lateral I		8. Sewage				-		cticide storage	40 046		s wen cify below
2. Sewer lines	5. Cess Po		-	_		. Fuel sto	_	14. ADa	ndon water we		. (0,000	, 20 .0
3. Watertight sew Direction from well?		e pit	9. Feed ya	ıu	12	remize	er storage	How	many feet? 10	ft. plus		
From To		ITHOLOG	IC LOG		T	From	То			OGIC LO	3	
0 4	topsoil											
4 18	clay and sand	· · · · · · · · · · · · · · · · · · ·										
18 60 60 70	shale limestone											
-	Ittilestone											

				***	- 		+ +					r
							1 .					

12-28-2006

Kansas Water Well Contractor's License No. 236

This water well record was completed on (mo/day/year)

under the business name of Harp Well and Pump Service

by (signature)

Todd S. Harp