

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number		
County: Sedgwick		NE 1/4 NE 1/4 NE 1/4		19		T 27S S		R 2E E/W		
Distance and direction from nearest town or city street address of well if located within city?										
7707 E. Central, Wichita, KS 480' FNL & 350' FEL of Section 19										
2 WATER WELL OWNER: Dillon Stores, Inc.										
RR#, St. Address, Box # : PO Box 1608										
City, State, ZIP Code : Hutchinson, KS 67504-1608										
Board of Agriculture, Division of Water Resources										
Application Number:										
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 35 ft. ELEVATION:								
		Depth(s) Groundwater Encountered 1. 24 ft. 2. ft. 3. ft.								
		WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr								
		Pump test data: Well water was ft. after hours pumping gpm								
		Est. Yield gpm: Well water was ft. after hours pumping gpm								
		Bore Hole Diameter 8.25 in. to 35 ft. and in. to ft.								
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well								
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)								
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well								
		Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted								
		Water Well Disinfected? Yes No								
5 TYPE OF BLANK CASING USED:										
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped										
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded										
3 Fiberglass Threaded X										
Blank casing diameter 4 in. to 35 ft. Dia in. to ft. Dia in. to ft.										
Casing height above land surface -12 in. weight lbs./ft. Wall thickness or gauge No. Sch 40										
TYPE OF SCREEN OR PERFORATION MATERIAL:										
1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement										
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)										
12 None used (open hole)										
SCREEN OR PERFORATION OPENINGS ARE:										
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)										
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes										
7 Torch cut 10 Other (specify)										
SCREEN-PERFORATED INTERVALS: From 35 ft. to 10 ft. From ft. to ft.										
From ft. to ft. From ft. to ft.										
GRAVEL PACK INTERVALS: From 35 ft. to 8 ft. From ft. to ft.										
From ft. to ft. From ft. to ft.										
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other										
Grout intervals: From 0 ft. to 8 ft. From ft. to ft. From ft. to ft.										
What is the nearest source of possible contamination:										
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well										
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well										
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)										
13 Insecticide storage										
Direction from well? North How many feet? 200										
LITHOLOGIC LOG										
FROM	TO	LITHOLOGIC LOG						FROM	TO	PLUGGING INTERVALS
0	3	Fill								
3	11	Clay, brown								
11	35	Clay-weathered shale, green-gray								
35		Shale, gray with gypsum seams								
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1/3/2007 and this record is true to the best of my knowledge and belief. Kansas										
Water Well Contractor's License No. 416 This Water Well Record was completed on (mo/day/yr) by (signature) Steve Fisher										
under the business name of TERRACON										