WATER WELL RECORD Form WWC-5 KSA 82a-1212 LOCATION OF WATER WELL: RANGE NUMBER FRACTION SECTION NUMBER TOWNSHIP NUMBER Sedgwick NWSE 2 27 **2E** 1/4 1/4 Т S E/W Distance and direction from nearest town or city street address of well if located within city? 13505 E. Boxthorn Wichita, Kansas LETGEND CO. WATER WELL OWNER: Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: 7309 E. 21st St. N. #110 Wichita, Kansas CITY, STATE: Application Number: ZIP CODE: 93 **ELEVATION:** 4 DEPTH OF COMPLETED WELL: LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: ft. Depth of groundwater Encountered: ft ft. WELL'S STATIC WATER LEVEL 35 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: Pump test data: Well water was ft. after hours of pumping @ gpm NW NE Est. Yield: Well water was ft. after hours of pumping @ gpm gpm Ī 12 Bore Hole Diameter ft. in. and in. WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering 5. Public water supply 7. Lawn and garden only SW SE 1. Domestic 3. Feedlot 12. Other (Specify below) 10. Monitoring well 6. Oil field water supply 8. Air conditioning 2. Irrigation 4. Industrial ; If yes, what mo/day/yr was sample (NO Was a chemical/bacteriological sample submitted to Department? submitted Was Water Well Disinfected? (YES) NO TYPE OF CASING USED: 5 CASING JOINTS: Clued Threaded 9. Other (Specify below) 7. Fiberglass 5. Wrought Iron 1. Steel 3. RPM (SR) Welded Clamped SDR-26 6. Asbestos-Cement 8. Concrete tile 2. PVC 4. ABS 5 Blank casing diameter 43 to ft.. Dia. to Dia in. to ft. Casing height above land surface: 12 Weight: 2.35 lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 3. Stainless Steel 7. PVC 9 ABS 11. Other (specify) 1. Steel 5. Fiberglass 8. RMP (SR) 12. None used (open hole) 2. Brass 4. Galvanized 6. Concrete Tile 10. Asbestos-Cement SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 8. Saw cut 10. Other (specify) 6. Wire wrapped 4. Key punched SCREEN - PERFORATION INTERVAL 43 93 ft. ft.. From to From ft. From ft. to ft., From ft. to ft. **GRAVEL PACK INTERVALS:** 24 ft. 93 From ft.. From ft. to ft. From ft. to ft.. From ft ft. GROUT MATERIALS: Other bentonite hole plug 1. Neat cement 2. Cement Grout 3. Bentonite Grout Intervals: ft. 24 From ft.. ft to ft., From ft. What is the nearest source of possible contamination: 10. Livestock pens 15. Oil well/Gas well 7. Pit privy 13. Insecticide storage 1. Septic tank 4. Lateral lines 16. Other (specify below) 11. Fuel storage 8. Sewage lagoon 14. Abandon water well 5. Cess Pool 2. Sewer lines 3. Watertight sewer line 12. Fertilizer storage 9. Feed yard 6. Seepage pit South Direction from well? How many feet? 20 ft. plus LITHOLOGIC LOG From LITHOLOGIC LOG From Τo Τо topsoil clav 18 93 shale

under my jurisdiction and Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged 2-28-2007 was completed on (mo/day/year) and this record is true to the best of my knowledge and belief. 3-2-2007

Kansas Water Well Contractor's License No. 236

This water well record was completed on (mo/day/year)

under the business name of Harp Well and Pump Service

by (signature)

Todd S. Harb