			WATER WE	ELL RECORI	D Fo	rm WW	C-5 K	SA 82a-121	2		
1 LOCATION	OF WATER	WELL:	FRACTION			SECTI	ON NUMBER	TOWNSHIP	NUMBER	RANGE NU	JMBER
□ Sedgwi	ck		SE 1/4	SW 1/4	NW ·	1/4	11	т 27	7 s	R 2E	E/W
Distance and di	rection from	nearest town or cit	ty street address of well	if located within city?							
13025 E. Reeds Cove Ct. Wichita, Kansas											
2 WATER	WELL O	WNER: RO	BL CONSTRU	CTION							
RR#,ST. A	DDRESS,I	BOX #: 584	2 W. 21st N.			Board of Agriculture, Division of Water Resource					
	CITY, S	STATE: Wie	chita, Kansas		ZIP CODE: Application Number:						
3 LOCATE V	WELL'S LOC	CATION 4	DEPTH OF COMPL	ETED WELL:	93	ft.		ELEVATION:			
WITH AN	"X" IN SECT	TION BOX:	epth of groundwater			ft.			ft.		ft.
l 1	N				50 F			DEADE MEADU		2/16	
		1 1	VELL'S STATIC WA		-		V LAND SU	RFACE MEASU			
N	₩	- NE		•	Well water			ft. after		s of pumping @	gpm
₩ <u>₩</u>	1	: L I	Est. Yield:	1.0	Well water			ft. after		s of pumping @	gpm
			Bore Hole Diameter	""		to 93	3 ft.	and	in.	to	ft.
Гs	WELL WATER TO BE USED AS: 1. Domestic 3. Feedlot 5. Public water su						7 Lawn a	nd garden only	9. Dewateri	ng ,	ction well
"	12. Other (Specify									ecify below)	
	2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well Was a chemical/bacteriological sample submitted to Department? YES NO ; If yes, what mo/day/yr was sample										vas sample
submitted Was a chemical/bacteriological sample submitted to Department? YES Was Water Well Disinfected? YES NO YES NO NO NO NO NO NO NO NO NO N											
5 TYPE OF CASING USED: CASING JOINTS, Chied Threaded											
	Steel	3. RPM (\$	SR) 5. Wrought	Iron 7. Fib	erglass			below) CAS	iivo Jolivio.	Welded	Clamped
2.1	PVC	4. ABS	6. Asbestos	-Cement 8. Co	ncrete tile	SDR	R-26			VV Claea	Clarriped
Blank casin		_	in. to	93 ft.,	Dia.	in.	to	ft.,	Dia.	in. to	ft.
	•	_	10								
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)											
1,500											
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)											
SCREEN OR PERFORATION OPENINGS ARE:											
1. Continu	uous slot	3. Mill	slot 5. G	Sauzed wrapped		7. Tor	ch cut	9. Drill	ed holes	11. None (c	pen hole)
2. Louver	ed shutter	4. Key	punched 6. V	Vire wrapped		8. Sav	v cut	10. Oth	er (specify)		
SCREEN - F	EBEORA.	TION INTERVAL	- From	53 ft.	to	93	ft.,	From	4	40	4
JOOKEEN	LIN ONA	HOW HAT ENVAL				75			ft.	to	ft.
			From	ft.	to	00	ft.,	From	ft.	to	ft.
GR.	AVEL PAC	CK INTERVALS:	From	24 ft.	to	93	ft.,	From	ft.	to	ft.
			From	ft.	to		ft.,	From	ft.	to	ft.
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout						3	Bentonite		Other bent	tonite hole pla	ug
Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to									ft.		
What is the nearest source of possible contamination:											
1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide								cide storage	15. Oil well/0		
2. Sewer	lines	5. Cess	s Pool 8.	Sewage lagoon	11	. Fuel stor	age	14. Aband	on water well	16. Other (sp	ecify below)
3. Waterti	aht sewei	line 6. See	page pit 9.	Feed yard	12	. Fertilizer	storage				
Direction fro		South						How ma	any feet? 10	ft. plus	
From	То		LITHOLOGIC	CLOG		From	To		LITHOLO	OGIC LOG	
0		topsoil									
4		clay									
15		shale									

											···
\vdash											
											- t
-											
\vdash											
-											
											
7											
Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and											
was completed on (mo/day/year) 3-16-2007 and this record is true to the best of my knowledge and belief.											
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 3-21-2007											
under the business name of Harp Well and Pump Service by (signature) Todd S. Horb)