			WATERV	VELL RE	CORD	Form W	WC-5 F	(SA 82a-12	12		
1 LOCATION OF V		VELL:	FRACTION	NIE	077		CTION NUMBE		IP NUMBER	RANGE N	_
Sedgwick			NE 1/4		1/4 SW	1/4	2	Т 2	7 s	R 21	E E/W
		earest town or city st			vithin city?						
13508 E. N			Vichita, Ka FERPIECE		S INC						
2 WATER WE			SW Butler		5 INC.				Board of Agri	culture, Division of V	Vater Resource
	XESS,6 XITY, ST		ill, Kansas	Ku.			ZID CODE.		Application Num	hor	
				DI ETED W	T	97 ft.	ZIP CODE:	ELEVATION:	Application Nutr	idei .	
3 LOCATE WELL WITH AN "X" IN		ON BOX:	EPTH OF COM					ELEVATION:	_		
	N		h of groundwat				t.		ft.		ft.
		WEI	LL'S STATIC W				OW LAND S		URED ON mo/d		4/07
, VM		NE .		ump test da		ater was		ft. after		of pumping @	gpn
ww			Est. Yield:	gpm		ater was	0.5	ft. after		of pumping @	gpm
1 1 1	XI —		re Hole Diamete			to	97 f	t. and	in.	to	ft.
	-		LL WATER TO Domestic	BE USED A B. Feedlot		ater sunnly	C7 Lawn	and garden on	9. Dewaterii	'e	ction well
		· ""		. Industrial			y 8. Air co		10. Monitorin		pecify below
I <u> </u>	s		s a chemical/bact				YES	(NO)		what mo/day/yr v	was sample
	3		mitted					Water Well Disir	nfected?	YES	NO
5 TYPE OF	CASIN	G USED:	5 Wrough	at Iron	7. Fiberglas	9. (Other (Specif	v below) CA	SING JOINTS: (Glued	Threaded
1. Stee	1	3. RPM (SR)			Ü	CT.	R-26	, ,		Welded	Clamped
2. PVC		4. ABS	6. Asbest	os-Cement	8. Concrete	tile SL	/IX-2U				,
Blank casing dia	ameter	5 ir	n. to	47 ft.,	Dia.	in.	to	ft.,	Dia.	in. to	ft.
Casing height a	above la	nd surface:	12 in.,		Weight:	2.35	lbs. / ft.	Wall t	hickness or gaug	ge No214	
		PERFORATION	-								
1. Steel		Stainless Steel	5. Fiberglas	s (7. PVC	9.	ABS	11. O	ther (specify)		
2. Brass	4. 0	Salvanized	6. Concrete	Tile	8. RMP (SR	10.	Asbestos-Ce	ment 12. N	one used (open	hole)	
SCREEN OR DE		ATION OPENINGS	e ADE:			•					
				Gauzed w	ranned	7 T	orch cut	9 Dri	lled holes	11 None (onen hole)
1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut											
2. Louvered s	hutter	4. Key pur	nched 6.	Wire wrap	ped	<u>8. s</u>	aw cut	10. Oth	ner (specify)		
SCREEN - PERF	ORATI	ON INTERVAL	From	47	ft.	to 97	ft.,	From	ft.	to	ft.
			From		ft.	to	ft.,	From	ft.	to	ft.
GRAVE	L PACK	(INTERVALS:	From	24	ft.	to 97	ft.,	From	ft.	to	ft.
					ft.	to	-	From			
		_	From		п.	10	ft.,	Fiom	ft.	to	ft.
GROUT MA		1. 11041 0			ent Grout		3. Bentonit		Other bent	onite hole pl	ug
Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to											ft.
What is the nearest source of possible contamination: 1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage								15. Oil well/0	Gas well		
9 Source large 11 First storage 44 About								don water well	16. Other (s	pecify below)	
2. Sewer lines			,,,	_	-	12. Fertiliz	-	r-r. r.bum			
3. Watertight		ine 6. Seepag South	e pit	9. Feed yar	u	12. Ferunz	er storage	Ном т	nany feet? 50 f	ft plue	
Direction from w			ITHOLOG	C I OC		From	То	T TOW II		GIC LOG	
	0 1		ITHOLOG	C LOG		From	10	1	LITHOLO	GIC LOG	
0 4 4 1		opsoil lav						<u> </u>			·
15 80		hale						1			· · · · · · · · · · · · · · · · · · ·
80 9		me and shale				-		<u> </u>			
		ine and share									
							_				
							+				
	1					_					
7 Contractor	's or Lai	ndowner's Certifica	ation: This water	er well was 1	construct	ed) 2. I	econstructe	ed or 3.	plugged	under my jurisdic	tion and
was complete	d on (m	o/day/year)	4-24-200	7	and this recor	d is true to the	ne best of my	knowledge and	belief.		
,	•	ontractor's License	a No. 236				_	d on (mo/day/ye		-2007	
				~				,			
under the busi	iness na	ame of Harp V	vell and Pu	mp Serv	ıce	by (signature)	T	oaa S	. Hart)