WATER WELL RECORD F	orm WWC-5 KSA 82a-1212
1 LOCATION OF WATER WELL: FRACTION	SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER
Sedgwick NW 1/4 SE 1/4 SE	1/4 2 T 27 S R 2E E/W
Distance and direction from nearest town or city street address of well if located within city?	
13804 Mainsgate Wichita, Kansas	
2 WATER WELL OWNER: HOPPER, Jim	
RR#,ST. ADDRESS,BOX #: 13804 Mainsgate	Board of Agriculture, Division of Water Resource
CITY, STATE: Wichita, Kansas	ZIP CODE: Application Number:
3 LOCATE WELL'S LOCATION 4 DEPTH OF COMPLETED WELL: 12	
WITH AN "X" IN SECTION BOX:	
Depth of groundwater Encountered:	
WELL'S STATIC WATER LEVEL 65	FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 5/16/07
Pump test data: Well wat	
(a) Est. Yield: gpm Well wat	, , , ,
Est. Yield: gpm Well wat Bore Hole Diameter 12 in.	to 127 . ft. and in. to ft.
├─ WELL WATER TO BE USED AS:	9. Dewatering 11. Injection well
1. Domestic 3. Feedlot 5. Public was	er supply 12. Other (Specify below
2. Irrigation 4. Industrial 6. Oil field w	. If we are the transfer of the contract of th
S Was a chemical/bacteriological sample submitted to D	
submitted	Was Water Well Disinfected? YES NO
TYPE OF CASING USED: 5. Wrought Iron 7. Fiberglass	Other (Specify below) CASING JOINTS: Glued Threaded
1. Steel 3. RPM (SR)	SDR-26 Welded Clamped
2. PVC 4. ABS 6. Asbestos-Cement 8. Concrete ti	e
Blank casing diameter 5 in. to 60 ft., Dia.	in. to ft., Dia. in. to ft.
Casing height above land surface: 12 in., Weight:	2.35 lbs. / ft. Wall thickness or gauge No214
TYPE OF SCREEN OR PERFORATION MATERIAL:	TAKT
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC	9. ABS 11. Other (specify)
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR)	10. Asbestos-Cement 12. None used (open hole)
, ,	10. Addicates Actions 12. Hollo descriptions
SCREEN OR PERFORATION OPENINGS ARE:	
1. Continuous slot 3. Mill slot 5. Gauzed wrapped	7. Torch cut 9. Drilled holes 11. None (open hole)
2. Louvered shutter 4. Key punched 6. Wire wrapped	8. Saw cut 10. Other (specify)
	127 ft., From ft to ft.
SCREEN - PERFORATION INTERVAL From 60 ft. to	
From ft. to	ft., From ft. to ft.
GRAVEL PACK INTERVALS: From 24 ft. to	127 ft., From ft. to ft.
From ft. to	ft., From ft. to ft.
	10 10 10
1. Neat cement 2. Cement Grout	o. Belliolite
Grout Intervals: From 4 ft. to 24 ft., From	ft. to ft., From ft. to f
What is the nearest source of possible contamination: 1. Septic tank 4. Lateral lines 7. Pit privy	0. Livestock pens 13. Insecticide storage 15. Oil well/Gas well
9 Sawara Israan	46 Other (enecify below
2. Sewer lines 5. Cess Foot	14. Aballuoli Water Well
Watertight sewer file	2. Fertilizer storage
Direction from well? West	How many feet? 40 ft. plus
From To LITHOLOGIC LOG	From To LITHOLOGIC LOG
0 4 topsoil	
4 18 clay	
18 120 shale	
120 127 limestone	
7 Contractor's or Landowner's Certification: This water well was 1. constructed	2. reconstructed or 3. plugged under my jurisdiction and
7.14.0007	
	is true to the best of my knowledge and belief.
Kansas Water Well Contractor's License No. 236 This water w	ell record was completed on (mo/day/year) 5-18-2007
and a the business of TV VVI II IV	by (signature) Todd S. Harp
under the business name of Harp Well and Pump Service	by (signature) Toda, S. Harb