	WATER WELL RE	CORD For	rm WWC	C-5 KS.	A 82a-1212			
1 LOCATION OF WATER WELL:	FRACTION		SECTIO	ON NUMBER	TOWNSHIP N	UMBER	RANGE NUME	BER
Sedgwick Sedgwick	SW 1/4 SE		1/4	11	T 27	_ S	R 2E	E/W
Distance and direction from nearest town or cit		ithin city?						
13221 E. Bridlewood	Wichita, Kansas							
	FT, Troy					Board of Agri	iculture, Division of Wate	r Resource
RR#,ST. ADDRESS,BOX #: 13221 E. Bridlewood CITY, STATE: Wichita, Kansas			710	CODE		Application Nur	nhae	
		ELL: 95	ft.	CODE:	ELEVATION:	Application Nur	nder:	
3 LOCATE WELL'S LOCATION 4 WITH AN "X" IN SECTION BOX:	DEPTH OF COMPLETED W				ELEVATION:	_		_
	epth of groundwater Encounte		ft.			ft.		ft.
	VELL'S STATIC WATER LEVI	_		V LAND SUF	RFACE MEASUR			
NA NE	Pump test da				ft. after		s of pumping @	gpm
₩ X E	Est. Yield: gpm Bore Hole Diameter 12	Well water	rwas to 95		ft. after		s of pumping @	gpm
	Bore Hole Diameter 12 WELL WATER TO BE USED A		10 93	5 ft.	and	in.	to ina 11. Injectio	ft. on well
sw se	1. Domestic 3. Feedlot	5. Public wate	rsupply <	7. Lawn ar	d garden only	9. Dewateri	ing 11. injects 12. Other (Spec	
	2. Irrigation 4. Industria			8. Air cond		10. Monitori		, 20.01.,
S	Was a chemical/bacteriological sa	mple submitted to De	partment?	YES	NO		what mo/day/yr was	•
	submitted			Was W	ater Well Disinfe	ted?	YES NO	
5 TYPE OF CASING USED:	5. Wrought Iron	7. Fiberglass	9. Oth	ner (Specify I	below) CASI	NG JOINTS:	Glued T	hreaded
1. Steel 3. RPM (\$	6. Asbestos-Cement	8. Concrete tile	SDR	-26			Welded C	lamped
2. PVC 4. ABS					4 5			
Blank casing diameter 5	in. to 55 ft.		in.	to	ft., D	ia.	in. to	ft.
Casing height above land surface:	12 _{in.,}	Weight: 2	2.35 lbs	s. / ft.	Wall thic	kness or gau	ge No214	
TYPE OF SCREEN OR PERFORATIO		7 000	0.40		11 Othe	or (enecify)		
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify) 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)								
Brass 4. Galvanized	6. Concrete Tile	8. RMP (SR)	10. AS	besios-cem	ent 12. Non	e useu (opei	i noie)	
SCREEN OR PERFORATION OPENII		_			0.0-111-		44 None (
1. Continuous slot 3. Mill	slot 5. Gauzed w	rapped	7. Tor	ch cut	9. Drille	a noies	11. None (ope	en noie)
2. Louvered shutter 4. Key	punched 6. Wire wrap	ped	8. Sav	v cut	10. Other	(specify)		
SCREEN - PERFORATION INTERVAL	. From 55	ft. to	95	ft.,	From	ft.	to	ft.
	From	ft. to		ft.,	From	ft.	to	ft.
GRAVEL PACK INTERVALS:	From 24	ft. to	95	ft.,	From	ft.	to	ft.
STONE THORNWELL WILL	From	ft. to	,,,		From			
- L OPOUT MATERIALS				ft.,		ft.	to	ft.
GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hole plug								
Grout Intervals: From	4 ft. to 24	ft., From	ft.	to	ft.,	From	ft. to	ft.
What is the nearest source of possible contamination: 1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well						s well		
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below)								
2. 60	page pit 9. Feed ya	rd 12	2. Fertilizer	storage				
Direction from well? East How many feet? 10 ft. plus								
From To	LITHOLOGIC LOG		From	To			OGIC LOG	
0 4 topsoil								
4 12 clay								
12 95 shale								
	. <u> </u>	······································						
	·							
7 Contractor's or Landowner's Cer								
C 4005								
was completed as (maldaubias)				constructed	• •	olugged	under my jurisdictio	n and
was completed on (mo/day/year)	6-6-2007	and this record i	s true to the	e best of my	knowledge and b	elief.		n and
was completed on (mo/day/year) Kansas Water Well Contractor's Lic	6-6-2007	and this record i	s true to the	e best of my	knowledge and b	elief.	under my jurisdiction 8-2007 S. Howb	on and