WATER WELL RECORD Form WWC-5 Division of Water Resources; App. No.

1 LOCATION OF WATER WELL: County: Sedgwick	Fraction SE ¼ SW ¼ SE ¼	Section Number 19	Township Number T 27 S	Range Number R 2 E/W

Distance and direction from nearest town or city street address of well if located within city?
7310 E. Kellogg, Wichita, KS

Global Positioning Systems (decimal degrees, min. of 4 digits)
Latitude:
Longitude:
Elevation:
Datum:
Data Collection Method:

2 WATER WELL OWNER: RR#, St. Address, Box # City, State, ZIP Code: Rusty Eck Ford, Inc. 7310 E. Kellogg Wichita, KS 67207-1608

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

N
W --NW-- --NE-- E
--SW-- --SE--
S

4 DEPTH OF COMPLETED WELL 24.1 ft.

Depth(s) Groundwater Encountered (1) ft. (2) ft. (3) ft.
WELL'S STATIC WATER LEVEL 6.9 ft. below land surface measured on mo/day/yr 6-12-07
Pump test data: Well water was ft. after hours pumping gpm
Est. Yield gpm: Well water was ft. after hours pumping gpm
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Domestic (lawn& garden) 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yrs
Sample was submitted Water well disinfected? Yes No X

5 TYPE OF CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded
2 PVC 4 ABS 7 Fiberglass Threaded X
Blank casing diameter 2 in. to 9.1 ft., Diameter in. to ft., Diameter in. to ft.
Casing height above land surface in., Weight lbs./ft. Wall thickness or guage No. SCH40
TYPE OF SCREEN OR PERFORATION MATERIAL:
1 Steel 3 Stainless Steel 5 Fiberglass 7 PVC 9 ABS 11 Other (Specify)
2 Brass 4 Galvanized Steal 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:
1 Continuous slot 3 Mill slot 5 Guazed wrapped 7 Torch cut 9 Drilled holes 11 None (open hole)
2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify)
SCREEN-PERFORATED INTERVALS: From 24.1 ft. to 9.1 ft., From ft. to ft.
From ft. to ft., From ft. to ft.
GRAVEL PACK INTERVALS: From 24.1 ft. to 8 ft., From ft. to ft.
From ft. to ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Cement
Grout Intervals: From 8 ft. to 0.5 ft., From 0.5 ft. to 0 ft., From ft. to ft.
What is the nearest source of possible contamination:
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 13 Insecticide Storage 16 Other (specify below) Parking lot
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 14 Abandoned water well
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer Storage 15 Oil well/gas well
Direction from well? Immediate vicinity How many feet? Immediate vicinity

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	0.5	Clay fill with sand and gravel	24.1	8	10/20 Sand
0.5	5	Fill clay with gravel	8	0.5	3/8 Bentonite chips
5	10	Blue/grey lean clay	0.5	0	Cement
10	15	Brown lean clay			
15	24.2	Brown fat clay			
					MW-9

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-8-07 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 665 This Water Well Record was completed on (mo/day/year) 6-20-07 under the business name of Pratt Well Environmental by (signature) Glenn E. Ezell

INSTRUCTIONS: Use typewriter or ball point pen. *PLEASE PRESS FIRMLY* and *PRINT* clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1 000 SW Jackson St., Suite 420, Topeka, Kansas 66612- 1 367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of $5.00 for each constructed well. Visit us at http://www.kdhe.state.ks.us/gw/waterwells.

KSA 82a-1212