CONTINO NEW NAME   FINAL NAME   SE   1/4   2   T   27   S   R   2E   EW
Same   Control of the control of t
Wichita, Kansas   Wichita, Kansas   CENTZ, Aaron   Soard of Agriculture, Division of Water Resource   Agriculture, Division of Page   Agri
WATER WELL OWNER: CENTZ, AARON   13917 Ayesbury   Based of Agriculture, Division of Weller Resource CITY, STATE: Wichita, Kansas   ZIP CODE: Application Number: Number: Application Number: Number: Application Number: Number: Application Number: Number: Number: Application Number:
RRS.T. ADDRESS, BOX# . 1391.7 Ayesbury
CREEN OR PERFORATION OPENINGS ARE:  1. Store   3. Stainless Size   5. Fiberglass   5. Fibergla
Depth of Completed Well   STATIC WATER LEVEL   97 ft.   ELEVATION:   ft.   f
Depth of groundwater Encountered:  WELL'S STATIC WATER LEVEL  Beth of groundwater Encountered:  WELL'S STATIC WATER LEVEL  Well water was the after hours of pumping @ gpm Bore hole Diameter 12 in. to 97 ft. and in. to ft. after hours of pumping @ gpm Well water was the after hours of pumping @ gpm Well water was the after hours of pumping @ gpm Well water was the after hours of pumping @ gpm Well water was the after hours of pumping @ gpm Well water was the after hours of pumping @ gpm Well water was the after hours of pumping @ gpm Well water was the after hours of pumping @ gpm Well water was the after hours of pumping @ gpm Well water was the after hours of pumping @ gpm Well water was the after hours of pumping @ gpm Well water was the after hours of pumping @ gpm Well water was the after hours of pumping @ gpm Well water was the after hours of pumping @ gpm Well water was the after hours of pumping @ gpm Well water was the after hours of pumping @ gpm Well water was the after hours of pumping @ gpm Well water was the after hours of pumping @ gpm Well water was the after hours of pumping @ gpm No the after hours of pumping Well water was the after hours of pumping Wes states upply & A ft concerns the after hours of pumping Well water was the after hours of pumping West was sample water supply & A ft concerns the after hours of pumping West was sample was after supply & A ft concerns the after hours of pumping Well water was the after hours of pumping Well water was the after ho
WELL'S STATIC WATER LEVEL Pump test data: Veli water was t. a. after hours of pumping @ gpm Bore Hole Diameter 12 in. to 97 ft. and in. to ft. SWELL WATER TO BE USED AS: 1. Domestic S. Feedlot 5. Public water supply Lawn and garden only. 2. Irrigation 4. Industrial 6. (i) if field water supply 8. Air conditioning well was sample submitted bepartmen?  TYPE OF CASING USED: 1. Steel 3. RPM (SR) 5. Wought Iron 7. Fiberglass 9. Other (Specify below)  TYPE OF CASING USED: 1. Steel 3. RPM (SR) 5. Wought Iron 7. Fiberglass 9. Other (Specify below)  SDR-26  SDR-26  Well water was 1. a. after hours of pumping @ gpm In. to ft. In. log in. to ft. Was water was pumping @ gpm In. to graph in. to ft. Was water was in. and garden only. 1. Steel 3. RPM (SR) 1. Steel 3. RPM (SR) 5. Wought Iron 7. Fiberglass 9. Other (Specify below)  SDR-26  SDR-26  SDR-26  Well water was 1. a. after hours of pumping @ gpm In. to ft. Continuous side in. to ft. Dia. Dia. Dia. Dia. Dia. Dia. Dia. Dia
Pump test data: Well water was ft. after hours of pumping @ gpm Bore Hole Diameter 12 in. to 97 ft. and in. to ft. well. WATER TO BE USED AS: 1. Domestic 3. Feedlot 5. Public water supply Lawn and garden only 11. Injection well 12. Inrigation 4. Industrial 6. Oil field water supply Was a chemical/backeriological sample submitted to Department? YES NO 11. Post No 11. Injection well 12. Inrigation 4. Industrial 6. Oil field water supply YES NO 11. West Vater Well Disinfected? YES NO 11. Steel 3. RPM (SR) 5. Whought Iron 7. Fiberglass 9. Other (Specify below) CASING JOINTS: Glued Clamped SDR-26
Est. Yield: gpm Well water was to 97 ft. and in. to to to to to 97 ft. and in. to 12 in. and in. to 12 in. and in. to 13 in. and in. to 14 in. in. to 15 in. to 97 ft. and in. to 15 in. to 15 in. to 15 ft. place in. Threaded Clamped Submitted Submitted to Department? Submitted Submitted to Department? Submitted Submitted in Department? Submitted in Department? Submitted Submitted in Department? Submitted in Depart
WELL WATER TO BE USED AS: 1. Domestic 3. Feedlot 5. Public water supply 1. Lawn and garden only 12. Other (Specify below submitted 12. Other (Specify below Submitted 12. Infragation 4. Industrial 6. Oil field water supply Was a chemical/bacteriological sample submitted 15. Sheet 1.
WELL WATER TO BE USED AS: 1. Domestic 3. Feedlot 5. Public water supply 1. Lawn and garden only 12. Other (Specify below submitted 12. Other (Specify below Submitted 12. Infragation 4. Industrial 6. Oil field water supply Was a chemical/bacteriological sample submitted 15. Sheet 1.
2. Irrigation 4. Industrial 6. Oil field water supply submitted to Department?  10. Monitoring well if yes, what moldarly/r was sample submitted to Department?  11. Steel 3. RPM (SR) 5. Wrought Iron 7. Fiberglass 9. Other (Specify below) CASING JOINTS: Glued Clamped SDR-26  12. In., Weight 2.35 lbs. / ft. Wall thickness or gauge No214  1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify) 2. Brass 4. Galvanized 6. Concrete file 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)  SCREEN OR PERFORATION OPENINGS ARE:  1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole)  SCREEN - PERFORATION INTERVAL From 57 ft. to 97 ft., From ft. to ft. From ft. T
Wes a dremical/bacteriological sample submitted to Department? VES NO  TYPE OF CASING USED: 1. Sleel 3. RPM (SR) 5. Wrought Iron 7. Fiberglass 9. Other (Specify below) CASING JOINTS. Glued Threaded Clamped 2. PVC 4. ABS 6. Asbestos-Cernent 8. Concrete title SDR-26  SDR-26  SDR-26  SDR-26  Casing height above land surface: 12 in, Weight 2.35 lbs. / ft. Wall thickness or gauge No. , 214  TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Sheel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify) 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cernent 12. None used (open hole)  SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole)  SCREEN OR PERFORATION INTERVAL From ft. to ft. From ft.
TYPE OF CASING USED: 1. Steel 3. RPM (SR) 2. PVC 4. ABS 6. Asbestos-Cement 8. Concrete tile SDR-26  Blank casing diameter 5 in. to 57 ft., Dia. in. to ft., Dia. in. to ft.  Casing height above land surface: 12 in., Weight 2.35 ibs. / ft. Wall thickness or gauge No214  TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify) 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)  SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole)  SCREEN - PERFORATION INTERVAL From 57 ft. to 97 ft., From ft. to ft.  GRAVEL PACK INTERVALS: From 24 ft. to 97 ft., From ft. to ft.  From ft. to ft., From ft. to ft.  From ft. to ft., From ft. to ft.  From ft. to f
1. Steel 3. RPM (SR) 6. Asbestos-Cement 8. Concrete tile SDR-26  2. PVC 4. ABS 6. Asbestos-Cement 8. Concrete tile SDR-26  SDR-26  SDR-26  SDR-26  SDR-26  Welded Clamped Clamped Clamped Clamped Part Steel Spr. Spr. Spr. Spr. Spr. Spr. Spr. Spr.
1. Steel 3. RPM (SR) 6. Asbestos-Cement 8. Concrete tile SDR-26  Blank casing diameter 5 in. to 57 ft., Dia. in. to ft., Dia. in. to ft.  Casing height above land surface: 12 in., Weight: 2.35 lbs./ft. Wall thickness or gauge No214  TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify) 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)  SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole)  2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify)  SCREEN - PERFORATION INTERVAL From 57 ft. to 97 ft., From ft. to ft.  From ft. to ft., From ft. to ft.  GRAVEL PACK INTERVALS: From 24 ft. to 97 ft., From ft. to ft.  From ft. to ft., From ft. to ft.  GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft.  Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft.  Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft.  Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft.  Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft.  Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft.  Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft.  Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft.  What is the nearest source of possible contamination: 1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well ft.  Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage 14. Abandon water well 16. Other (specify below) 15. Oil well/Gas well 16. Other (specify below) 15. South 15. Oil well/Gas well 16. Other (specify below) 15. South 15. Oil well/Gas well 16. Other (specify below) 15. South 15. Oil well/Gas well 16. Other (specify below) 15. South 15. O
Blank casing diameter 5 in. to 57 ft., Dia. in. to ft., Dia. in. to ft.  Casing height above land surface: 12 in., Weight: 2.35 lbs. / ft. Wall thickness or gauge No214  TYPE OF SCREEN OR PERFORATION MATERIAL:  1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)  2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)  SCREEN OR PERFORATION OPENINGS ARE:  1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole)  2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify)  SCREEN - PERFORATION INTERVAL From 57 ft. to 97 ft., From ft. to ft.  From ft. to ft., From ft. to ft.  GRAVEL PACK INTERVALS: From 24 ft. to 97 ft., From ft. to ft.  From ft. to ft.  GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hole plug Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft.  Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well 16. Other (specify below)  2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below)  4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well 16. Other (specify below)  4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well 16. Other (specify below)  4. Watertight sever line 6. Seepage pit 9. Feed yard 12. Fertilizer storage 15. Oil well/Gas well 16. Other (specify below)  4. Lateral lines 7. Pit privy 10. Livestock pens 12. Fertilizer storage 15. Oil well/Gas well 16. Other (specify below)  4. Lateral lines 7. Pit privy 10. Livestock pens 12. Fertilizer storage 15. Oil well/Gas well 16. Other (specify below)  4. Lateral lines 7. Pit privy 10. Livestock pens 12. Fertilizer storage 15. Oil well/Gas well 16. Other (specify below)
Casing height above land surface: 12 in., Weight: 2.35 ibs. / ft. Wall thickness or gauge No. ,214  TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify) 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)  SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole)  SCREEN OR PERFORATION INTERVAL From 57 ft. to 97 ft., From ft. to ft.  GRAVEL PACK INTERVALS: From 24 ft. to 97 ft., From ft. to ft.  From ft. to ft., From ft. to ft.  From ft. to ft., From ft. to ft.  SCRUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Grout Intervals: From 4 ft. to 24 ft., From ft. to ft.  Septit tank 4. Lateral lines 7. PVC 9. ABS 11. Other (specify)  SCREEN - PERFORATION INTERVAL From 57 ft. to 97 ft., From ft. to ft.  From ft. to ft., From ft. to ft.  GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hole plug Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft.  Septit tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well 15. Septic tank 4. Lateral lines 9. Feed yard 12. Fertilizer storage 14. Abandon water well 16. Other (specify below) 12. Fertilizer storage How many feet? 15 ft. plus How many feet? 15 ft. plus 15 lay 15
TYPE OF SCREEN OR PERFORATION MATERIAL:  1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)  2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)  SCREEN OR PERFORATION OPENINGS ARE:  1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole)  2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify)  SCREEN - PERFORATION INTERVAL From 57 ft. to 97 ft., From ft. to ft.  From ft. to ft., From ft. to ft.  GRAVEL PACK INTERVALS: From 24 ft. to 97 ft., From ft. to ft.  From ft. to ft., From ft. to ft.  From ft. to ft., From ft. to ft.  SGROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft.  Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well 14. Abandon water well 16. Other (specify below)  Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage Direction from well? South LITHOLOGIC LOG From TO LITHOLOGIC LOG 14 to psoil 4 15 clay 15 kg lay
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)  SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole)  2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify)  SCREEN - PERFORATION INTERVAL From 57 ft. to 97 ft., From ft. to ft.  From ft. to ft., From ft. to ft.  GRAVEL PACK INTERVALS: From 24 ft. to 97 ft., From ft. to ft.  From ft. to ft., From ft. to ft.  GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft.  Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well 15. Oil well/Gas well 16. Other (specify)  Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage 15. Dius  From To LITHOLOGIC LOG From To LITHOLOGIC LOG 15. 80 shale
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)  SCREEN OR PERFORATION OPENINGS ARE:  1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole)  2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify)  SCREEN - PERFORATION INTERVAL From 57 ft. to 97 ft., From ft. to ft.  From ft. to 97 ft., From ft. to ft.  GRAVEL PACK INTERVALS: From 24 ft. to 97 ft., From ft. to ft.  From ft. to ft., From ft. to ft.  From ft. to ft., From ft. to ft.  S. GROUT MATERIALS: 1. Neat cement to 2. Cement Grout 3. Bentonite ft., From ft. to ft.  Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft.  S. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 13. Insecticide storage 15. Oil well/Gas well 12. Sever lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below, 15. Direction from well? South How many feet? 15 ft. plus  From To LITHOLOGIC LOG From To LITHOLOGIC LOG 15. 80 shale
SCREEN OR PERFORATION OPENINGS ARE:  1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole)  2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify)  SCREEN - PERFORATION INTERVAL From 57 ft. to 97 ft., From ft. to ft.  From ft. to ft., From ft. to ft.  GRAVEL PACK INTERVALS: From 24 ft. to 97 ft., From ft. to ft.  From ft. to ft., From ft. to ft.  From ft. to ft., From ft. to ft.  GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hole plug ft.  Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft.  Nhat is the nearest source of possible contamination: 1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well 14. Abandon water well 16. Other (specify below)  3. Watertight sever line 6. Seepage pit 9. Feed yard 12. Fertilizer storage 15. Oil well/Gas well 16. Other (specify below)  4. Lopsoil How many feet? 15 ft. plus  From To LITHOLOGIC LOG From To LITHOLOGIC LOG
1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify)  SCREEN - PERFORATION INTERVAL From 57 ft. to 97 ft., From ft. to ft.  From ft. to ft., From ft. to ft.  GRAVEL PACK INTERVALS: From 24 ft. to 97 ft., From ft. to ft.  From ft. to ft.  From ft. to ft.  GROUT MATERIALS: 1. Neat cement Grout 1. Septic tank 4. Lateral lines 2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage Direction from well?  Other bentonite hole plug 13. Insecticide storage 15. Oil well/Gas well 14. Abandon water well 16. Other (specify below) 12. Fertilizer storage Direction from well?  Other bentonite hole plug 15. Oil well/Gas well 14. Abandon water well 16. Other (specify below) 15. From To LITHOLOGIC LOG 14. To psoil 4. 15. Clay 15. RO shale
2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify)  SCREEN - PERFORATION INTERVAL From 57 ft. to 97 ft., From ft. to ft.  From ft. to ft., From ft. to ft.  GRAVEL PACK INTERVALS: From 24 ft. to 97 ft., From ft. to ft.  From ft. to ft., From ft. to ft.  GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft.  South 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well 16. Other (specify below)  3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage Direction from well? South How many feet? 15 ft. plus  From To LITHOLOGIC LOG From To LITHOLOGIC LOG 15. Repair 15. Oil well/Gas well 15. Oil yell/Gas Watertight South LITHOLOGIC LOG From To LITHOLOGIC LOG 15. Oil well/Gas Watertight South LITHOLOGIC LOG From To LITHOLOGIC LOG 15. Oil well/Gas Watertight South LITHOLOGIC LOG From To LITHOLOGIC LOG 15. Oil well/Gas Watertight South LITHOLOGIC LOG From To LITHOLOGIC LOG 15. Oil well/Gas Watertight South LITHOLOGIC LOG 15. Oil well/Gas Water
SCREEN - PERFORATION INTERVAL From 57 ft. to 97 ft., From ft. to ft.  GRAVEL PACK INTERVALS: From 24 ft. to 97 ft., From ft. to ft.  From ft. to ft., From ft. to ft.  From ft. to ft., From ft. to ft.  From ft. to ft.  GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft.  Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well 1. Septic tank 4. Lateral lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below) 3. Watertight sewer line South 10. LITHOLOGIC LOG From TO LITHOLOGIC LOG 15. 80 shale
From ft. to ft., From ft. to ft.  GRAVEL PACK INTERVALS: From 2.4 ft. to 97 ft., From ft. to ft.  From ft. to ft., From ft. to ft.  GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Grout Intervals: From 4 ft. to 2.4 ft., From ft. to ft.  What is the nearest source of possible contamination: 1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well 2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below)  Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage 15. Oil well/Gas well 14. Abandon water well 16. Other (specify below)  Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage 15. Oil well/Gas well 15. Other (specify below)  LITHOLOGIC LOG From To LITHOLOGIC LOG
GRAVEL PACK INTERVALS:  From  ft.  to  ft.,  From  ft.  to  ft.  GROUT MATERIALS:  1. Neat cement  2. Cement Grout  3. Bentonite  Grout Intervals:  From  4 ft.  to  24 ft.,  From  ft.  to  6. Seepage pit  9. Feed yard  12. Fertilizer storage  15. Oil well/Gas well  16. Other (specify below)  17. Pit privy  18. Sewage lagoon  19. Feed yard  10. Livestock pens  11. Fuel storage  12. Fertilizer storage  13. Insecticide storage  14. Abandon water well  16. Other (specify below)  17. Pit privy  18. Seepage pit  19. Feed yard  19. Feed yard  10. Livestock pens  11. Fuel storage  12. Fertilizer storage  13. Insecticide storage  14. Abandon water well  15. Oil well/Gas well  16. Other (specify below)  17. Pit privy  18. Seepage pit  19. Feed yard  19. Feed yard  19. Fertilizer storage  19. Form  To  LITHOLOGIC LOG  10. LITHOLOGIC LOG  10. LITHOLOGIC LOG  11. From  To  LITHOLOGIC LOG  15. Oil well/Gas well  16. Other (specify below)  17. Pit privy  18. Seepage pit  19. Feed yard  19. Fertilizer storage  How many feet?  15. It plus  15. Oil well/Gas well  16. Other (specify below)  17. Pit privy  18. Seepage pit  19. Feed yard  19. Fertilizer storage  How many feet?  15. Oil well/Gas well  16. Other (specify below)  17. Pit privy  18. Seepage pit  19. Feed yard  19. Fertilizer storage  19. Form  To  LITHOLOGIC LOG  10. LITHOLOGIC LOG  10. LITHOLOGIC LOG  11. Fuel storage  12. Fertilizer storage  13. Insecticide storage  14. Abandon water well  16. Other (specify below)  16. Other (specify below)
From ft. to ft., From ft. to ft.  GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hole plug Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft.  What is the nearest source of possible contamination: 1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well 2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below)  Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage  Direction from well? South How many feet? 15 ft. plus  From To LITHOLOGIC LOG From To LITHOLOGIC LOG 15 ft. plus 15 clay 15 kg shale
GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hole plug  Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination: 1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well 2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below)  3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage  Direction from well? South How many feet? 15 ft. plus  From To LITHOLOGIC LOG From To LITHOLOGIC LOG 15 ft. plus  15 80 shale
GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hole plug  Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft.  What is the nearest source of possible contamination: 1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well 2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below)  Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage  Direction from well? South How many feet? 15 ft. plus  From To LITHOLOGIC LOG From To LITHOLOGIC LOG  15. 80 shale
Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination:  1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well  2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below)  3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage  Direction from well? South How many feet? 15 ft. plus  From To LITHOLOGIC LOG From To LITHOLOGIC LOG 15 clay 15 solution 15 solution 15 clay 15 solution 15 solution 15 solution 15 solution 15 solution 16 solution 16 solution 16 solution 16 solution 17 solution 18 solution 17 solution 18 solution 17 solution 18
What is the nearest source of possible contamination:  1. Septic tank  2. Sewer lines  5. Cess Pool  8. Sewage lagoon  11. Fuel storage  12. Fertilizer storage  Direction from well?  To LITHOLOGIC LOG  13. Insecticide storage  14. Abandon water well  16. Other (specify below)  17. Fit privy  18. Sewage lagoon  19. Feed yard  19. Fertilizer storage  19. From To LITHOLOGIC LOG  10. Lityestock pens  11. Fuel storage  12. Fertilizer storage  How many feet?  15. Oil well/Gas well  16. Other (specify below)  17. From To LITHOLOGIC LOG  18. Seepage pit  19. From To LITHOLOGIC LOG  19. From To LITHOLOGIC LOG  10. Lityestock pens  11. Fuel storage  12. Fertilizer storage  13. Insecticide storage  14. Abandon water well  15. Oil well/Gas well  16. Other (specify below)  16. Other (specify below)  17. Fit privy  18. Seepage pit  19. Form To LITHOLOGIC LOG  19. From To LITHOLOGIC LOG  10. Lityestock pens  11. Fuel storage  12. Fertilizer storage  13. Insecticide storage  14. Abandon water well  16. Other (specify below)  16. Other (specify below)  17. Fit privy  18. Sewage lagoon  19. Form To Lityestock pens  19. Oil well/Gas well  19. Other (specify below)  19. Feed yard  19. Oil well/Gas well  19. Oil well/Gas well  19. Oil well/Gas well  19. Other (specify below)
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below)  3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage  Direction from well? South How many feet? 15 ft. plus  From To LITHOLOGIC LOG From To LITHOLOGIC LOG  0 4 topsoil LITHOLOGIC LOG LITHOLOGIC LOG LITHOLOGIC LOG  15 80 shale
2. Sewer lines 5. Cess Pool 5. Sewage lagoon 12. Fertilizer storage    Watertight sewer line   6. Seepage pit   9. Feed yard   12. Fertilizer storage
Direction from well? South  From To LITHOLOGIC LOG From To LITHOLOGIC LOG  0 4 topsoil  4 15 clay  15 80 shale
From         To         LITHOLOGIC LOG         From         To         LITHOLOGIC LOG           0         4         topsoil         4         15         clay         15         80         shale         80         shale         15
0 4 topsoil 4 15 clay 15 80 shale
4 15 clay 15 80 shale
15 80 shale
7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and
,
was completed on (mo/day/year)  Kansas Water Well Contractor's License No. 236  This water well record was completed on (mo/day/year)  8/22/2007  under the business name of Harp Well and Pump Service  by (signature)  Todd S. Horp