	WATER WELL R	ECORD F	orm WW	/C-5 K	SA 82a-1212	2			
LOCATION OF WATER WELL:  Sedgwick  FRACTION  SW 1/4 SE 1/4 SW		1	1		NUMBER	RANGE NUMBER			
Sedgwick  Distance and direction from nearest town or	- 11		1/4	2	Т 27	S	R 2E	E/W	
2302 N. Lindsay Circle Wichita, Kansas									
2 WATER WELL OWNER: NIES CONSTRUCTION									
RR#,ST. ADDRESS,BOX #: 10333 E. 21st N. #303									
	ichita, Kansas	weii: 97		P CODE:	ELEVATION:	Application Nun	nber:		
WITH AN "X" IN SECTION BOX:	DEPTH OF COMPLETED \ Depth of groundwater Encoun	******	ft.		ELEVATION:	ft.		ft.	
N N	WELL'S STATIC WATER LEV	<b>50</b>		W LAND SH	RFACE MEASUR		day/yr: 9/21		
NW NE	NE Pump test data: Well water was ft. after hours of pumping @ gpm								
	Est. Yield: gpm		er was		ft. after	hours	of pumping @	gpm	
E	2070 7 1010 2 101110101	1 <b>2</b> in.	to 9	<b>7</b> ft.	and	in.	to	ft.	
	WELL WATER TO BE USED AS: 9. Dewatering 11. Injection well 1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 12. Other (Specify below)								
1. Domestic 3. Feedot 5. Public water supply 12. Other (Specify below) 2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well									
Was a chemical/bacteriological sample submitted to Department?  Was a chemical/bacteriological sample submitted to Department?  Was Water Well Disinfected?  YES  NO  NO  NO  NO  NO  NO  NO  NO  NO  N									
5 TYPE OF CASING USED:			0.04		·		=		
TYPE OF CASING USED:  1. Steel 3. RPM (SR)  5. Wrought Iron 7. Fiberglass 9. Other (Specify below) CASING JOINTS: Glued Threaded SDR-26  SDR-26									
2. PVC 4. ABS 6. Asbestos-Cement 8. Concrete tile SDR-26									
Blank casing diameter 5		t., Dia.	in.	to	ft., D	ia.	in. to	ft.	
Casing height above land surface:	12 in.,	Weight:	<b>2.35</b> lb	s. / ft.	Wall thic	kness or gauç	ge No214		
TYPE OF SCREEN OR PERFORATION MATERIAL:  1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)									
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)  2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:									
	Il slot 5. Gauzed	wrapped	7. Tor	ch cut	9. Drille	d holes	11. None ( o	pen hole)	
2. Louvered shutter 4. Ke	y punched 6. Wire wra	pped	8. Sav	w cut	10. Other	(specify)			
SCREEN - PERFORATION INTERVA	AL From 40	ft. to	100	ft.,	From	ft.	to	ft.	
	From	ft. to		ft.,	From	ft.	to	ft.	
GRAVEL PACK INTERVALS	S: From <b>24</b>	ft. to	100	ft.,	From	ft.	to	ft.	
	From	ft. to		ft.,	From	ft.	to	ft.	
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hole plug						10			
						ft.			
What is the nearest source of possible contamination:  1 Septic tank 4 Lateral lines 7. Pit privy			D. Livestoci	restock pens 13. Insecticide storage 15. Oil well/Gas well					
1. Septic tank 4. Lateral lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below							ecify below)		
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage									
Direction from well? West					How man	y feet? 50 1			
From To	LITHOLOGIC LOG	3	From	То		LITHOLO	OGIC LOG		
0 4 topsoil 4 18 clay									
4 18 clay 18 80 shale									
80 97 limestone								1	
				<u> </u>					
								11 100	
	W # E 10 0 E								
							70		
7 Contractor's or Landowner's Co	edification. This water well was	1 Constructed	) 2. red	constructed	or 3, p	ugged	under my jurisdict	ion and	
Contractor's or Landowner's Certification: This water well was 1. Constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 9/21/2007 and this record is true to the best of my knowledge and belief.									
under the business name of Harp Well and Pump Service by (signature) Todd S. Havp									