			Form WWC-	5 Di			ources; App. No.		
1 LOCATIO	ON OF V	VATER WELL:	Fraction	ess. V	Section N	lumber	Township Numbe	r Range N	lumber
Distance and	direction	from nearest town	nw ¼ ne ¼ or city street address o	fwell if (Global Po	sitionin	System (decimal de	K Ze	£/V
located within	city?	nom nearest town	or city street address o	1 WCII II	Latitude:	31110111113	g System (decimal de	igiees, min. o	i 4 digits
2538 rosemo									
2 WATER WELL OWNER: Paul Graf						:			
RR#, St. Address, Box # : 2538 Rosemont					Danim.				
City, State	, ZIP Coo	le : Wichita	, Ks 67235		Data Coll	ection N	/lethod:		
3 LOCATE	WELL'	S 4 DEPTH OF	COMPLETED WEL	LL 67			ft.		
LOCATO	N								
WITH A	N "X" IN	Depth(s) Groun	dwater Encountered 1			ft. 2	ft.	3	ft.
SECTION	N BOX:	WELL'S STAT	dwater Encountered 1 IC WATER LEVEL	29 f	t. below la	nd surfa	ice measured on mo	/dav/vr	
XN		Pump	test data: Well water	was	ft.	after	hours pum	ping	gpm
^		Est. Yield 25	test data: Well water gpm: Well water	was	ft	after	hours num	ning	onm
	- NE -	- IWELL WATER	CTO BE USED AS⊂5	Public w	ater sunnis	√ RAi	r conditioning 11	Injection we	3
'	7	1 Domestic 3	Feed lot Oil field	water sun	alv. supp.,	9 Dew	atering 12 O	ther (Specify	/ helow)
w x		E 2 Irrigation 4	Industrial Domestic	: (lawn &	garden)	10 Mon	itoring well	mer (Speeny	, ocion,
, , , ,	- sE			(<i>B</i>)				
		Was a chemical	/bacteriological sample	e submitte	d to Denai	tment?	Ves No v	· If yes mo/	daylyre
S		Sample was sul	omitted	c suommic	a to Depai	Water W	ell Disinfected? V	, if yes, mon	May/yrs
5 TYPE OF	CASING	G USED: 5	Wrought Iron	8 Concre	ete tile	CAS	ING JOINTS: Glue	d x Clam	ped
Steel	3	KMP(SR) = 6	Asbestos-Cement	9 Other (specify be	elow)	Weld	ded	
Q PVC	4	ABS 7	Fiberglass				Thre	aded	
Blank casing	diameter	5 in. to	27 ft., Dia		in. to	ft.,	Dia i	n. to	ft.
Casing height	above lar	id surface 12	Fiberglass 27 ft., Dia in., Weight	2.40	lbs.	/ft. Wal	I thickness or gauge	No. 16	0psi
TYPE OF SC	REEN OF	R PERFORATION	MATERIAL: erglass PVC						
1 Steel	3 Stainle	ess steel 5 Fib	erglass PVC	9 A	ABS		11 Other (specify),.,.	
SCREEN OR	4 Gaiva	nized steel 6 Col LAZION OPENINO	ncrete tile 8 RM (SR	() 10 A	isbestos-C	ement	12 None used (op	en hole)	
1 Contin	nous slot	3) Mill slot	JO ANE. 5. Guaze wranned	7 Torc	h cut	9 Drill	ed hales 11 Nar	ne (onen hole	a)
2 Louve	red shutte	r 4 Kev punche	5 Guaze wrapped d 6 Wire wrapped	8 Saw	Cut	10 Othe	r (specify)	ic (open note	•)
SCREEN-PEI	RFORAT	ED INTERVALS:	From 27	ft. to	67	ft. Fro	om ft.	to	ft
			From	ft. to		ft Fro	om ft	to	ft
GRAV	EL PACK	INTERVALS:	From 29	ft to	67	ft Fr	om ft	to	A
		Tivi Bit vii Bo.	From	ft to		ft Fr	om f	to	ft.
(CDOUT!	4 A TERRIT	4.8 1.3V	From ent 2 Cement grout	···			Jiii 1t.		16.
6 GROUIT	MATERI	AL: I Neat cem	ent 2 Cement grout	Bento	onite 4	4 Other			
Grout Interval	s Froi	m 3 n. to	29 ft. From	ft.	to	ft.	From	ft. to	ft.
	_	rce of possible con					=		
1 Septic to				10 Livesto	-		ecticide Storage	16 Other (
Sewer li		5 Cess pool		II Fuel st			indoned water well	below))
Direction from		lines 6 Seepage p					well/ gas well		
				How many					
	ТО		OGIC LOG	FROM	TO		PLUGGING INT	ERVALS	
0		op soil							
7		lay							
	67 L	imestone							
				- 		<u> </u>			
				-		-			
				 					
			R'S CERTIFICATION	N: This v					
			no/day/year) <u>7-27-07</u>				true to the best of my	~	nd belief.
		ctor's License No.				om plete d	on (mo/day/year)	8-10-07)
		f Weninger Drill		by (signat	·		->-		<u></u> .
INSTRUCTION	S: Please fi	ll in blanks or circle the	correct answers. Send top t	hree copies t	o Kansas De	partment o	of Health and Environme	nt, Bureau of W	Vater,
your records. Fee	of \$5.00 fo	r each constructed well	opeka, Kansas 66612-1367. Visit us at http://www.kdh	i eiepnone 7 eks.gov/wate	ъэ-296-5522 :rwell.	. Send on	ie to WATER WELL OV	VNEK and retain	n one for
··· ·· · · · · · · · · · · · · · · · ·									