WATER WELL RECORD F	orm WWC-5 K	SA 82a-1212	
1 LOCATION OF WATER WELL: FRACTION SE	SECTION NUMBER		RANGE NUMBER
Sedgwick SW 1/4 SW 1/4 NW	1/4 8	T 27 S	R 2E E/W
Distance and direction from nearest town or city street address of well if located within city?  8203 Steeple Chase Wichita, Kansas			
2 WATER WELL OWNER: VEREEKE, David			
RR#,ST. ADDRESS,BOX #: 8203 Steeple Chase		Board of Agr	iculture, Division of Water Resource
CITY, STATE: Wichita, Kansas	ZIP CODE:	Application Nur	nber:
3 LOCATE WELL'S LOCATION 4 DEPTH OF COMPLETED WELL: 98	ft.	ELEVATION:	
Depth of groundwater Encountered:	ft.	ft.	ft.
WELL'S STATIC WATER LEVEL 40	FT. BELOW LAND SU	JRFACE MEASURED ON mo/o	day/yr: 11/8/07
Pump test data: Well wat			of pumping @ gpm
Est. Yield: gpm Well wat Bore Hole Diameter 12 in.	er was to <b>98</b> ft.		s of pumping @ gpm to ft.
WELL WATER TO BE USED AS:	10 20 11.	9. Dewateri	44
	er supply 🦪 Lawn a	and garden only	12. Other (Specify below)
2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well  Was a chemical/hacteriological sample submitted to Department?  VES NO ; If yes, what mo/day/yr was sample			
S Was a chemical/bacteriological sample submitted to D submitted		NO ; if yes, 'Vater Well Disinfected?	YES NO
5 TYPE OF CASING USED: 5 Wrought Iron 7 Fiberglass	9. Other (Specify	below) CASING JOINTS: (	Glued Threaded
1. Steel 3. RPM (SR)	SDD 26	55.511,	Welded Clamped
2. PVC 4. ABS 6. Asbestos-Cement 8. Concrete til	C		
Blank casing diameter 5 in. to 28 ft., Dia.	in. to	ft., Dia.	in. to ft.
	<b>2.35</b> lbs. / ft.	Wall thickness or gaug	ge No214
TYPE OF SCREEN OR PERFORATION MATERIAL:  1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC	9. ABS	11. Other (specify)	
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR)	10. Asbestos-Cer	nent 12. None used (open	hole)
SCREEN OR PERFORATION OPENINGS ARE:			
1. Continuous slot 3. Mill slot 5. Gauzed wrapped	7. Torch cut	9. Drilled holes	11. None ( open hole)
2. Louvered shutter 4. Key punched 6. Wire wrapped	8. Saw cut	10. Other (specify)	
SCREEN - PERFORATION INTERVAL From 28 ft. to	98 ft.,	From ft.	to ft.
From ft. to	ft.,	From ft.	to ft.
GRAVEL PACK INTERVALS: From 24 ft. to	98 ft.,	From ft.	to ft.
From ft. to	ft.,	From ft.	to ft.
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout	3. Bentonite	Other bent	onite hole plug
Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From 25 ft. to 28 ft.			
What is the nearest source of possible contamination:  1. Septic tank  4. Lateral lines  7. Pit privy	0. Livestock pens	13. Insecticide storage	15. Oil well/Gas well
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below)			
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage			
Direction from well? South		How many feet? 10 t	
From To LITHOLOGIC LOG	From To	LITHOLO	GIC LOG
0 4 topsoil 4 15 clay			
15 20 fine sand		·	
20 50 soft shale			
50 98 shale and limestone	<u> </u>	<del></del>	
100000000000000000000000000000000000000			
	<del>                                     </del>		
7 Contractor's or Landowner's Certification: This water well was 1. constructed	2 reconstructed	or 3. plugged	under my jurisdiction and
11.0.0007			
14.0000			
under the business name of Harp Well and Pump Service by (signature) Todd S. Harp			