		WATER W	ELL REC	CORD	Form W\	NC-5 K	SA 82a-	1212					
1 LOCATION OF WATER V	WELL:	FRACTION NE 4/4 NIX				TION NUMBE	,	TOWNSHIP NUMBER			RANGE NUMBER		
Sedgwick Distance and direction from n	pearest town or city s	SW 1/4		1/4 NW	1/4	11	<u> </u>	27 5	<u> </u>	R	2E	E/W	
1910 N. Glenwo	•		hita, Kan	•									
2 WATER WELL OW		HIE BUILD											
RR#,ST. ADDRESS,B0		E. 22nd St. N	N. Buildi	ng 1000				Boa	rd of Agricultu	re, Division	of Wat	er Resource	
CITY, ST		ita, Kansas				IP CODE:		Applica	tion Number:				
3 LOCATE WELL'S LOCA WITH AN "X" IN SECTION	ATION 4 D	EPTH OF COMP	PLETED WE	LL: {	35 ft.		ELEVATIO	N:					
N	Dep	th of groundwater			f			ft				ft.	
		LL'S STATIC WA				DW LAND S				•	1/30/		
1 1 1	NE	Pui Est. Yield:	mp test data		ater was ater was		ft. after ft. after		hours of p	, , ,	_	gpm	
W Wile	Е Во	ore Hole Diameter	gpm r 12	in.	to	85 ft			hours of p in.	oumping (to	_	gpm ft.	
-	' I I	LL WATER TO B						9 D	ewatering	-	_	on well	
sw	SE 1.	Domestic 3.	Feedlot			7. Lawn		only	ū	12. Othe	-	cify below)	
		•	Industrial	6. Oil field		_			onitoring ware on the second of the second o		hir was	e eamnle	
S		as a chemical/bacte mitted	riological samp	ole submitted to	Department?	YES Was \	NO Water Well D		YE		NO		
5 TYPE OF CASING	G USED:	5. Wrought	Iron	7. Fiberglas	9. C	ther (Specify	/ below)	CASING JO	INTS: GI	lued	Т	hreaded	
1. Steel	3. RPM (SR)) -		Ü	כם	R-26	,,		_	elded	C	Clamped	
2. PVC	4. ABS	6. Asbestos		8. Concrete	ule								
Blank casing diameter		n. to	45 ft.,	Dia.	in.	to	ft.,	Dia.	in.	to		ft.	
Casing height above la		12 in.,		Weight:	2.35	lbs. / ft.	Wa	all thickness	or gauge N	o. .2	214		
TYPE OF SCREEN OR 1. Steel 3. S	Stainless Steel	5. Fiberglass		7. PVC	9. A	ABS	11	. Other (spe	cify)				
	Salvanized	6. Concrete T	Tile	8. RMP (SR)	10. /	Asbestos-Cei		. None used	• •	a)			
SCREEN OR PERFORA	ATION OPENING	S ARE:											
1. Continuous slot	3. Mill slo	t 5. (Gauzed wra	pped	7. T c	orch cut	9. I	Drilled hole	s	11. Non	е (оре	en hole)	
2. Louvered shutter	4. Key pu	nched 6. V	Wire wrappe	ed	(8. S a	aw cut	10.	Other (spec	cify)				
SCREEN - PERFORATION	ON INTERVAL	From	45 f		o 85	ft.,	From			4		4	
JOOKEEN TENTONATIO	OIVIIVIERVAL	From			0	ft.,	From	f		to		ft.	
GRAVEL PACK	INTERVALS:	From	24 ft		to 85	ft.,	From	f		to to		ft. ft.	
		From	ft		0.0	ft.,	From	f					
6 GROUT MATERIAL	S: 1. Neat c		2. Ceme			3. Bentonite	***************************************	Other	bentoni	to holo	nlua	ft.	
<u>ы</u>	From 4	ft. to	2. Cemer 24 ft.		ft.		ı ft.			ft.	to	ft.	
What is the nearest source	•	7	Dit meion	,				,					
1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Ga													
2. Sewer lines	5. Cess Po		Sewage la	goon	11. Fuel sto	•	14. Ab	andon wate	er well	io. Other	(spec	ily below;	
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer Direction from well? East							Hov	v many feet	2 10 ft. r	alus			
From To		ITHOLOGIC	CLOG		From	То			HOLOGI		}		
	psoil												
	ay				 	1							
11 85 gı	ray shale						ij.						
							:						
					 	 				····			
						 							
			~ ``										
						-							
		· · · · · · · · · · · · · · · · · · ·											
7 Contractor's or Lan	downer's Certifica	ation: This water	well was 1.0	constructe	d) 2. re	constructed	or 3.	plugge	d unde	er my juris	sdiction	n and	
was completed on (mo	o/day/year)	11-30-2007	7 а	nd this record	I is true to th	e best of my	knowledge a	and belief.					
Kansas Water Well Co		e No. 236				as completed	•		12/3/20	07			
under the business na			nn Servic			ignature)					d'h		
	rraih A	· · · · · · · · · · · · · · · · · · ·			-, (Todi	N 3. 1	πw	ν		