WATER WELL RECORD	Form WWC-5 K	SA 82a-1212	
1 LOCATION OF WATER WELL: FRACTION	SECTION NUMBER		RANGE NUMBER
Sedgwick NE 1/4 NW 1/4 S	SE 1/4 1	T 27 S	R 2 E E/W
Distance and direction from nearest town or city street address of well if located within city?			
2326 N. Chelmsford Wichita, Kansas			
2 WATER WELL OWNER: INK-DRUMWRIGHT			
RR#,ST. ADDRESS,BOX #: P.O. Box 780427		Board of Agri	iculture, Division of Water Resource
CITY, STATE: Wichita, Kansas	ZIP CODE:	Application Nun	nber:
3 LOCATE WELL'S LOCATION 4 DEPTH OF COMPLETED WELL:	123 ft.	ELEVATION:	
WITH AN "X" IN SECTION BOX:	ft.	ft.	ft.
Depth of groundwater Encountered:			
WELL'S STATIC WATER LEVEL 50		RFACE MEASURED ON mo/o	day/yr: 1/18/08
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	ell water was		s of pumping @ gpm
	ell water was	ft. after hours	s of pumping @ gpm
	to 123 ft.	and in.	to ft.
WELL WATER TO BE USED AS:		9. Dewateri	ng 11. Injection well
	ic water supply 7. Lawn a		12. Other (Specify below)
	eld water supply 8. Air con	15	ng well what mo/day/yr was sample
S Was a chemical/bacteriological sample submitted		/ater Well Disinfected?	YES NO
			\geq
TYPE OF CASING USED: 5. Wrought Iron 7. Fiberg	glass 9. Other (Specify	below) CASING JOINTS: (Glued Threaded
	rete tile SDR-26	s*	Welded Clamped
7. ABS			
Blank casing diameter 5 in. to 53 ft., Dia	in. to	ft., Dia.	in. to ft.
Casing height above land surface: 12 in., Weight	: 2.35 lbs. / ft.	Wall thickness or gaug	ge No214
TYPE OF SCREEN OR PERFORATION MATERIAL:			
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC	9. ABS	Other (specify)	
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cer	nent 12. None used (open	hole)
SCREEN OR PERFORATION OPENINGS ARE:			
1. Continuous slot 3. Mill slot 5. Gauzed wrapped	7. Torch cut	9. Drilled holes	11. None (open hole)
			Tit Hone (open note)
2. Louvered shutter 4. Key punched 6. Wire wrapped	8. Saw cut	10. Other (specify)	
SCREEN - PERFORATION INTERVAL From 53 ft.	to 123 ft.,	From ft.	to ft.
From ft.	to ft.,	From ft.	to ft.
24	,		
1	,	From ft.	to ft.
From ft.	to ft.,	From ft.	to ft.
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout	3. Bentonite	Other bent	onite hole plug
Grout Intervals: From 4 ft. to 24 ft., From	rom ft. to	ft., From	ft. to ft.
What is the nearest source of possible contamination:		·	
1. Septic tank 4. Lateral lines 7. Pit privy	10. Livestock pens	13. Insecticide storage	15. Oil well/Gas well
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below)			
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage			
Direction from well? East		How many feet? 10 1	ft. plus
From To LITHOLOGIC LOG	From To		OGÍC LOG
0 4 topsoil	110	2020	70.0 200
4 18 clay		· · · · · · · · · · · · · · · · · · ·	
18 123 shale			
Contractor's or Landowner's Certification: This water well was 1. constru	ucted 2. reconstructed	or 3, plugged	under my jurisdiction and
was completed on (mo/day/year) 1-18-2008 and this record is true to the best of my knowledge and belief.			
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 1-21-2008			
under the business name of Harp Well and Pump Service by (signature) Todd S. Horb			