WATER WELL RECORD	Form WWC-5	KSA 82a-1212	
1 LOCATION OF WATER WELL: FRACTION	SECTION NUMBI		RANGE NUMBER
Sedgwick NE 1/4 NW 1/4 SE Distance and direction from nearest town or city street address of well if located within city?	1/4 1	T 27 S	R 2E E/W
Reserve B. Monarch Landing Wichita, K	ancac .	v.	
2 WATER WELL OWNER: RITCHIE DEVELOPMENT	4113413		
RR#,ST. ADDRESS,BOX #: 8100 E. 22nd N. Bldg. 1000		Board of Ag	riculture, Division of Water Resource
CITY, STATE: Wichita, Kansas	ZIP CODE:	Application Nu	mber:
3 LOCATE WELL'S LOCATION 4 DEPTH OF WITH AN "X" IN SECTION BOX:	15 ft.	ELEVATION:	
Depth of groundwater Encountered:	ft.	ft.	ft.
WELL'S STATIC WATER LEVEL 50		SURFACE MEASURED ON mo/	day/yr: 1/29/08
Pump test data: Well wa			s of pumping @ gpm
E Para Hala Diameter in	ater was to	ft. after hour	s of pumping @ gpm to ft.
WELL WATER TO SED AS:	10	9. Dewater	44 Intention well
1. Domestic 3. Feedlot 5. Public wa	ater supply 7. Lawn	and garden only	12. Other (Specify below)
		onditioning 10. Monitori	ng well what mo/day/yr was sample
S Was a chemical/bacteriological sample submitted to submitted	,	NO ; If yes, Water Well Disinfected?	YES NO
TYPE OF CASING USED: 5. Wrought Iron 7. Fiberglass	9. Other (Speci	fy below) CASING JOINTS:	Glued Threaded
1. Steel 3. RPM (SR)			Welded Clamped
2. PVC 4. ABS 6. Asbestos-Cement 8. Concrete to			
Blank casing diameter 5 in. to ft., Dia.	in. to	ft., Dia.	in. to ft.
Casing height the total and surface: 36 in., Weight:	lbs. / ft.	Wall thickness or gau	ge No.
TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC	9. ABS	11. Other (specify)	N/A
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR)	10. Asbestos-Co	ement 12. None used (oper	hole)
SCREEN OR PERFORATION OPENINGS ARE:			
1. Continuous slot 3. Mill slot 5. Gauzed wrapped	7. Torch cut	9. Drilled holes	11. None (open hole)
2. Louvered shutter 4. Key punched 6. Wire wrapped	8. Saw cut	10. Other (specify) N	J/A
SCREEN - PERFORATION INTERVAL From ft. to	o ft.,	From ft.	to ft.
From ft. to	,	From ft.	to ft.
GRAVEL PACK INTERVALS: From ft. to		From ft.	to ft.
From ft. to		From ft.	to ft.
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout	3. Bentonii		tonite hole plug
Grout Intervals: From ft. to ft., From	ft. to		• •
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7. Pit privy	10. Livestock pens	:	15. Oil well/Gas well
9 Coware larger	11. Fuel storage	13. Insecticide storage	48. Other (annulf : balance)
2. Sewer mies 0. Substituti	12. Fertilizer storage	14. Abandon water well	None Apparent
3. Watertight sewer line 6. Seepage pit 9. Feed yard Direction from well?	12. Pertinzer storage	How many feet?	• • • • • • • • • • • • • • • • • • • •
From To LITHOLOGIC LOG	From To	<u> </u>	OGIC LOG
	0 3	compacted clay	
	3 23	bentonite hole plug	
	23 115	chlorinated gravel	
	 		
	+ +		
Contractor's or Landowner's Certification: This water well was 1. constructed	d 2. reconstructe	ed or 3. plugged	under my jurisdiction and
was completed on (mo/day/year) 1-29-2008 and this record is true to the best of my knowledge and belief.			
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 2-8-2008			
under the business name of Harp Well and Pump Service by (signature) Todd S. Harb			