								242		
1 LOCATION OF WAT	ER WELL:	WATER WI	ELL REC	ORD Fo		ON NUMBE	SA 82a-1	212 SHIP NUMBER	RANGE N	UMBER
Sedgwick	CIV WELL.	NW 1/4	NW 1/4	4 SE	1/4	2	T	27 s	R 21	
Distance and direction from	om nearest town or cit	y street address of well	if located within	city?			-			
13508 Ayesb		Wichita,		YON						
2 WATER WELL		ENTZEL CON		ION			*	Board of Agr	riculture, Division of \	Water Resource
RR#,ST. ADDRES		0 W. 21st St. N chita, Kansas	., Suite F		715	CODE:	•	Application Nur	mher	
3 LOCATE WELL'S L	1.	DEPTH OF COMP	ETED WELL	. 87	ft.	CODE.	ELEVATIO		71001.	
WITH AN "X" IN SE	CTION BOX:	epth of groundwater			ft.	•		ft.		ft.
lı r		VELL'S STATIC WA				W LAND S	URFACE MEA	ASURED ON mo/	day/yr: 2/2	7/08
NW -	NE	Pun	np test data:	Well wate	r was		ft after	hours	s of pumping @	gpm
W Wile		Est. Yield:	gpm	Well water		_	ft. after	hour	s of pumping @	gpm
	X	Bore Hole Diameter	12	in.	to 8	7 f	t. and	in.	to	ft.
) sw		VELL WATER TO BI 1. Domestic 3.		5. Public wate	er supply '	7. Lawn	and garden o	9. Dewater	iiig ,	ection well specify below)
		2. Irrigation 4.		6. Oil field wa				10. Monitori		pecity below,
\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \		Was a chemical/bacter				YES	· NO		what mo/day/yr	was sample NO
E TYPE OF CA	SING USED:	ubmitted				-	Water Well Di		\sim	
5 TYPE OF CA	3. RPM (S	5. Wrought	Iron 7	7. Fiberglass		her (Specif	y below) (CASING JOINTS:	Glued Welded	Threaded Clamped
2. PVC	A. ABS	6. Asbestos	-Cement 8	3. Concrete tile	, SDF	R-26			Weided	Clamped
Blank casing diame	ter 5	in. to	40 ft.,	Dia.	in.	to	ft.,	Dia.	in. to	ft.
Casing height above	e land surface:	12 in.,		Weight: 2	2.35 lb	s. / ft.	. Wa	II thickness or gau	ge No214	ļ
TYPE OF SCREEN	OR PERFORATIO	N MATERIAL:								
1. Steel	3. Stainless Steel	5. Fiberglass	_	PVC	9. Ai			Other (specify)		
2. Brass	4. Galvanized	Concrete T	ile 8	. RMP (SR)	10. A	sbestos-Ce	emeņt 12.	None used (open	n hole)	
SCREEN OR PERF			.		7.7.			مدادها الدادم	44 Nana/	anan hala\
1. Continuous slo			Sauzed wrap			rch cut		Orilled holes	11. None (open hole)
2. Louvered shut	ter 4. Key	punched 6. V	Vire wrapped	i	8. Sa	w cut	. 10.0	Other (specify)		
SCREEN - PERFOR	RATION INTERVAL	From	40 ft.	to	87	ft.,	From	ft.	to	ft.
Ì		From	ft.	to		ft.,	From	ft.	to	ft.
GRAVEL P	ACK INTERVALS:	From	24 ft.	to	87	ft.,	From	ft.	to	ft.
		From	ft.	to		ft.,	From	ft.	to	ft.
6 GROUT MATER	RIALS: 1. Nea	t cement	2. Cement	Grout	3	B. Bentonit	e į	Other ben	tonite hole pl	lug
Grout Intervals:	From 4	•	24 ft.,	From	ft.	to	ft.,	From	ft. to	ft.
What is the nearest : 1. Septic tank	source or possible of 4. Later	7	Pit privy	10	. Livestoc	k pens	13. Ins	ecticide storage	15. Oil well/	Gas well
2 Sewer lines	5. Cess	•	Sewage lag	oon 11	l. Fuel sto	rage	14. Ab	andon water well	16. Other (s	pecify below)
3. Watertight sew	ver line 6. Seep	page pit 9.	Feed yard	12	2. Fertilizer	storage				
Direction from well?	0 4						Hov	many feet? 65		
From To		LITHOLOGIC	LOG		From	То		LITHOLO	OGIC LOG	
0 4	topsoil						1			
4 15 15 80	clay shale						36			
80 87	limestone									
	_					-				
							+:			
							3			
							1			
	_									
						-				
7 Contractor's o	r Landowner's Cert	ification: This water	well was 1.C	constructed) 2. re	constructe	ed or 3.	plugged	under my jurisdi	ction and
was completed or		2-27-2008				hest of m	v knowledge a	and belief.		

Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 2/29

under the business name of Harp Well and Pump Service

by (signature) '

Todd S. Harp