	WATER WELL RE	CORD Fo	rm WW	C-5 K	SA 82a-121	2				
1 LOCATION OF WATER WELL:	FRACTION		SECTI	ON NUMBER	TOWNSHIP	NUMBER	RANGE NUI	MBER .		
☐ Sedgwick	NE 1/4 NW		1/4	1	T 27	s	R 2E	E/W		
Distance and direction from nearest town or city street address of well if located within city?										
15402 E. Camden Chase Ct		Kansas		<u> </u>						
	Board of Angle, the on Division of Mater Dage							ter Resource		
	****					board of Agriculture, Division of Water Nessource				
	T	100		CODE:		Application Num	nber:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	DEPTH OF COMPLETED W	ELL: 122	ft.		ELEVATION:					
	oth of groundwater Encounte	red:	ft.			ft.		ft.		
	ELL'S STATIC WATER LEVE	EL 50 1	FT. BELOV	W LAND SU	JRFACE MEASU	RED ON mo/d	lay/yr: 3/6/0)8		
N V- NE	Pump test dat	ta: Well water	r was		ft. after	hours	of pumping @	gpm		
₩ E B	Est. Yield: gpm	Well wate	r was		ft. after	hours	of pumping @	gpm		
	ore Hole Diameter 12	in.	to 12	22 ft.	and	in.	to	ft.		
	ELL WATER TO BE USED A				and mandan and	9. Dewaterii	ng 11. Inject	tion well		
	12. Other (Specify below)									
	Irrigation 4. Industrial						ng well what mo/day/yr wa	as sample		
	/as a chemical/bacteriological sar bmitted	npie submitted to De	partment?	YES Was V	NO Water Well Disinf		YES N			
5 TYPE OF CASING USED:			0.04				Glued	Threaded		
1. Steel 3. RPM (SR)										
2. PVC 4. ABS	Asbestos-Cement	Concrete tile	SDR	R-26			***************************************	Ciamped		
Blank casing diameter 5	in. to 52 ft.,	Dia.	in.	to	ft.,	Dia.	in. to	ft.		
Casing height above land surface:	12 in.,	Weight: 2	35 Ib	e /ft	Wall th	ckness or gaug	ne No. 214			
Casing height above land surface: 12 in., Weight: 2.35 lbs. / ft. Wall thickness or gauge No214 TYPE OF SCREEN OR PERFORATION MATERIAL:										
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)										
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)										
SCREEN OR PERFORATION OPENINGS ARE:										
1. Continuous slot 3. Mill sl		• •		ch cut	9. Drii	ed holes	11. None (o	oen noie;		
2. Louvered shutter 4. Key p	unched 6. Wire wrap	ped	8. Sav	v cut	10. Oth	er (specify)				
SCREEN - PERFORATION INTERVAL	From 52	ft. to	122	ft.,	From	ft.	to	ft.		
	From	ft. to		ft.,	From	ft.	to	ft.		
GRAVEL PACK INTERVALS:	From 24	ft. to	122	ft.,	From	ft.	to	ft.		
		ft. to	122	-						
	From	π. το		ft.,	From	ft.	to	ft.		
GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hole plug						g				
Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft.								ft.		
What is the nearest source of possible co	7 Diá mais a c	10	. Livestoci	k pens	13. Insecti	cide storage	15. Oil well/G	as well		
Septic tank 4. Lateral lines 9. Severe levels 11. Eval storage 4. Lateral lines 9. Severe levels 11. Eval storage 4. Lateral lines 9. Severe levels 11. Eval storage 4. Lateral lines 9. Severe levels 11. Eval storage 4. Lateral lines 9. Severe levels 11. Eval storage 11. Eval st							cify below)			
2. Sewer lines 5. Cess Pool 5. Sevinge rageon 1. Total State of the Control of th										
Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage Direction from well? North How many feet? 20 ft. plus										
	LITHOLOGIC LOC		From	To .	now ma		OGIC LOG			
	LITHOLOGIC LOG		From	То		LITHOLC	JGIC LOG			
0 4 topsoil 4 25 clay										
25 115 shale										
115 122 limestone										
				•	•					
				`,						
				1						
				ļ	1					
				 			i.			
7 Contractor's or Landowner's Certifi	cation. This water well was	Constructed) 2	constructe	d or 3,	plugged	under my jurisdicti	on and		
							ander my jurisdicti	on and		
was completed on (mo/day/year)	3/6/2008	and this record is			-					
Kansas Water Well Contractor's Licen	se No. 236	This water wel	I record wa	s complete	d on (mo/day/yea	or) 3/10	0/2008			
under the business name of Harp Well and Pump Service by (signature) Todd S. Harp										
1	•				,		μ			