WATER WELL RECORD	Form WWC-5 KSA 82a-1212
1 LOCATION OF WATER WELL: FRACTION	SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER
Sedgwick NW 1/4 NW 1/4 SE	1/4 2 T 27 S R 2E E/W
Distance and direction from nearest town or city street address of well if located within city? 13604 E. Boxthorn Wichita, Kansas	
2 WATER WELL OWNER: NIES CONSTRUCTION	
RR#,ST. ADDRESS,BOX #: 10333 E. 21st N. #303	Board of Agriculture, Division of Water Resource
CITY, STATE: Wichita, Kansas	ZIP CODE: Application Number:
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	8 ft. ELEVATION:
Depth of groundwater Encountered:	ft. ft. ft.
WELL'S STATIC WATER LEVEL 45	FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 3/13/08
	ater was . • • ft. after hours of pumping @ gpm
	ater was ft. after hours of pumping @ gpm
Bore Hole Diameter 12 in. WELL WATER TO BE USED AS:	to 98 ft. and in. to ft.
	ater supply 7. Lawn and garden only 9. Dewatering 11. Injection well 12. Other (Specify below)
2. Irrigation 4. Industrial 6. Oil field	water supply 8. Air conditioning 10. Monitoring well
S Was a chemical/bacteriological sample submitted to submitted	Department? YES NO ; If yes, what mo/day/yr was sample Was Water Well Disinfected? YES NO
5 TYPE OF CASING USED:	CACINIC IONITS (Clud) Threeded
1. Steel 3. RPM (SR) 5. Wrought Iron 7. Fiberglas	o, olio, (open, color,)
2. PVC 4. ABS 6. Asbestos-Cement 8. Concrete	
Blank casing diameter 5 in. to 45 ft., Dia.	in. to tt., Dia. in. to ft.
Casing height above land surface: 12 in., Weight:	2.35 lbs. / ft. Wall thickness or gauge No214
TYPE OF SCREEN OR PERFORATION MATERIAL:	44.00 (20.00%)
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC	9. ABS 11. Other (specify)
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR)	10. Asbestos-Cement 12. None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped	7. Torch cut 9. Drilled holes 11. None (open hole)
2. Louvered shutter 4. Key punched 6. Wire wrapped	8. Saw cut 10. Other (specify)
1.5	o 98 ft., From ft. to ft.
	o ft., From ft. to ft.
GRAVEL PACK INTERVALS: From 24 ft.	to $oldsymbol{98}$ ft., From ft. to ft.
From ft.	to ft., From ft. to ft.
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout	3. Bentonite Other bentonite hole plug
Grout Intervals: From 4 ft. to 24 ft., From What is the nearest source of possible contamination:	ft. to ft., From ft. to ft.
1. Septic tank 4. Lateral lines 7. Pit privy	10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well
2. Sewer lines 5. Cess Pool 8. Sewage lagoon	11. Fuel storage 14. Abandon water well 16. Other (specify below)
3. Watertight sewer line 6. Seepage pit 9. Feed yard	12. Fertilizer storage
Direction from well? North	. How many feet? 10 ft. plus
From To LITHOLOGIC LOG	From To LITHOLOGIC LOG
0 4 topsoil 4 15 clay	
4 15 clay 15 70 shale	
70 98 limestone	
	
Contractor's or Landowner's Certification: This water well was 1. construct	2. reconstructed or 3. plugged under my jurisdiction and
was completed on (mo/day/year) 3/13/2008 and this record	d is true to the best of my knowledge and belief.
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 3/17/2008	
under the business name of Harp Well and Pump Service by (signature) Todd S. Harp	
in p it of and I dillp bet the	i uwu si tiwi p