	WATER WELL F	RECORD	Form WV	VC-5 K	SA 82a-12	212				
1 LOCATION OF WATER WELL:	FRACTION SE SW SW NE			SECTION NUMBE				RANGE NUMBER		
Sedgwick	1/4 89A		1/4	8	<u> </u>	2 7 S	R	2E E	-M	
Distance and direction from nearest town or city 1805 N. Paddock Green	wichita, l	•								
	UYEN, Jimmy	Xansas								
	5 N. Paddock Green	1				Board of Ag	griculture, Division	of Water R	esource	
1	hita, Kansas		· z	IP CODE:		Application No	ımber:			
3 LOCATE WELL'S LOCATION 4	DEPTH OF COLUMN	WELL: 1	00 ft.		ELEVATION	:				
WITH AN "X" IN SECTION BOX:	epth of groundwater Encou	intered:	; ft			ft.			ft.	
	VELL'S STATIC WATER LE	EVEL 15	FT. BELC	W LAND SU	JRFACE MEA	SURED ON mo	/day/yr: 3	3/28/08		
NE	Pump test	data: Well w	ater was		ft. after	hou	rs of pumping (<u>D</u>	gpm	
W Hill	Est. Yield: gp		ater was		ft. after	hou	rs of pumping (_	gpm	
	Bore Hole Diameter VELL WATER 1€ 16 USEI	in.	to	ft	. and	in.	to		ft.	
	1. Domestic 3. Feedle		ater supply	7. Lawn	and garden o	9. Dewate	9	Injection v r (Specify		
	2. Irrigation 4. Indust		water supply	8. Air co	nditioning	10. Monitor		(Specify	Delow	
	Was a chemical/bacteriological	sample submitted to	Department?	YES	NO		what mo/day/	•	ımple	
5 TYPE OF CASING USED:	ubmitted			Was	Water Well Dis		(YES)	NO		
1. Steel 3. RPM (S	5. Wrought Iron	7. Fiberglas	s 9. O	ther (Specify	below) C.	ASING JOINTS:	Glued Welded		aded	
2. PVC 4. ABS	6. Asbestos-Ceme	nt 8. Concrete	tile				vveided	Clan	nped	
Blank casing diameter 5	in. to	ft., Dia.	in.	to	ft.,	Dia.	in. to		ft.	
Casing height apply and surface:	36 in.,	Weight:	i	bs. / ft.	Wall	thickness or gau	ge No.			
TYPE OF SCREEN OR PERFORATIO	N MATERIAL:					•	37/A			
1. Steel 3. Stainless Steel	5. Fiberglass	7. PVC	9. A	BS		Other (specify)				
2. Brass 4. Galvanized	6. Concrete Tile	8. RMP (SR)	10. A	sbestos-Ce	ment 12.	None used (oper	n hole)			
SCREEN OR PERFORATION OPENIN										
1. Continuous slot 3. Mill s		• • •		rch cut		rilled holes		e (open h	iole)	
2. Louvered shutter 4. Key p	ounched 6. Wire wi	rapped	8. S a	w cut	10. O	ther (specify) 1	N/A			
SCREEN - PERFORATION INTERVAL	From	ft. t	0	ft.,	From	ft.	to		ft.	
1	From	ft. t	0	ft.,	From	ft.	to		ft.	
GRAVEL PACK INTERVALS:	From	ft.	to	ft.,	From	ft.	to		ft.	
	From	ft.	to	ft.,	From	ft.	to		ft.	
6 GROUT MATERIALS: 1. Neat	cement 2. C	ement Grout		3. Bentonite	1	Other ben	tonite hole	plug		
Grout Intervals: From	ft. to	ft., From	ft.	to	ft.,	From	3 ft.	to 40	ft.	
What is the nearest source of possible control 1. Septic tank 4. Latera	7 D#	ivy	10. Livestoo	k pens	13. inse	cticide storage	15. Oil w e	ell/Gas we	ell	
1. Copie talk				1. Fuel storage 14. Abandon water well 16. Other (specify below)						
3. Watertight sewer line 6. Seepa		vard	12. Fertilize	r storage						
Direction from well? North	-90 Pit			•	How	many feet? 12	5			
From To	LITHOLOGIC LO	3	From	То		LITHOL	OGIC LOG	i		
			0	3	compacted					
			3	100	bentonite					
			40	100	well grave					
								-		
			-							
			-							
7 Contractor's or Landowner's Certif	fication: This water well wa	s 1. constructe	ed 2. re	constructed	or 3. <	plugged	under my juris	diction an	ıd	
was completed on (mo/day/year)	3/28/2008	and this record								
Kansas Water Well Contractor's Licer				•	•		1/2008			
under the business name of Harp	wen and rump Se	rvice	by (S	gnature)	,	oaas	s. Hau	TD		