			WATER W	VELL RECC	ORD F	orm WW	C-5 K	SA 82a-1212	·			
1'1	LOCATION OF WATER WELL: FRACTION Sedgwick NW 1/4 SE 1/4 NW						ION NUMBER			1	RANGE NUMBER	
			NW 1/4			1/4	11	Т 27	S	R 2E	E/W	
Distance and direction from nearest town or city street address of well if located within city? 13210 E. Reeds Cove Wichita, Kansas												
2 WATER WELL OWNER: AYRES, Clint												
\mathbf{L}	RR#,ST. ADDRESS,BOX #: 13210 E. Reeds Cove Board of Agriculture, Division of Water Resou											
	CITY,	STATE: W	ichita, Kansas			ZII	P CODE:		Application Nur	mber:		
3 LOCATI	E WELL'S LO	CATION	4 DEPTH OF COM	PLETED WELL	: 95	ft.		ELEVATION:				
MTH A	N "X" IN SEC		Depth of groundwate	er Encountered:		ft.			ft.		ft.	
	I F		WELL'S STATIC W	ATER LEVEL	40	FT. BELOV	W LAND SU	JRFACE MEASUR	ED ON mo/c	day/yr: 4/24	/08	
Pump test data: Well water was ft. after hours of pumping @										gpm		
w <u>⊠</u>	^	;	Est. Yield:	gpm	Well water	_	_	ft. after	hour	s of pumping @	gpm	
≥ w		E	Bore Hole Diamete		in.	to 9	95 ft.	. and	in.	to	ft.	
	WELL WATER TO BE USED AS: 9. Dewatering 11. Injection 12. Other (Specific Variety of the control of the contr											
	2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well											
' -	Was a chemical/bacteriological sample submitted to Department? YES NO ; If yes, what mo/day/yr was sample											
submitted Was Water Well Disinfected? YES NO												
TYPE OF CASING USED: 5. Wrought Iron 7. Fiberglass 9. Other (Specify below) CASING JOINTS: Glued Threaded												
1. Steel 3. RPM (SR) 2. PVC 4. ABS 6. Asbestos-Cement 8. Concrete tile SDR-26 Welded Clamped												
_	ing diamete	_	in. to	45 ft.,	Dia.	in.	to	ft., D	ia.	in. to	ft.	
ı	-	_	10					,			IL.	
1	•	e land surface:	IZ in., ION MATERIAL:		Weight: 2	2.35 lb	os. / ft.	Wall thic	kness or gaug	ge No214		
1. Stee		3. Stainless Stee		s 7.	PVC	9. AE	BS	11. Othe	er (specify)			
	2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)											
SCREEN	OR PERFO	RATION OPEN	JINGS ARE:									
	nuous slot			Gauzed wrapp	oed	7. To r	rch cut	9. Drille	d holes	11. None (o	pen hole)	
1	ered shutte			Wire wrapped		(8. Sav		10, Other	r (specify)			
l .						95			• • • • • • • • • • • • • • • • • • • •			
SCREEN -	PERFURA	ATION INTERVA		45 ft.	to	95	ft.,	From	ft.	to	ft.	
			From	ft.	to	05	ft.,	From -	ft.	to	ft.	
٥	RAVEL PAG	CK INTERVALS		24 ft.	to .	95	ft.,	From -	ft.	to	ft.	
			From	ft.	to		ft.,	From	ft.	to	ft.	
<u> </u>	UT MATERI	1. 140	eat cement	2. Cement		3	Bentonite	,	Other bent	tonite hole plu	ıg	
	Intervals:	From	4 ft. to e contamination:	24 ft.,	From	ft.	to	ft.,	From	ft. to	ft.	
1. Septie			e contamination. teral lines	7. Pit privy	10	0. Livestoci	k pens	13. Insectic	ide storage	15. Oil well/G	as well	
2. Sewe				8. Sewage lago	oon 1	1. Fuel stor	rage	14. Abando	n water well	16. Other (sp	ecify below)	
l	rtight sewe	_		9. Feed yard	1:	2. Fertilizer	storage					
	from well?	Northe	east					How man	ny feet? 10		<u></u>	
From	То		LITHOLOGI	C LOG		From	То		LITHOLO	OGIC LOG		
0	4	topsoil				\vdash						
10	18	clay										
18 80	80 95	shale limestone										
-	ļ									,		
7 Con			"f - " - This make							- de como bodo dist		
10.10000												
was completed on (mo/day/year) 4/24/2008 and this record is true to the best of my knowledge and belief.												
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 4/28/2008												
under the business name of Harp Well and Pump Service by (signature) Todd S. Harb)	