	WATER WELL R	ECORD F	orm WW	C-5 K	SA 82a-1212	2			
1 LOCATION OF WATER WELL:				ION NUMBER		TOWNSHIP NUMBER		RANGE NUMBER	
Sedgwick	NE 1/4 NW	1/4 SE	1/4	1	T 27	S	R 2E	E/W	
Distance and direction from nearest town or city street address of well if located within city? 15418 Camden Chase Wichita, Kansas									
2 WATER WELL OWNER: SHARP CONSTRUCTION									
	Board of Agriculture Division of Water Resource								
	usta, Kansas		ZIF	CODE:		Application Num	nber:		
	DEPTH OF COMPLETED V	WELL: 95	ft.		ELEVATION:				
WITH AN "X" IN SECTION BOX:	epth of groundwater Encount	tered:	ft.			ft.		ft.	
	/ELL'S STATIC WATER LE\	/EL 45	FT. BELO	W LAND SU	RFACE MEASUR	ED ON mo/d	lay/yr: 6/12/	08	
NW - NE	Pump test d	ata: Well wate	r was		ft. after	hours	of pumping @	gpm	
	Est. Yield: gpm				ft. after	hours	of pumping @	gpm	
		2 in.	to 9	5 ft.	and	in.	to	ft.	
-	WELL WATER TO BE USED AS: 9. Dewatering 11. Injection well								
	1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 12. Other (Specify below) 2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well								
Was a chemical/bacteriological sample submitted to Department? YES NO ; If yes, what mo/day/yr was sample									
	ubmitted			Was V	vater Well Disinfe	cted? (YES N	<u> </u>	
5 TYPE OF CASING USED:	5. Wrought Iron	7. Fiberglass	9. Ot	her (Specify	below) CASI	NG JOINTS: (Threaded	
1. Steel 3. RPM (SR) Welded Clamped 2. PVC 4. ABS 6. Asbestos-Cement 8. Concrete tile SDR-26									
2. PVC 4. ABS Blank casing diameter 5		t., Dia.	in.	to	ft., D	ia.	in. to	ft.	
	12 in.,								
Casing height above land surface: 12 in., Weight: 2.35 lbs. / ft. Wall thickness or gauge No214 TYPE OF SCREEN OR PERFORATION MATERIAL:									
1. Steel 3. Stainless Steel	5. Fiberglass	7. PVC	9. Al	38	11. Oth	er (specify)			
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:									
						11. None (o	en hole)		
2. Louvered shutter 4. Key p	ounched 6. Wire wra	pped	8. Sa	w cut	10. Other	(specify)			
SCREEN - PERFORATION INTERVAL	From 55	ft. to	95	ft.,	From	ft.	to	ft.	
SCREEN-PERIORATION INTERVAL	From	ft. to	,,	ft.,	From	ft.	to	ft.	
GRAVEL PACK INTERVALS:	From 24	ft. to	95	ft.,	From	ft.	to	ft.	
GRAVEE FACILITY ETCALES.	From	ft. to	,,	ft.,	From	ft.	to		
6 GROUT MATERIALS: 1 Next				·				f'	
. Heat certain cloth							_		
What is the nearest source of possible contamination:				ft. to ft., From ft. to ft.					
1. Septic tank 4. Lateral lines 7. Pit privy 10). Livestoc		13. Insectic	13. Insecticide storage 15. Oil well/Gas well			
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below)								city below)	
3 Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage									
Direction from well? South	LITUOLOGIO LOG		-	T-	How mar	y feet? 10 f			
From To	LITHOLOGIC LOG		From	То	···	LITHOLC	OGIC LOG		
0 4 topsoil 4 15 clay									
15 95 shale									
							···		

7 Contractor's or Landowner's Certi	fication: This water well was	1. constructed) 2. re	constructed	or 3. p	lugged	under my jurisdicti	on and	
was completed on (mo/day/year) 6-12-2008 and this record is true to the best of my knowledge and belief.									
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 6-13-2008									
under the business name of Harp Well and Pump Service by (signature) Todd S. Harp									