		WATER WE	LL RECORD	Form WV	/C-5 K	SA 82a-121	2			
1 LOCATION OF WATER WELL: FRACTION			SECT	ION NUMBER	1			JMBER		
Sedgwick NE 1/4 SE 1/4 SE Distance and direction from nearest town or city street address of well if located within city?			1/4	1	T 27	7 s	R 21	E/W		
1										
2323 Flutter I		Wichita, Ka				•				
	WATER WELL OWNER: SHARP CONSTRUCTION R#.ST. ADDRESS.BOX #: Board of Agriculture, Division of Water Resource									
RR#,ST. ADDRESS	71	B 00DE								
		gusta, Kansas	=======================================		P CODE:	EL ELIATION:	Application Num	ber:		
3 LOCATE WELL'S LO WITH AN "X" IN SEC	CTION BOX:	DEPTH OF COMPL				ELEVATION:				
N N	I	epth of groundwater f		ft.			ft.		ft.	
		VELL'S STATIC WAT			W LAND SU	JRFACE MEASU				
NW	NE			ater was		ft. after		of pumping @	gpm	
M Mile		Est. Yield: Bore Hole Diameter	gpm Well v 12 in.	vater was to 1	12 ft.	ft. after and	in.	of pumping @ to	gpm ft.	
- "	1 1	VELL WATER TO BE		10 1	1.2	and		44 1.1	ction well	
sw	SE 1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 12. Other (Specify below									
	\sim	2 Irrigation 4. I	ndustrial 6. Oil field	water supply	8. Air cor	ditioning	10. Monitorin	g well		
Was a chemical/bacteriological sample submitted to Department? YES NO ; If yes, what mo/day/yr was sample										
submitted Was Water Well Disinfected? YES NO										
5 TYPE OF CAS	SING USED: 3. RPM (S	5. Wrought In	ron 7. Fiberglas	9. O	ther (Specify	below) CAS	ING JOINTS: (Glued	Threaded	
2. PVC	3. KFW (3	6. Asbestos-	Cement 8. Concrete	tile SDI	R-26			Welded	Clamped	
Blank casing diamete	_		5 ft., Dia.	in.	to	ft.,	Dia. i	n. to	ft.	
1	-		,			,				
Casing height above land surface: 12 in., Weight: 2.35 lbs. / ft. Wall thickness or gauge No214										
TYPE OF SCREEN C	3. Stainless Steel	5. Fiberglass	7. PVC	9. A	BS	11. Oth	ner (specify)			
7. 5.55.	I. Galvanized	6. Concrete Til	e 8. RMP (SR) 10. A	sbestos-Cer		ne used (open	hole)		
SCREEN OR PERFORATION OPENINGS ARE:										
1. Continuous slot			auzed wrapped	7 To	rch cut	9 Drille	ed holes	11. None (d	open hole)	
									, po,	
2. Louvered shutte	er 4. Key p	punched 6. W	ire wrapped		w cut	10. Otne	er (specify)			
SCREEN - PERFORA	ATION INTERVAL	From	45 ft.	to 112	ft.,	From	ft.	to	ft.	
		From	ft.	to	ft.,	From	ft.	to	ft.	
GRAVEL PA	CK INTERVALS:	From	24 ft.	to 112	ft.,	From	ft.	to	ft.	
		From	ft.	to	ft.,	From	ft.	to	ft.	
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hole plug									Πά	
Grout Intervals: From 4 ft. to 24 ft From ft. to ft., From ft. to									ft.	
What is the nearest so	ource of possible of	contamination:	0							
1. Septic tank 4. Lateral lines 7. Pit privy 10.). Livestock pens		13. Insecticide storage 15. Oil well/Gas well 14. Abandon water well 16. Other (specify below)			
2. Sewer lines	5. Cess	Pool 8.	Sewage lagoon	11. Fuel sto	rage	14. Aband	on water well	٠,	• .	
3. Watertight sewe	er line 6. Seep.	age pit 9.	Feed yard	12. Fertilize	r storag e			None Ap	parent	
Direction from well?			1.00		· -	How ma	any feet?	010100		
From To		LITHOLOGIC	LOG	From	То		LITHOLO	GIC LOG		
0 4	topsoil				ļ					
4 25 25 95	clay soft shale									
95 112	shale and lin	nestone								
	J									
	-					<u> </u>				
7 Contractor's or	Landowner's Certi	ification: This water v	vell was 1. construct	ed 2. re	constructe	d or 3.	plugged	under my jurisdic	tion and	
was completed on	(mo/day/year)	6-11-2008	and this reco	rd is true to the	e best of my	knowledge and t	belief.			
· ·		ense No. 236				-		-2008		
under the business name of Harp Well and Pump Service by (signature) Todd S. Horb										