	WATER WELL F	RECORD FO	orm WW	C-5 K	SA 82a-1212	2			
LOCATION OF WATER WELL: FRACTION Sedgwick SW 1/4 SE 1/4 SE		- 1	SECTION NUMBER		TOWNSHIP NUMBER		RANGE NUMBER		
Sedgwick  Distance and direction from nearest town or			1/4	8	T 27	S	R 2E	E/W	
1400 N. Foliage Dr.	Wichita, Kan	•							
2 WATER WELL OWNER: FOLIAGE HOA									
RR#,ST. ADDRESS,BOX #: 1710 Duckcross Cove  Board of Agriculture, Division of Water Resource									
	ichita, Kansas			CODE:		Application Num	nber:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED	WELL: 90	ft.		ELEVATION:				
	Depth of groundwater Encou		ft.			ft.		ft.	
	WELL'S STATIC WATER LI			V LAND SU	RFACE MEASUR		• •	_	
NW	Pump test Est. Yield: ap				ft. after		of pumping @	gpm	
W Wile		m Well wate ${f 12}$ in.	erwas to 90	0 ft.	ft. after and	nours in.	s of pumping @ to	gpm ft.	
[	WELL WATER TO BE USE	D AS:				9. Dewateri	44 1.14		
swse									
	2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well  Was a chemical/bacteriological sample suppritted to Department? VES NO ; if yes, what mo/day/yr was sample								
S	Was a chemical/bacteriological submitted	sample submitted to De	epartment?	YES Was W	NO Vater Well Disinfe		YES NO	•	
5 TYPE OF CASING USED:	5 Wrought Iron	7 Fiberaless	9. Ot			NG JOINTS: (	Glued	Threaded	
1. Steel 3. RPM (SR) Welded Clamped									
2. PVC 4. ABS	6. Asbestos-Ceme		9 501	C-20					
Blank casing diameter 5	in. to 30	ft., Dia.	in.	to	ft., D	ia.	in. to	ft.	
Casing height above land surface:	12 in.,	Weight:	<b>2.35</b> lb	s. / ft.	Wall thic	kness or gau	ge No214		
TYPE OF SCREEN OR PERFORATION MATERIAL:  1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)									
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)  2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)									
( )									
SCREEN OR PERFORATION OPENINGS ARE:  1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None ( open hole)									
2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify)									
						(specify)			
SCREEN - PERFORATION INTERV			90	ft.,	From	ft.	to	ft.	
	From	ft. to	00	ft.,	From	ft.	to	ft.	
GRAVEL PACK INTERVALS	_		90	ft.,	From	ft.	to	ft.	
	From	ft. to		ft.,	From	ft.	to	ft.	
GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hole plug									
Grout Intervals: From What is the nearest source of possible	4 ft. to 24 le contamination:	ft., From	ft.	to	ft.,	From	ft. to	ft.	
1. Septic tank 4. Lateral lines 7. Pit privy				estock pens 13. Insecticide storage 15. Oil well/Gas well			s well		
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below)							cify below)		
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage									
Direction from well? Southw					How mai	ny feet? 50			
From To topsoil	LITHOLOGIC LO	G	From	То		LITHOLO	OGIC LOG		
0 4 topsoil 4 20 clay								-	
20 80 shale				•					
80 90 shale and	lime								
					·				
			<b></b>						
				<b></b>	·				
		-							
				1					
Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and									
was completed on (mo/day/year) 7/3/2008 and this record is true to the best of my knowledge and belief.									
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 7/7/2008									
under the business name of Harp Well and Pump Service by (signature) Todd S. Horb									